PRACTICAL 8A:

INPUT::

bindu@Bindusree: ~

GNU nano 8.7.1 practical8a.c

```c
#include <stdio.h>
#include <stdlib.h>

int main()
{
    int *a, *b;

    a = (int*)malloc(5 * sizeof(int));

    b = (int*)calloc(5, sizeof(int));

    a = (int*)realloc(a, 10 * sizeof(int));

    free(a);
    free(b);

    return 0;
}
```

OUTPUT::

```
bindu@Bindusree:~$ nano practical8a.c
bindu@Bindusree:~$ gcc practical8a.c -o practical8a
bindu@Bindusree:~$ ./practical8a
bindu@Bindusree:~$ nano practical8a.c
bindu@Bindusree:~$ ./practical8a
bindu@Bindusree:~$
```

PRACTICAL 8B::

INPUT::

bindu@Bindusree: ~

GNU nano 8.7.1 practical8b.c

```c
#include <stdio.h>
#include <unistd.h>

int main()
{
    int x = 100;

    if (fork() == 0)
    {
        printf("Child Before=%d\n", x);
        x = 500;
        printf("Child After=%d\n", x);
    }
    else
    {
        sleep(2);
        printf("Parent=%d\n", x);
    }

    return 0;
}
```

OUTPUT:

```
bindu@Bindusree:~$ nano practical8b.c
bindu@Bindusree:~$ ./practical8b
Child Before=100
Child After=500
Parent=100
bindu@Bindusree:~$
```