

11.To Store Commands, Maintain History Buffer, Handle Capacity Limits, Retrieve Entries, Display History, Validate Consistency.

To Create Pipeline Structures, Store Commands, Maintain Execution Order, Connect Processes, Validate Pipeline Layout, Test Configurations.

```
bindu@Bindusree:~$ nano skill11.c
bindu@Bindusree:~$ gcc skill11.c -o skill11
bindu@Bindusree:~$ ./skill11
Simple Command History
Type 'history' to display commands
Type 'exit' to quit

shell> ls
shell> pwd
shell> date
shell> history
Command History:
1  ls
2  pwd
3  date
shell> history
Command History:
1  ls
2  pwd
3  date
shell>
```

```

#include <stdio.h>
#include <string.h>

#define MAX_HISTORY 10
#define MAX_CMD 100

int main() {
    char history[MAX_HISTORY][MAX_CMD];
    char command[MAX_CMD];
    int count = 0;

    printf("Simple Command History\n");
    printf("Type 'history' to display commands\n");
    printf("Type 'exit' to quit\n\n");

    while (1) {
        printf("shell> ");
        fgets(command, MAX_CMD, stdin);

        command[strcspn(command, "\n")] = '\0';

        if (strcmp(command, "exit") == 0)
            break;

        if (strcmp(command, "history") == 0) {
            printf("\nCommand History:\n");

            for (int i = 0; i < count; i++) {
                printf("%d %s\n", i + 1, history[i]);
            }

            continue;
        }

        if (strlen(command) == 0)
            continue;
    }
}

```

```
        continue;
    }

    if (strlen(command) == 0)
        continue;

    if (count < MAX_HISTORY) {
        strcpy(history[count], command);
        count++;
    } else {
        for (int i = 0; i < MAX_HISTORY - 1; i++)
            strcpy(history[i], history[i + 1]);

        strcpy(history[MAX_HISTORY - 1], command);
    }
}

return 0;
}
```