



SECTION A-A

- NOTE:  
ELECTICAL  
1. CURRENT RATING:2.2 A PER PIN  
(2 ADJACENT PINS POWERED)  
2.INSULATOR MATERIAL:BLACK LCP  
3.VOLTAGE RATING:250 VAC  
4.INSULATION RESISTANCE 500MEGA OHMS MIN.  
5.AT 100 VDC PHYSICAL  
6.CONTACT: COPPER ALLOY  
7.OPERATING TEMPERATURE:-55°C TO +125°C

L B 1 0 9 0 - G \* \* - B \* R

PACKING: R:REEL  
0:WITH POSITIONING POSTS  
1:WITHOUT POSITIONING POSTS  
COLOR:BLACK

PIN

PLATING: G:GOLD FLASH  
1:CONTACT AREA PLATING 3u"Min GOLD.  
F:CONTACT AREA PLATING 10u"Min GOLD.

HEIGHT:90-9.04H

1:1.0 BTB

LXWCONN BTB CONNECTOR SERIES



制图 (DR): Jerry 2022.10.10		品名(TITLE): MEC1 1.0mm			
审核 (CHKD):		料号(PART NO): LB1090-G**-B*R			
核准 (APPD): Tong 2022.10.10		比例(SCALE): 1 : 1	单位(UNITS): mm	张数(SHEET): 1 OF 1	图幅(SIZE): A4

修订 SER	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE	版本 (REV)	A	一般公差 GENERAL TOLERANCE .X ±0.35 .XX ±0.01 .XXX ±0.05 .000 ±0.005 ANGLES ±2°
-----------	------------------------------	-----------------	------------	-------------	---	---