



- ### ■ Specifications :
- Voltage rating: 250V AC / DC
 - Current rating: 3A AC / DC
 - Withstanding voltage: 1000V AC/minute
 - Temperature range: -25°C~+85°C
 - Insulation resistance:≥1000MΩ
 - Contact resistance: ≤10mΩ
 - After environmental testing: ≤20mΩ
 - Material(Pin):Brass
 - Mates With C/ST Housing:2501HG-K

2501 W R X-XX K-660 L XX

- ①
- ②
- ③
- ④
- ⑤
- ⑥
- ⑦
- ⑧
- ⑨

① Series No.

② Category: W-WAFER

③ Welding Board Angle: R-Right Angle 90°

④ Welding Way: Blank-DIP

⑤ Row No.-Pin No.: XX-Single Row ;

⑥ Special No.: K-With Lock

⑦ Material: 660-PA66 94V-0

⑧ Plating Category: L-Bright Tin Plating

⑨ Color : Blank-Natural Color

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
02	2.50	7.50	12	27.50	32.50
03	5.00	10.00	13	30.00	35.00
04	7.50	12.50	14	32.50	37.50
05	10.00	15.00	15	35.00	40.00
06	12.50	17.50	16	37.50	42.50
07	15.00	20.00	17	40.00	45.00
08	17.50	22.50	18	42.50	47.50
09	20.00	25.00	19	45.00	50.00
10	22.50	27.50	20	47.50	52.50
11	25.00	30.00			

[illegible]