Card Stop List Export

Contents

CHAPTER 1. CARD STOP LIST EXPORT

2

Chapter 1. Card Stop List Export

The Card Stop List Export file contains information on blocked cards. The file is outgoing of WAY4.

The files are generated in the ASCII format. The length of each record is 185 bytes including 2 bytes of the line delimiter (CRLF). Each line of the file contains a single message. The following types of messages are stored in the file: the file header, the file footer, the transaction messages. The header comes first in the file, whereas the footer is the last message.

The formats of the file fields are as follows:

- is a numeric field containing only digits; the field is right-aligned and it should to be appended with leading zeros to reach the specified length.
- an is a character field containing any printable characters; the field is leftaligned, it should be appended with trailing blanks to reach the specified length.
- JJJ is a date, where JJJ represent the day number of the year (ranging from 001 to 366).
- YYMM is a date, where YY – represent the last two digits of the year number $(00 \dots 99)$ and MM – the month of the year $(01 \dots 12)$.
- is a date, where YYYY represent the year YYYYMMDD (0000 ... 9999), MM – the month of the year (01 ... 12) and DD – the day of the month (01 ... 31).
- **HHMISS** is time, where HH is the hour (00 ... 23), MI is the minute $(00 \dots 59)$, SS – is the second $(00 \dots 59)$.
- is a binary field only used to store line delimiter characters.

Money amounts are stored in the minimal units (cents, pennies ...).

The flags specifying if the entry of data in the field is mandatory, are as follows:

- **M** the entry of data is mandatory,
- the entry of data is optional,
- the entry of data depends on values specified in the other fields.

If no data is stored in the field, it has to be filled with space characters (blanks).

The file name format is as follows:

| N | Field | Pos | Len | M/O | Format | Comments |
|----|-----------------------|-----|-----|-----|--------|--|
| 1. | File Name Prefix | 1 | 5 | М | an | "STP_F" / "STP_U" |
| 2. | Delimiter | 6 | 1 | М | an | "_" (one <underscore> character).</underscore> |
| 3. | File Number | 7 | 2 | М | n | The file number in the current day. |
| 4. | Delimiter | 9 | 1 | М | an | "" " |
| 5. | File Creation Date | 10 | 3 | М | JJJ | File creation date. |

The file header format is as follows:

| T | The the header format is as follows. | | | | | | |
|-----|--------------------------------------|-----|-----|-----|------------------|---|--|
| N | Field | Pos | Len | M/O | Format | Comments | |
| 1. | Row Code | 1 | 2 | М | an | "FH" | |
| 2. | Row Number | 3 | 6 | М | n | The line number in the file (000001 - is assigned to the header). | |
| 3. | File Label | 9 | 10 | М | an | "STOP LIST" | |
| 4. | Version | 19 | 3 | М | an | "10 " | |
| 5. | Reserved | 22 | 6 | М | an | To be filled with spaces. | |
| 6. | File Creation Date | 28 | 8 | М | YYYY MMD D | The date when the file was created. | |
| 7. | File Creation Time | 36 | 6 | М | HHMI SS | The time when the file was created. | |
| 8. | File Number | 42 | 4 | М | n | The file number in the current day. Right-aligned, padded with leading zeroes. | |
| 9. | List Type | 46 | 1 | М | an | "F" – Full stop-list."U" – Stop-list changes. | |
| 10. | Previous Update Date | 47 | 8 | М | YYYY MMD D | Date when the previous file was created. | |
| 11. | Previous Update Number | 55 | 4 | М | n | The previous file number in its day. Right-aligned, padded with leading zeroes. | |
| 12. | Reserved | 59 | 124 | М | an | To be filled with spaces | |
| 13. | Terminal Symbol | 183 | 1 | М | an | " * " | |
| 14. | Delimiter | 184 | 2 | М | b | 0x0D, 0x0A (CRLF) | |

The file footer format is as follows:

| N | Field | Pos | Len | M/O | Format | Comments |
|----|------------|-----|-----|-----|--------|------------------------------|
| 1. | Row Code | 1 | 2 | М | an | "FT" |
| 2. | Row Number | 3 | 6 | М | n | The line number in the file. |

| N | Field | Pos | Len | M/O | Format | Comments |
|----|--------------------|-----|-----|-----|--------|----------------------------------|
| 3. | Number of Records | 9 | 6 | М | n | Quantity of records in the file. |
| 4. | Reserved | 15 | 168 | М | an | To be filled with spaces. |
| 5. | Terminal Symbol | 183 | 1 | М | an | (i ★?) |
| 6. | Delimiter | 184 | 2 | М | b | 0x0D , 0x0A (CRLF) |

The format of transaction messages is as follows:

| N | Field | Pos | Len | M/O | Format | Comments |
|-----|-----------------------------|-----|-----|-----|--------|---|
| 1. | Row Code | 1 | 2 | М | an | "RD" |
| 2. | Row Number | 3 | 6 | М | n | The line number in the file |
| 3. | Operation | 9 | 1 | М | an | "A" – The card is added to the stop-list "D" – The card is removed from the stop-list. |
| 4. | Range Type | 10 | 1 | М | an | "C" – Single card."R" – Range of card numbers. |
| 5. | Card Number | 11 | 24 | С | an | Single card number. |
| 6. | Card Range Low Boundary | 35 | 24 | С | an | Low range of card numbers. |
| 7. | Card Range High Boundary | 59 | 24 | С | an | High range of card numbers. |
| 8. | Reserved | 83 | 100 | М | an | To be filled with spaces. |
| 9. | Terminal Symbol | 183 | 1 | М | an | " * " |
| 10. | Delimiter | 184 | 2 | М | b | 0x0D , 0x0A (CRLF) |