

Reflective Journal: Bias-Variance Tradeoff

Course: ITAI1371

Lab Assignment: Lab 08

Group ID: ML_1371_12321_9

Student: Cuong Dang

Date: July 25, 2026

1. Core Technical Insights and Learning Progress

This laboratory provided a profound bridge between textbook theory and practical machine learning engineering. By implementing Polynomial Regression across varying degrees (1, 4, and 15) against a noisy synthetic sine wave, I visually mapped the math behind the Bias-Variance Tradeoff.

Key Observations:

- **The Inflexible Boundary (Degree 1):** This model showcased high bias. A straight line is structurally incapable of capturing non-linear signals, causing both Training and Validation learning curves to merge permanently at a critically low baseline performance of R-squared approximately equal to 0.26.
- **The Over-Parameterized Trap (Degree 15):** This model demonstrated extreme variance. The algorithm utilized its excess degrees of freedom to memorize localized Gaussian noise. While it achieved a flawless training score of 1.00, its cross-validation curve cratered at a poor 0.55 to 0.60, showcasing a catastrophic generalization gap of roughly 0.40 to 0.45.
- **The Reality of Irreducible Error:** I discovered why perfect real-world generalization caps at approximately 0.90 instead of 1.00. Since our noise standard deviation was injected at 0.5, the irreducible variance (0.25) acts as a permanent lower bound on total Mean Squared Error (MSE), setting a natural optimization ceiling that no algorithm can bypass.

2. Critical Thinking and Code Hygiene Practices

During the laboratory setup, I encountered an architectural pattern where the raw data array was re-assigned to satisfy Scikit-Learn requirements using the syntax `X = X[:, np.newaxis]`.

Reflective Realization: In strict computer science practice, overwriting the primary variable destroys the original 1D array, creating mutable dependency risks for subsequent visualizations.

Engineering Fix: While I kept the original variable structure to perfectly preserve the professor's template structure and prevent script execution errors, I documented it explicitly with code comments. In professional practice, generating a decoupled 2D array or a dense plotting array (200 points) is highly superior for smooth curve plotting because it captures high-frequency polynomial oscillations that a sparse 100-point original array skips over entirely.

3. High-Level Implications: The Y2K Paradox of Autonomous AI

The most impactful takeaway of this lab extended beyond static charts into the philosophy of continuous, autonomous machine learning. If an AI system—such as a self-driving robot—is allowed to train continuously on live data streams without a hardcoded termination threshold, it faces severe systemic risks.

First, it triggers Model Collapse. Feeding an automated system infinite loops of real-world or synthetic noise force a high-degree algorithm to hallucinate non-existent rules. It begins treating dust particles or random shadows as absolute physical barriers, destroying its spatial reasoning.

Second, it reveals the critical need for a Mathematical Handbrake. We cannot simply upgrade processing chips to handle endless complexity. True AI control requires strict structural constraints. By monitoring the output of the `plot_learning_curve` function, we can engineer

automated validation checks to trigger an immediate Early Stopping sequence. This forces the training process to halt, permanently locking the autonomous agent within a safe, predictable, and aligned operational sweet spot.

4. Personal Action Plan for Future Modeling

Moving forward into advanced machine learning architectures, I will enforce a Safety-First, Baseline-First workflow:

- Never start with deep, hyper-flexible models. I will always initialize a rigid, high-bias baseline model first to benchmark the underlying data profile.
 - Mandatory Cross-Validation. I will actively implement K-Fold cross-validation loops (such as 5 x 5 Repeated K-Fold) to guarantee that any performance boost is statistically stable, and not a byproduct of lucky data splits.
 - Aggressive Quantifiable Metrics. I will always evaluate my systems using exact empirical data and performance intervals rather than relying on abstract, qualitative trend interpretations.
-