



Pin connection diagram for the KH-2.54FH-1X15P-H8.3KH-2.54FH-1X15P-H8.5 module. The diagram shows two 15-pin headers, P3 and P4, connected to a 3V power source and GND. Pin 1 of P3 is connected to 3V, and Pin 15 of P4 is connected to GND. Other pins are connected to GND or are unconnected. The module is labeled KH-2.54FH-1X15P-H8.3KH-2.54FH-1X15P-H8.5.

Diagram showing the pin connections for the B7B-XH-A(LF)(SN) component. The component has a 7-pin header labeled P5. The connections are as follows:

- Pin 1: 3V3
- Pin 2: IRQ
- Pin 3: ABO
- Pin 4: SCL
- Pin 5: SDA
- Pin 6: AB1
- Pin 7: GND

Red 'X' marks are present on the ABO, SCL, and AB1 lines, indicating a connection error or conflict.

Pin connection diagram for B6B-XH-A(LF) (SMD):

- Pin 1: 3V3
- Pin 2: SCL
- Pin 3: SDA
- Pin 4: CSB
- Pin 5: SDO
- Pin 6: GND

Title		
Size C	Number	Revision
Date:	6/15/2026	Sheet of
File:	D:\FIRMWARE\Sheet1.Sch	Drawn By: