

Bioconductor's nnNorm package

Laurentiu A. Tarca¹

March 30, 2005

1. CRBF, Laval University, CANADA, <http://www.crbf.ulaval.ca>

1 Overview

The **nnNorm** package contains mainly a function for intensity and spatial normalization of cDNA two color data, or paired single channel data, based on neural networks fitting. Functionality to compare the distributions of the normalized log ratios is also provided. For the simpler case when only intensity normalization is performed (univariate distortion color model), we provide functionality to plot the bias estimates against the level of intensity for each print tip group on the slide. This document provides only a basic introduction to the **nnNorm** package. A more extended description is available in the **nnNormGuide.pdf** document. For a detailed description of the principles and algorithmic implemented by this package consult Tarca et al. (2005).

We demonstrate the functionality of this package using the swirl data set from the **marray** package. To load the swirl dataset in a object called **swirl** of type **marrayRaw** we use the following lines:

```
> library(marray)
> data(swirl)
```

Now we perform normalization with the method **maNormNN** available in the **nnNorm** package. This function returns a **marrayNorm** object (containing the normalized log ratios).

```
> library(nnNorm)
> swirl_n1 <- maNormNN(swirl[, 1])
```

If data is available in a **RGList** or **MAList** object (see **limma** package) they can be easily converted to a **marrayRaw** object using functionality of the library **convert**. For more details on the **nnNorm** package Please consult **nnNormGuide.pdf**.

References

A. L. Tarca, J. E. K. Cooke, and J. Mackay. Robust neural networks approach for spatial and intensity dependent normalization of cDNA data. *Bioinformatics*. (accepted), 2005.