

HOWARD Help

Contents

1	Introduction	3
2	QUERY tool	3
2.1	Main options	3
2.2	Explode	4
2.3	Query	4
2.4	Export	4
3	FILTER tool	5
3.1	Main options	5
3.2	Filters	5
3.3	Export	5
4	SORT tool	6
4.1	Main options	6
4.2	Export	6
5	STATS tool	6
5.1	Main options	6
5.2	Stats	7
6	CONVERT tool	7
6.1	Main options	7
6.2	Explode	8
6.3	Export	8
7	HGVS tool	8
7.1	Main options	9
7.2	HGVS	9
8	ANNOTATION tool	10
8.1	Main options	10
8.2	Annotation	12
9	CALCULATION tool	12
9.1	Main options	13
9.2	Calculation	13
9.3	NOMEN	13
9.4	TRIO	13
9.5	BARCODEFAMILY	14
10	PRIORITIZATION tool	14
10.1	Main options	14
10.2	Prioritization	14
11	PROCESS tool	15
11.1	Main options	15
11.2	HGVS	16

11.3 Annotation	17
11.4 Calculation	17
11.5 Prioritization	17
11.6 Query	18
11.7 Explode	18
11.8 Export	18
11.9 Chunking	19
12 DATABASES tool	19
12.1 Main options	20
12.2 Genomes	20
12.3 snpEff	21
12.4 Annovar	21
12.5 refSeq	21
12.6 dbNSFP	22
12.7 AlphaMissense	23
12.8 Exomiser	23
12.9 dbSNP	24
12.10HGMD	25
12.11from_Annovar	25
12.12from_extann	26
12.13Parameters	27
13 GUI tool	27
14 HELP tool	27
14.1 Main options	27
15 UPDATE_DATABASE tool	28
15.1 Main options	28
15.2 Update_database	28
15.3 Options	29
16 TO_EXCEL tool	29
16.1 Main options	29
16.2 Add	29
17 TRANSCRIPTS_CHECK tool	29
17.1 Main options	30
18 GENEBE tool	30
18.1 Main options	30
18.2 GeneBe	30
18.3 Explode	31
18.4 Export	31
19 MINIMALIZE tool	31
19.1 Main options	32
19.2 Minimalize	32
19.3 Explode	32
19.4 Export	33
20 BIGWIG tool	33
20.1 Main options	33
20.2 Options	33
21 Shared arguments	34

1 Introduction

Usage examples:

```
howard process --input=tests/data/example.vcf.gz --output=/tmp/example.annotated.vcf.gz --param=config/param.json
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.vcf.gz --annotations='tests/databases/an
howard calculation --input=tests/data/example.full.vcf --output=/tmp/example.calculation.tsv --
calculations='vartype'
howard prioritization --input=tests/data/example.vcf.gz --output=/tmp/example.prioritized.vcf.gz --
prioritization_config=config/prioritization_profiles.json --prioritizations='default,GERMLINE'
howard query --input=tests/data/example.vcf.gz --explode_infos --query='SELECT "#CHROM", POS, REF,
ALT, "DP", "CLNSIG", sample2, sample3 FROM variants WHERE "DP" >= 50 OR "CLNSIG" NOT NULL
ORDER BY "CLNSIG" DESC, "DP" DESC'
howard stats --input=tests/data/example.vcf.gz
howard convert --input=tests/data/example.vcf.gz --output=/tmp/example.tsv --explode_infos && cat
/tmp/example.tsv
```

2 QUERY tool

Query genetic variations in SQL format. Data can be loaded into 'variants' table from various formats (e.g. VCF, TSV, Parquet...). Using `--explode_infos` allow query on INFO/tag annotations. SQL query can also use external data within the request, such as a Parquet file(s).

Usage examples:

```
howard query --input=tests/data/example.vcf.gz --query="SELECT * FROM variants WHERE REF = 'A'
AND POS < 100000"
howard query --input=tests/data/example.vcf.gz --explode_infos --query='SELECT "#CHROM", POS, REF,
ALT, DP, CLNSIG, sample2, sample3 FROM variants WHERE DP >= 50 OR CLNSIG NOT NULL ORDER
BY DP DESC'
howard query --query="SELECT "#CHROM", POS, REF, ALT, "INFO/Interpro_domain" FROM
'tests/databases/annotations/current/hg19/dbnsfp42a.parquet' WHERE "INFO/Interpro_domain" NOT
NULL ORDER BY "INFO/SiPhy_29way_logOdds_rankscore" DESC LIMIT 10"
howard query --explode_infos --explode_infos_prefix='INFO/' --query="SELECT "#CHROM", POS, REF,
ALT, STRING_AGG(INFO, ';') AS INFO FROM 'tests/databases/annotations/current/hg19/*.parquet'
GROUP BY "#CHROM", POS, REF, ALT" --output=/tmp/full_annotation.tsv && head -n2
/tmp/full_annotation.tsv
howard query --input=tests/data/example.vcf.gz --param=config/param.json
```

2.1 Main options

`--input=<input>`

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--output=<output>`

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--param=<param> (default: {})`

Parameters JSON file (or string) defines parameters to process annotations, calculations, prioritizations, conversions and queries.

`--query=<query>`

Query in SQL format
(e.g. 'SELECT * FROM variants LIMIT 50').

2.2 Explode

`--explode_infos`

Explode VCF INFO/Tag into table columns (e.g. 'variants', 'transcripts').

`--explode_infos_prefix=<explode infos prefix>`

Explode VCF INFO/Tag with a specific prefix.

`--explode_infos_fields=<explode infos list> (default: *)`

Explode VCF INFO/Tag specific fields/tags.
Keyword '*' specify all available fields, except those already specified.
Pattern (regex) can be used, such as '.*_score' for fields named with '_score' at the end.
Examples:

- 'HGVS,SIFT,Clinvar' (list of 3 fields)
- 'HGVS,*,Clinvar' (list of 2 fields with all other fields in the middle)
- 'HGVS,.*_score,Clinvar' (list of 2 fields with all scores in the middle)
- 'HGVS,.*_score,*' (1 field, scores, all other fields at the end)

2.3 Query

`--query_limit=<query limit> (default: 10)`

Limit of number of row for query (only for print result, not output).

`--query_print_mode=<print mode> [None, 'dataframe', 'markdown', 'tabulate', 'disabled']`

Print mode of query result (only for print result, not output).
Either None (default), 'dataframe', 'markdown', 'tabulate' or disabled.
If None, print mode is 'dataframe' if no export file is provided.

`--interactive_mode=<interactive mode> ['table', 'view', 'harlequin', 'harlequin_view', 'harlequin_ta`

Interactive mode for variants view.

Either 'table' for loading data and speed up queries, or 'view' for dynamic queries (slower), or 'harleq

2.4 Export

`--include_header`

Include header (in VCF format) in output file.
Only for compatible formats (tab-delimiter format as TSV or BED).

`--parquet_partitions=<parquet partitions>`

Parquet partitioning using hive (available for any format).
This option is faster parallel writing, but memory consuming.
Use 'None' (string) for NO partition but split parquet files into a folder.
Examples: '#CHROM', '#CHROM,REF', 'None'.

3 FILTER tool

Filter genetic variations in SQL format. Data can be loaded into 'variants' table from various formats (e.g. VCF, TSV, Parquet...). SQL filter can also use external data within the request, such as a Parquet file(s).

Usage examples:

```
howard filter --input=tests/data/example.vcf.gz --output=/tmp/example.filter.vcf.gz --filter="REF = 'A' AND POS < 100000"
```

```
howard filter --input=tests/data/example.vcf.gz --output=/tmp/example.filter.vcf.gz --filter="REF = 'A' AND POS < 100000" --samples="sample1,sample2"
```

```
howard filter --input=tests/data/example.vcf.gz --output=/tmp/example.filter.vcf.gz --filter="INFOS.CLNSIG LIKE 'pathogenic'" --samples="sample1,sample2"
```

```
howard filter --input=tests/data/example.vcf.gz --output=/tmp/example.filter.vcf.gz --filter="QUAL > 100 AND SAMPLES.sample2.GT != './.'" --samples="sample2"
```

3.1 Main options

`--input=<input>` | required

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--output=<output>` | required

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

3.2 Filters

`--filter=<filter>`

Filter variant using SQL format

(e.g. 'POS < 100000').

`--samples=<samples>`

List of samples

(e.g. 'sample1,sample2').

3.3 Export

`--include_header`

Include header (in VCF format) in output file.

Only for compatible formats (tab-delimiter format as TSV or BED).

`--parquet_partitions=<parquet partitions>`

Parquet partitioning using hive (available for any format).

This option is faster parallel writing, but memory consuming.

Use 'None' (string) for NO partition but split parquet files into a folder.

Examples: '#CHROM', '#CHROM,REF', 'None'.

4 SORT tool

Sort genetic variations from contig order. Data can be loaded into 'variants' table from various formats (e.g. VCF, TSV, Parquet...). SQL filter can also use external data within the request, such as a Parquet file(s).

Usage examples:

```
howard sort --input=tests/data/example.vcf.gz --output=/tmp/example.sorted.vcf.gz
```

4.1 Main options

`--input=<input> | required`

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--output=<output> | required`

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

4.2 Export

`--include_header`

Include header (in VCF format) in output file.

Only for compatible formats (tab-delimiter format as TSV or BED).

`--parquet_partitions=<parquet partitions>`

Parquet partitioning using hive (available for any format).

This option is faster parallel writing, but memory consuming.

Use 'None' (string) for NO partition but split parquet files into a folder.

Examples: '#CHROM', '#CHROM,REF', 'None'.

5 STATS tool

Statistics on genetic variations, such as: number of variants, number of samples, statistics by chromosome, genotypes by samples...

Usage examples:

```
howard stats --input=tests/data/example.vcf.gz
```

```
howard stats --input=tests/data/example.vcf.gz --stats_md=/tmp/stats.md --stats_json=/tmp/stats.json
```

```
--stats_html=/tmp/stats.html --stats_pdf=/tmp/stats.pdf
```

```
howard stats --input=tests/data/example.vcf.gz --annotations_stats
```

```
howard stats --input=tests/data/example.vcf.gz --param=config/param.json
```

5.1 Main options

`--input=<input> | required`

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--param=<param> (default: {})`

Parameters JSON file (or string) defines parameters to process annotations, calculations, prioritizations, conversions and queries.

5.2 Stats

`--stats_stdout`

Print Markdown stats in stdout. Default False, except if no output files are requested.

`--stats_md=<stats markdown>`

Stats Output file in MarkDown format.

`--stats_json=<stats json>`

Stats Output file in JSON format.

`--stats_html=<stats html>`

Stats Output file in HTML format.

`--stats_pdf=<stats pdf>`

Stats Output file in PDF format.

`--annotations_stats`

Add statistics on annotations (INFO/tags)).

6 CONVERT tool

Convert genetic variations file to another format. Multiple format are available, such as usual and official VCF and BCF format, but also other formats such as TSV, CSV, PSV and Parquet/duckDB. These formats need a header '.hdr' file to take advantage of the power of howard (especially through INFO/tag definition), and using howard convert tool automatically generate header file fo futher use.

Usage examples:

```
howard convert --input=tests/data/example.vcf.gz --output=/tmp/example.tsv
```

```
howard convert --input=tests/data/example.vcf.gz --output=/tmp/example.parquet
```

```
howard convert --input=tests/data/example.vcf.gz --output=/tmp/example.tsv --explode_infos --  
explode_infos_fields='CLNSIG,SIFT,DP' --order_by='CLNSIG DESC, DP DESC'
```

```
howard convert --input=tests/data/example.vcf.gz --output=/tmp/example.tsv --explode_infos --  
explode_infos_prefix='INFO/' --explode_infos_fields='CLNSIG,SIFT,DP,*' --order_by='"INFO/CLNSIG"  
DESC, "INFO/DP" DESC' --include_header
```

```
howard convert --input=tests/data/example.vcf.gz --output=/tmp/example.tsv --param=config/param.json
```

6.1 Main options

`--input=<input> | required`

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--output=<output> | required`

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--param=<param> (default: {})`

Parameters JSON file (or string) defines parameters to process

annotations, calculations, prioritizations, conversions and queries.

6.2 Explode

`--explode_infos`

Explode VCF INFO/Tag into table columns (e.g. 'variants', 'transcripts').

`--explode_infos_prefix=<explode infos prefix>`

Explode VCF INFO/Tag with a specific prefix.

`--explode_infos_fields=<explode infos list> (default: *)`

Explode VCF INFO/Tag specific fields/tags.

Keyword `\*` specify all available fields, except those already specified.

Pattern (regex) can be used, such as `.\*\_score` for fields named with '_score' at the end.

Examples:

- 'HGVS,SIFT,Clinvar' (list of 3 fields)
- 'HGVS,*,Clinvar' (list of 2 fields with all other fields in the middle)
- 'HGVS,.*_score,Clinvar' (list of 2 fields with all scores in the middle)
- 'HGVS,.*_score,*' (1 field, scores, all other fields at the end)

6.3 Export

`--include_header`

Include header (in VCF format) in output file.

Only for compatible formats (tab-delimiter format as TSV or BED).

`--order_by=<order by>`

List of columns to sort the result-set in ascending or descending order.

Use SQL format, and keywords ASC (ascending) and DESC (descending).

If a column is not available, order will not be considered.

Order is enable only for compatible format (e.g. TSV, CSV, JSON).

Examples: 'ACMG_score DESC', 'PZFlag DESC, PZScore DESC'.

`--parquet_partitions=<parquet partitions>`

Parquet partitioning using hive (available for any format).

This option is faster parallel writing, but memory consuming.

Use 'None' (string) for NO partition but split parquet files into a folder.

Examples: '#CHROM', '#CHROM,REF', 'None'.

7 HGVS tool

HGVS annotation using HUGO HGVS international Sequence Variant Nomenclature (<http://varnomen.hgvs.org/>). Annotation refers to refGene and genome to generate HGVS nomenclature for all available transcripts. This annotation adds 'hgvs' field into VCF INFO column of a VCF file.

Usage examples:

`howard hgvs --input=tests/data/example.full.vcf --output=/tmp/example.hgvs.vcf`

`howard hgvs --input=tests/data/example.full.vcf --output=/tmp/example.hgvs.tsv --param=config/param.json`


```
howard hgvs --input=tests/data/example.full.vcf --output=/tmp/example.hgvs.vcf --full_format --use_exon
```

7.1 Main options

`--input=<input>` | required

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. `vcf.gz`, `tsv.gz`).

`--output=<output>` | required

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. `vcf.gz`, `tsv.gz`).

`--param=<param>` (default: `{}`)

Parameters JSON file (or string) defines parameters to process annotations, calculations, prioritizations, conversions and queries.

`--hgvs_options=<HGVS options>`

Quick HGVS annotation options.

This option will skip all other hgvs options.

Examples:

- 'default' (for default options)
- 'full_format' (for full format HGVS annotation)
- 'use_gene=True:add_protein=true:codon_type=FULL'

`--assembly=<assembly>` (default: `hg19`)

Genome Assembly (e.g. `'hg19'`, `'hg38'`).

7.2 HGVS

`--use_gene`

Use Gene information to generate HGVS annotation
(e.g. `'NM_152232(TAS1R2):c.231T>C'`)

`--use_exon`

Use Exon information to generate HGVS annotation
(e.g. `'NM_152232(exon2):c.231T>C'`).
Only if 'use_gene' is not enabled.

`--use_protein`

Use Protein level to generate HGVS annotation
(e.g. `'NP_689418:p.Cys77Arg'`).
Can be used with 'use_exon' or 'use_gene'.

`--add_protein`

Add Protein level to DNA HGVS annotation (e.g. `'NM_152232:c.231T>C,NP_689418:p.Cys77Arg'`).

`--full_format`

Generates HGVS annotation in a full format
by using all information to generates an exhaustive annotation
(non-standard, e.g. `'TAS1R2:NM_152232:NP_689418:c.231T>C:p.Cys77Arg'`).

Use 'use_exon' to add exon information
(e.g. 'TAS1R2:NM_152232:NP_689418:exon2:c.231T>C:p.Cys77Arg').

```
--codon_type=<Codon type> ['1', '3', 'FULL'] (default: 3)
```

Amino Acide Codon format type to use to generate HGVS annotation.
Available:

- '1': codon in 1 character (e.g. 'C', 'R')
- '3': codon in 3 character (e.g. 'Cys', 'Arg')
- 'FULL': codon in full name (e.g. 'Cysteine', 'Arginine')

```
--refgene=<refGene>
```

Path to refGene annotation file.

```
--refseqlink=<refSeqLink>
```

Path to refSeqLink annotation file.

8 ANNOTATION tool

Annotation is mainly based on a build-in Parquet annotation method, and tools such as BCFTOOLS, Annovar and snpEff. It uses available databases (see Annovar and snpEff) and homemade databases. Format of databases are: parquet, duckdb, vcf, bed, Annovar and snpEff (Annovar and snpEff databases are automatically downloaded, see howard databases tool).

Usage examples:

```
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.vcf.gz --annotations='tests/databases/an
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.tsv --assembly=hg19 --
annotations='annovar:refGene,annovar:cosmic70,snpEff,tests/databases/annotations/current/hg19/clinvar_20210123.parquet'
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.tsv --assembly=hg19 --
annotation_parquet='tests/databases/annotations/current/hg19/avsnp150.parquet,tests/databases/annotations/current/hg19/
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.tsv --assembly=hg19 --
annotation_bcftools='tests/databases/annotations/current/hg19/nci60.vcf.gz,tests/databases/annotations/current/hg19/dbnsfp
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.tsv --assembly=hg19 --
annotation_snpsift='tests/databases/annotations/current/hg19/nci60.vcf.gz,tests/databases/annotations/current/hg19/dbnsfp
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.tsv --assembly=hg19
--annotation_annovar='nci60:cosmic70'
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.tsv --assembly=hg19
--annotation_snpeff='-hgvs'
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.tsv --assembly=hg19
--annotation_exomiser='preset=exome:transcript_source=refseq'
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.tsv --assembly=hg19
--annotation_splice='split_mode=one:spliceai_distance=500:spliceai_mask=1'
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.tsv --assembly=hg19
--annotations='ALL:parquet'
howard annotation --input=tests/data/example.vcf.gz --output=/tmp/example.howard.tsv --param=config/param.json
```

8.1 Main options

```
--input=<input> | required
```

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

--output=<output> | required

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

--param=<param> (default: {})

Parameters JSON file (or string) defines parameters to process annotations, calculations, prioritizations, conversions and queries.

--annotations=<annotations>

Annotation with databases files, or with tools,

as a list of files in Parquet, VCF, BED, or keywords

(e.g. 'file.parquet,bcftools:file2.vcf.gz,annovar:refGene,snpEff').

- For a Parquet/VCF/BED, use file paths

(e.g. 'file1.parquet,file2.vcf.gz').

- For BCFTools annotation, use keyword 'bcftools' with file paths

(e.g. 'bcftools:file.vcf.gz:file.bed.gz').

- For Parquet annotation, use keyword 'parquet' with file paths

(e.g. 'parquet:file.parquet').

- For Annovar annotation, use keyword 'annovar' with annovar code

(e.g. 'annovar:refGene', 'annovar:refGene:cosmic70').

- For snpEff annotation, use keyword 'snpEff' with options

(e.g. 'snpEff', 'snpEff:-hgvs -noShiftHgvs -spliceSiteSize 3').

- For snpSift annotation, use keyword 'snpsift' with file paths

(e.g. 'snpsift:file.vcf.gz:file.bed.gz').

- For Exomiser annotation, use keyword 'exomiser' with options as key=value

(e.g. 'exomiser:preset=exome:transcript_source=refseq').

- For add all available databases files, use 'ALL' keyword,

with filters on format (e.g. 'parquet', 'vcf') and release (e.g. 'current', 'devel')

(e.g. 'ALL', 'ALL:format=parquet', 'ALL:format=parquet:release=current', 'ALL:format=parquet+vcf:release=current').

--annotation_parquet=<annotation parquet>

Annotation with Parquet method, as a list of files in Parquet, VCF or BED

(e.g. 'file1.parquet,file2.vcf.gz').

For add all available databases files, use 'ALL' keyword,

with filters on type and release

(e.g. 'ALL', 'ALL:parquet:current', 'ALL:parquet,vcf:current,devel').

--annotation_bcftools=<annotation BCFTools>

Annotation with BCFTools, as a list of files VCF or BED

(e.g. 'file.vcf.gz,file.bed.gz').

--annotation_annovar=<annotation Annovar>

Annotation with Annovar, as a list of database keywords

(e.g. 'refGene', 'refGene:cosmic70').

--annotation_snpEff=<annotation snpEff>

Annotation with snpEff, with options

(e.g. '', '-hgvs -noShiftHgvs -spliceSiteSize 3').

--annotation_snpsift=<annotation snpSift>

Annotation with snpSift, as a list of files VCF

(e.g. 'file.vcf.gz,file.bed.gz').

```

--annotation_exomiser=<annotation Exomiser>

Annotation with Exomiser, as a list of options
(e.g. 'preset=exome:transcript_source=refseq').

--annotation_splice=<annotation Splice>

Annotation with Splice, as a list of options
(e.g. 'split_mode=one:spliceai_distance=500:spliceai_mask=1').

--assembly=<assembly> (default: hg19)

Genome Assembly (e.g. 'hg19', 'hg38').

--fast

Fast annotation mode (Experimental).
Speedup export and reduce memory.
Only Parquet annotation will be processed.

```

8.2 Annotation

```

--annotations_update

Update option for annotation (Only for Parquet annotation).
If True, annotation fields will be removed and re-annotated.
These options will be applied to all annotation databases.

--annotations_append

Append option for annotation (Only for Parquet annotation).
If True, annotation fields will be annotated only if not annotation exists for the variant.
These options will be applied to all annotation databases.

```

9 CALCULATION tool

Calculation processes variants information to generate new information, such as: identify variation type (VarType), harmonizes allele frequency (VAF) and calculate statistics (VAF_stats), extracts Nomen (transcript, cNomen, pNomen...) from an HGVS field (e.g. snpEff, Annovar) with an optional list of personalized transcripts, generates VaRank format barcode, identify trio inheritance.

Usage examples:

```

howard calculation --input=tests/data/example.full.vcf --output=/tmp/example.calculation.tsv --
calculations='vartype'

howard calculation --input=tests/data/example.ann.vcf.gz --output=/tmp/example.calculated.tsv --
calculations='snpeff_hgvs,NOMEN' --hgvs_field=snpeff_hgvs --transcripts=tests/data/transcripts.tsv

howard calculation --input=tests/data/example.vcf.gz --output=/tmp/example.calculated.tsv --calculations='TRIO'
--trio_pedigree='sample1,sample2,sample4'

howard calculation --input=tests/data/example.vcf.gz --output=/tmp/example.calculated.tsv --calculations='BARCODEFAMILY'
--family_pedigree='sample1,sample2,sample4'

howard calculation --input=tests/data/example.ann.transcripts.vcf.gz --output=/tmp/example.calculation.transcripts.tsv
--param=config/param.transcripts.json --calculations='TRANSCRIPTS_ANNOTATIONS,TRANSCRIPTS_PRIORITIZATION'

howard calculation --input=tests/data/example.ann.vcf.gz --output=/tmp/example.ann.tsv --param=config/param.json

howard calculation --show_calculations --show_calculations_md=/tmp/calculations.md

```

9.1 Main options

`--input=<input>`

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. `vcf.gz`, `tsv.gz`).

`--output=<output>`

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. `vcf.gz`, `tsv.gz`).

`--param=<param>` (default: `{}`)

Parameters JSON file (or string) defines parameters to process annotations, calculations, prioritizations, conversions and queries.

`--calculations=<operations>`

Quick calculations on genetic variants information and genotype information, as a list of operations (e.g. `'VARTYPE,variant_id'`).

List of available calculations by default

(unsensitive case, see doc for more information):

VARTYPE snpeff_hgvs FIND_SAMPLES GENOTYPECONCORDANCE BARCODE TRIO VAF VAF_STATS DP_STATS

9.2 Calculation

`--calculation_config=<calculation config>`

Calculation configuration JSON file.

`--show_calculations`

Show available calculation operations.

`--show_calculations_md=<show_calculations_md>`

Show available calculation operations into a Markdown file.

9.3 NOMEN

`--hgvs_field=<HGVS field>` (default: `hgvs`)

HGVS INFO/tag containing a list of HGVS annotations.

`--transcripts=<transcripts>`

Transcripts TSV file,

with Transcript in first column, optional Gene in second column.

9.4 TRIO

`--trio_pedigree=<trio pedigree>`

Pedigree Trio for trio inheritance calculation.

Either a JSON file or JSON string or a list of samples

(e.g. `'sample1,sample2,sample3'` for father, mother and child,

`'{"father": "sample1", "mother": "sample2", "child": "sample3"}'`).

9.5 BARCODEFAMILY

```
--family_pedigree=<family pedigree>
```

Pedigree family for barcode calculation on genotype.

Either a JSON file or JSON string or a list of samples

(e.g. 'sample1,sample2,sample3,sample4',

'{"father": "sample1", "mother": "sample2", "child1": "sample3", "child2": "sample3"}').

10 PRIORITIZATION tool

Prioritization algorithm uses profiles to flag variants (as passed or filtered), calculate a prioritization score, and automatically generate a comment for each variants (example: 'polymorphism identified in dbSNP. associated to Lung Cancer. Found in ClinVar database'). Prioritization profiles are defined in a configuration file in JSON format. A profile is defined as a list of annotation/value, using wildcards and comparison options (contains, lower than, greater than, equal...). Annotations fields may be quality values (usually from callers, such as 'DP') or other annotations fields provided by annotations tools, such as HOWARD itself (example: COSMIC, Clinvar, 1000genomes, PolyPhen, SIFT). Multiple profiles can be used simultaneously, which is useful to define multiple validation/prioritization levels (example: 'standard', 'stringent', 'rare variants', 'low allele frequency').

Usage examples:

```
howard prioritization --input=tests/data/example.vcf.gz --output=/tmp/example.prioritized.vcf.gz --  
prioritizations='default'
```

```
howard prioritization --input=tests/data/example.vcf.gz --output=/tmp/example.prioritized.vcf.gz --  
prioritizations='default,GERMLINE' --prioritization_config=config/prioritization_profiles.json
```

```
howard prioritization --input=tests/data/example.vcf.gz --output=/tmp/example.prioritized.tsv --  
param=config/param.json
```

10.1 Main options

```
--input=<input> | required
```

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

```
--output=<output> | required
```

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

```
--param=<param> (default: {})
```

Parameters JSON file (or string) defines parameters to process

annotations, calculations, prioritizations, conversions and queries.

```
--prioritizations=<prioritisations>
```

List of prioritization profiles to process (based on Prioritization JSON file),
such as 'default', 'rare variants', 'low allele frequency', 'GERMLINE'.

By default, all profiles available will be processed.

10.2 Prioritization

```
--default_profile=<default profile>
```

Prioritization profile by default (see doc).

Default is the first profile in the list of prioritization profiles.

`--pzfields=<pzfields>` (default: PZScore,PZFlag)

Prioritization fields to provide (see doc).

Available: PZScore, PZFlag, PZTags, PZComment, PZInfos

`--prioritization_score_mode=<prioritization score mode>` ['HOWARD', 'VaRank'] (default: HOWARD)

Prioritization Score mode (see doc).

Available: HOWARD (increment score), VaRank (max score)

`--prioritization_config=<prioritization config>`

Prioritization configuration JSON file (defines profiles, see doc).

11 PROCESS tool

howard process tool manage genetic variations to:

- annotates genetic variants with multiple annotation databases/files and tools
- calculates and normalizes annotations
- prioritizes variants with profiles (list of criteria) to calculate scores and flags
- translates into various formats
- query genetic variants and annotations
- generates variants statistics

Usage examples:

```
howard process --input=tests/data/example.vcf.gz --output=/tmp/example.annotated.vcf.gz --param=config/param.json
```

```
howard process --input=tests/data/example.vcf.gz --annotations='snpeff' --calculations='snpeff_hgvs'
--prioritizations='default' --explode_infos --output=/tmp/example.annotated.tsv --query='SELECT
"#CHROM", POS, ALT, REF, snpeff_hgvs FROM variants'
```

```
howard process --input=tests/data/example.vcf.gz --hgvs_options='full_format,use_exon' --explode_infos
--output=/tmp/example.annotated.tsv --query='SELECT "#CHROM", POS, ALT, REF, hgvs FROM variants'
```

```
howard process --input=tests/data/example.vcf.gz --output=/tmp/example.howard.vcf.gz --hgvs='full_format,use_exon'
--annotations='tests/databases/annotations/current/hg19/avsnp150.parquet,tests/databases/annotations/current/hg19/dbnsfp'
--calculations='NOMEN' --explode_infos --query='SELECT NOMEN, REVEL_score, SIFT_score, AF AS
'gnomad_AF', ClinPred_score, ClinPred_pred FROM variants'
```

11.1 Main options

`--input=<input>` | required

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--output=<output>` | required

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--param=<param>` (default: {})

Parameters JSON file (or string) defines parameters to process

annotations, calculations, prioritizations, conversions and queries.

`--hgvs_options=<HGVS options>`

Quick HGVS annotation options.

This option will skip all other hgvs options.

Examples:

- 'default' (for default options)
- 'full_format' (for full format HGVS annotation)
- 'use_gene=True:add_protein=true:codon_type=FULL'

`--annotations=<annotations>`

Annotation with databases files, or with tools,

as a list of files in Parquet, VCF, BED, or keywords

(e.g. 'file.parquet,bcftools:file2.vcf.gz,annovar:refGene,snpeff').

- For a Parquet/VCF/BED, use file paths

(e.g. 'file1.parquet,file2.vcf.gz').

- For BCFTools annotation, use keyword 'bcftools' with file paths

(e.g. 'bcftools:file.vcf.gz:file.bed.gz').

- For Parquet annotation, use keyword 'parquet' with file paths

(e.g. 'parquet:file.parquet').

- For Annovar annotation, use keyword 'annovar' with annovar code

(e.g. 'annovar:refGene', 'annovar:refGene:cosmic70').

- For snpeff annotation, use keyword 'snpeff' with options

(e.g. 'snpeff', 'snpeff:-hgvs -noShiftHgvs -spliceSiteSize 3').

- For snpSift annotation, use keyword 'snpsift' with file paths

(e.g. 'snpsift:file.vcf.gz:file.bed.gz').

- For Exomiser annotation, use keyword 'exomiser' with options as key=value

(e.g. 'exomiser:preset=exome:transcript_source=refseq').

- For add all available databases files, use 'ALL' keyword,

with filters on format (e.g. 'parquet', 'vcf') and release (e.g. 'current', 'devel')

(e.g. 'ALL', 'ALL:format=parquet', 'ALL:format=parquet:release=current', 'ALL:format=parquet+vcf:release=current').

`--calculations=<operations>`

Quick calculations on genetic variants information and genotype information,

as a list of operations (e.g. 'VARTYPE,variant_id').

List of available calculations by default

(unsensitive case, see doc for more information):

VARTYPE snpeff_hgvs FIND_SAMPLES GENOTYPECONCORDANCE BARCODE TRIO VAF VAF_STATS DP_STATS

`--prioritizations=<prioritisations>`

List of prioritization profiles to process (based on Prioritization JSON file),

such as 'default', 'rare variants', 'low allele frequency', 'GERMLINE'.

By default, all profiles available will be processed.

`--assembly=<assembly>` (default: hg19)

Genome Assembly (e.g. 'hg19', 'hg38').

11.2 HGVS

`--use_gene`

Use Gene information to generate HGVS annotation

(e.g. 'NM_152232(TAS1R2):c.231T>C')

`--use_exon`

Use Exon information to generate HGVS annotation

(e.g. 'NM_152232(exon2):c.231T>C').
Only if 'use_gene' is not enabled.

`--use_protein`

Use Protein level to generate HGVS annotation
(e.g. 'NP_689418:p.Cys77Arg').
Can be used with 'use_exon' or 'use_gene'.

`--add_protein`

Add Protein level to DNA HGVS annotation (e.g. 'NM_152232:c.231T>C,NP_689418:p.Cys77Arg').

`--full_format`

Generates HGVS annotation in a full format
by using all information to generates an exhaustive annotation
(non-standard, e.g. 'TAS1R2:NM_152232:NP_689418:c.231T>C:p.Cys77Arg').
Use 'use_exon' to add exon information
(e.g. 'TAS1R2:NM_152232:NP_689418:exon2:c.231T>C:p.Cys77Arg').

`--codon_type=<Codon type> ['1', '3', 'FULL'] (default: 3)`

Amino Acide Codon format type to use to generate HGVS annotation.
Available:

- '1': codon in 1 character (e.g. 'C', 'R')
- '3': codon in 3 character (e.g. 'Cys', 'Arg')
- 'FULL': codon in full name (e.g. 'Cysteine', 'Arginine')

`--refgene=<refGene>`

Path to refGene annotation file.

`--refseqlink=<refSeqLink>`

Path to refSeqLink annotation file.

11.3 Annotation

`--annotations_update`

Update option for annotation (Only for Parquet annotation).
If True, annotation fields will be removed and re-annotated.
These options will be applied to all annotation databases.

`--annotations_append`

Append option for annotation (Only for Parquet annotation).
If True, annotation fields will be annotated only if not annotation exists for the variant.
These options will be applied to all annotation databases.

11.4 Calculation

`--calculation_config=<calculation config>`

Calculation configuration JSON file.

11.5 Prioritization

`--default_profile=<default profile>`

Prioritization profile by default (see doc).
Default is the first profile in the list of prioritization profiles.

`--pzfields=<pzfields> (default: PZScore,PZFlag)`

Prioritization fields to provide (see doc).

Available: PZScore, PZFlag, PZTags, PZComment, PZInfos

`--prioritization_score_mode=<prioritization score mode> ['HOWARD', 'VaRank'] (default: HOWARD)`

Prioritization Score mode (see doc).

Available: HOWARD (increment score), VaRank (max score)

`--prioritization_config=<prioritization config>`

Prioritization configuration JSON file (defines profiles, see doc).

11.6 Query

`--query=<query>`

Query in SQL format

(e.g. 'SELECT * FROM variants LIMIT 50').

`--query_limit=<query limit> (default: 10)`

Limit of number of row for query (only for print result, not output).

`--query_print_mode=<print mode> [None, 'dataframe', 'markdown', 'tabulate', 'disabled']`

Print mode of query result (only for print result, not output).

Either None (default), 'dataframe', 'markdown', 'tabulate' or disabled.

If None, print mode is 'dataframe' if no export file is provided.

11.7 Explode

`--explode_infos`

Explode VCF INFO/Tag into table columns (e.g. 'variants', 'transcripts').

`--explode_infos_prefix=<explode infos prefix>`

Explode VCF INFO/Tag with a specific prefix.

`--explode_infos_fields=<explode infos list> (default: *)`

Explode VCF INFO/Tag specific fields/tags.

Keyword ``\*`` specify all available fields, except those already specified.

Pattern (regex) can be used, such as ``\*\_score`` for fields named with '_score' at the end.

Examples:

- 'HGVS,SIFT,Clinvar' (list of 3 fields)
- 'HGVS,*,Clinvar' (list of 2 fields with all other fields in the middle)
- 'HGVS,.*_score,Clinvar' (list of 2 fields with all scores in the middle)
- 'HGVS,.*_score,*' (1 field, scores, all other fields at the end)

11.8 Export

`--include_header`

Include header (in VCF format) in output file.

Only for compatible formats (tab-delimiter format as TSV or BED).

`--order_by=<order by>`

List of columns to sort the result-set in ascending or descending order.

Use SQL format, and keywords ASC (ascending) and DESC (descending).

If a column is not available, order will not be considered.
Order is enable only for compatible format (e.g. TSV, CSV, JSON).
Examples: 'ACMG_score DESC', 'PZFlag DESC, PZScore DESC'.

`--parquet_partitions=<parquet partitions>`

Parquet partitioning using hive (available for any format).
This option is faster parallel writing, but memory consuming.
Use 'None' (string) for NO partition but split parquet files into a folder.
Examples: '#CHROM', '#CHROM,REF', 'None'.

11.9 Chunking

`--chunking_enable`

Chunking process aims to improve processing efficiency, either by:

- splitting input file into smaller parts.
- using duckDB database as a intermediate file storage.

`--chunking_mode=<chunking mode> (default: parquet)`

Chunking mode select the mode of chunking:

- 'parquet' mode will split files into smaller Parquet files (only if number of variants exceed this chunking size).
- 'duckdb' mode will use DuckDB to load the entire input file into an intermediate storage file.

`--chunking_size=<chunking size> (default: 1000000)`

Chunking size is the number of variants to process at a time.

With 'parquet' chunking mode, input file will be split into multiple smaller Parquet files with a maximum of 'chunking_size' variants per file.

With 'duckdb' chunking mode, the global chunk_size parameter will replaced by 'chunking_size'.

`--chunking_partitions=<chunking partitions> (default: None)`

Partitioning scheme to use with 'parquet' chunking mode, defining how the input file is partitioned during chunking.

`--chunking_sort`

Sort final output after chunking is applied.

Prevents issues with unordered variants after chunked processing.

12 DATABASES tool

Download databases and needed files for howard and associated tools

Usage examples:

```
howard databases --assembly=hg19 --download-genomes=~/howard/databases/genomes/current --download-genomes-provider=UCSC --download-genomes-contig-regex='chr[0-9XYM]+$'
```

```
howard databases --assembly=hg19 --download-genomes=~/howard/databases/genomes/current --download-genomes-provider-file=https://hgdownload.soe.ucsc.edu/goldenpath/hg19/bigZips/p13.plusMT/hg19.p13.plusMT.fa.gz --download-genomes-contig-regex='chr[0-9XYMT]+$'
```

```
howard databases --assembly=hg19 --download-annovar=~/howard/databases/annovar/current --download-annovar-files='refGene,cosmic70,nci60'
```

```
howard databases --assembly=hg19 --download-snpEff=~/howard/databases/snpEff/current
```

```
howard databases --assembly=hg19 --download-refseq=~/howard/databases/refseq/current --download-refseq-format-file='ncbiRefSeq.txt'
```

```

howard databases --assembly=hg19 --download-dbnsfp=~/howard/databases/dbnsfp/current --download-
dbnsfp-source=tests/databases/dbnsfp/dbNSFP4.4a.zip --download-dbnsfp-release='4.4a' --download-dbnsfp-
subdatabases

howard databases --assembly=hg19 --download-alphamissense=~/howard/databases/alphamissense/current

howard databases --assembly=hg19 --download-exomiser=~/howard/databases/exomiser/current

howard databases --assembly=hg19 --download-dbsnp=~/howard/databases/dbsnp/current --download-dbsnp-
vcf

cd ~/howard/databases && howard databases --assembly=hg19 --download-genomes=genomes/current
--download-genomes-provider=UCSC --download-genomes-contig-regex='chr[0-9XYM]+' --download-
annovar=annovar/current --download-annovar-files='refGene,cosmic70,nci60' --download-snpeff=snpeff/current -
--download-refseq=refseq/current --download-refseq-format-file='ncbiRefSeq.txt' --download-alphamissense=alphamissense/curre
--download-exomiser=exomiser/current --download-dbsnp=dbsnp/current --download-dbsnp-vcf --threads=8

howard databases --generate-param=/tmp/param.json --generate-param-description=/tmp/test.description.json
--generate-param-formats=parquet

howard databases --input__annovar=tests/databases/others/hg19_nci60.txt --output__annovar=/tmp/nci60.from__annovar.vcf.gz
--annovar_to__parquet=/tmp/nci60.from__annovar.parquet --annovar_code=nci60 --genome=~/howard/databases/genomes/cur

```

Notes:

- Downloading databases can take a while, depending on network, threads and memory
- Proxy: Beware of network and proxy configuration
- dbNSFP download: More threads, more memory usage (8 threads ~ 16Gb, 24 threads ~ 32Gb)

12.1 Main options

```
--assembly=<assembly> (default: hg19)
```

Genome Assembly (e.g. 'hg19', 'hg38').

```
--genomes-folder=<genomes> (default: ~/howard/databases/genomes/current)
```

Folder containing genomes.

(e.g. '~/howard/databases/genomes/current')

```
--genome=<genome> (default: ~/howard/databases/genomes/current/hg19/hg19.fa)
```

Genome file in fasta format (e.g. 'hg19.fa', 'hg38.fa').

```
--param=<param> (default: {})
```

Parameters JSON file (or string) defines parameters to process

annotations, calculations, prioritizations, conversions and queries.

12.2 Genomes

```
--download-genomes=<genomes>
```

Path to genomes folder

with Fasta files, indexes,

and all files generated by pygenome module.

(e.g. '~/howard/databases/genomes/current').

```
--download-genomes-provider=<genomes provider> ['GENCODE', 'Ensembl', 'UCSC', 'NCBI'] (default: UCSC)
```

Download Genome from an external provider.

Available: GENCODE, Ensembl, UCSC, NCBI.

`--download-genomes-provider-file=<genomes provider file>`

Download or Copy Genome from URL or a file.

(e.g. `https://hgdownload.soe.ucsc.edu/goldenPath/sacCer3/bigZips/sacCer3.fa.gz`).

`--download-genomes-contig-regex=<genomes contig regex>`

Regular expression to select specific chromosome

(e.g. `'chr[0-9XYM]+$'`).

12.3 snpEff

`--download-snpEff=<snpEff>`

Download snpEff databases within snpEff folder

12.4 Annovar

`--download-annovar=<Annovar>`

Path to Annovar databases

(e.g. `'~/howard/databases/annovar/current'`).

`--download-annovar-files=<Annovar code>`

Download Annovar databases for a list of Annovar file code (see Annovar Doc).

Use None to download all available files,

or Annovar keyword (e.g. `'refGene'`, `'cosmic70'`, `'clinvar_202*'`).

Note that refGene will at least be downloaded,

and only files that not already exist or changed will be downloaded.

`--download-annovar-url=<Annovar url>` (default: `http://www.openbioinformatics.org/annovar/download`)

Annovar databases URL (see Annovar Doc).

`--download-annovar-force-update`

Force update Annovar databases if different size, even if they already exist.

12.5 refSeq

`--download-refseq=<refSeq>`

Path to refSeq databases

(e.g. `'~/howard/databases/refseq/current'`).

`--download-refseq-url=<refSeq url>` (default: `http://hgdownload.soe.ucsc.edu/goldenPath`)

refSeq databases URL (see refSeq WebSite)

(e.g. `'http://hgdownload.soe.ucsc.edu/goldenPath'`)•/n

`--download-refseq-prefix=<refSeq prefix>` (default: `ncbiRefSeq`)

Check existing refSeq files in refSeq folder.

`--download-refseq-files=<refSeq files>` (default: `ncbiRefSeq.txt,ncbiRefSeqLink.txt`)

List of refSeq files to download.

`--download-refseq-format-file=<refSeq format file>`

Name of refSeq file to convert in BED format

(e.g. `'ncbiRefSeq.txt'`).

Process only if not None.

`--download-refseq-include-utr5`

Formating BED refSeq file including 5'UTR.

`--download-refseq-include-utr3`

Formating BED refSeq file including 3'UTR.

`--download-refseq-include-chrM`

Formating BED refSeq file including Mitochondiral chromosome 'chrM' or 'chrMT'.

`--download-refseq-include-non-canonical-chr`

Formating BED refSeq file including non canonical chromosomes.

`--download-refseq-include-non-coding-transcripts`

Formating BED refSeq file including non coding transcripts.

`--download-refseq-include-transcript-version`

Formating BED refSeq file including transcript version.

12.6 dbNSFP

`--download-dbnsfp=<dbNSFP>`

Download dbNSFP databases within dbNSFP folder(e.g. '~/howard/databases').

`--download-dbnsfp-url=<dbNSFP url>` (default: <https://dbnsfp.s3.amazonaws.com>)

Download dbNSFP databases URL (see dbNSFP website)
(e.g. <https://dbnsfp.s3.amazonaws.com>).

`--download-dbnsfp-release=<dbNSFP release>` (default: 4.4a)

Release of dbNSFP to download (see dbNSFP website)
(e.g. '4.4a').

`--download-dbnsfp-source=<dbNSFP source as a URL or a file>`

Source of dbNSFP as an URL or a local file
(e.g. '/path/to/dbNSFP5.1a.zip').

`--download-dbnsfp-parquet-size=<dbNSFP parquet size>` (default: 100)

Maximum size (Mb) of data files in Parquet folder.
Parquet folder are partitioned (hive) by chromosome (sub-folder),
which contain N data files.

`--download-dbnsfp-subdatabases`

Generate dbNSFP sub-databases.
dbNSFP provides multiple databases which are split onto multiple columns.
This option create a Parquet folder for each sub-database (based on columns names).

`--download-dbnsfp-parquet`

Generate a Parquet file for each Parquet folder.

`--download-dbnsfp-vcf`

Generate a VCF file for each Parquet folder.
Need genome FASTA file (see `--download-genome`).

`--download-dbnsfp-no-files-all`

Not generate database Parquet/VCF file for the entire database ('ALL').
Only sub-databases files will be generated.
(see `'--download-dbnsfp-subdatabases'`).

`--download-dbnsfp-add-info`

Add INFO column (VCF format) in Parquet folder and file.
Useful for speed up full annotation (all available columns).
Increase memory and space during generation of files.

`--download-dbnsfp-only-info`

Add only INFO column (VCF format) in Parquet folder and file.
Useful for speed up full annotation (all available columns).
Decrease memory and space during generation of files.
Increase time for partial annotation (some available columns).

`--download-dbnsfp-uniquify`

Uniquify values within column
(e.g. "D,D" to "D", "D.,T" to "D,T").
Remove transcripts information details.
Usefull to reduce size of the database.
Increase memory and space during generation of files.

`--download-dbnsfp-row-group-size=<dnNSFP row group size>` (default: 100000)

Minimum number of rows in a parquet row group (see duckDB doc).
Lower can reduce memory usage and slightly increase space during generation,
speed up highly selective queries, slow down whole file queries (e.g. aggregations).

12.7 AlphaMissense

`--download-alphamissense=<AlphaMissense>`

Path to AlphaMissense databases

`--download-alphamissense-url=<AlphaMissense url>` (default: https://storage.googleapis.com/dm_alphamissense)

Download AlphaMissense databases URL (see AlphaMissense website)
(e.g. `'https://storage.googleapis.com/dm_alphamissense'`).

12.8 Exomiser

`--download-exomiser=<Exomiser>`

Path to Exomiser databases

(e.g. `~/howard/databases/exomiser/current`).

`--download-exomiser-application-properties=<Exomiser application properties>`

Exomiser Application Properties configuration file (see Exomiser website).
This file contains configuration settings for the Exomiser tool.
If this parameter is not provided, the function will attempt to locate
the application properties file automatically based on the Exomiser.
Configuration information will be used to download expected releases (if no other parameters).
CADD and REMM will be downloaded only if 'path' are provided.

`--download-exomiser-url=<Exomiser url> (default: http://data.monarchinitiative.org/exomiser)`

URL where Exomiser database files can be downloaded from
(e.g. 'http://data.monarchinitiative.org/exomiser').

`--download-exomiser-release=<Exomiser release>`

Release of Exomiser data to download.

If "default", "auto", or "config", retrieve from Application Properties file.

If not provided (None), from Application Properties file (Exomiser data-version)
or default '2109'.

`--download-exomiser-phenotype-release=<Exomiser phenotype release>`

Release of Exomiser phenotype to download.

If not provided (None), from Application Properties file (Exomiser Phenotype data-version)
or Exomiser release.

`--download-exomiser-remm-release=<Exomiser remm release>`

Release of ReMM (Regulatory Mendelian Mutation) database to download.

If "default", "auto", or "config", retrieve from Application Properties file.

`--download-exomiser-remm-url=<Exomiser remm url> (default: https://kircherlab.bihealth.org/download/`

URL where ReMM (Regulatory Mendelian Mutation) database files can be downloaded from
(e.g. 'https://kircherlab.bihealth.org/download/ReMM').

`--download-exomiser-cadd-release=<Exomiser cadd release>`

Release of CADD (Combined Annotation Dependent Depletion) database to download.

If "default", "auto", or "config", retrieve from Application Properties file.

`--download-exomiser-cadd-url=<Exomiser cadd url> (default: https://kircherlab.bihealth.org/download/`

URL where CADD (Combined Annotation Dependent Depletion) database files can be downloaded from
(e.g. 'https://kircherlab.bihealth.org/download/CADD').

`--download-exomiser-cadd-url-snv-file=<Exomiser url snv file> (default: whole_genome_SNVs.tsv.gz)`

Name of the file containing the SNV (Single Nucleotide Variant) data
for the CADD (Combined Annotation Dependent Depletion) database.

`--download-exomiser-cadd-url-indel-file=<Exomiser cadd url indel> (default: InDels.tsv.gz)`

Name of the file containing the INDEL (Insertion-Deletion) data
for the CADD (Combined Annotation Dependent Depletion) database.

12.9 dbSNP

`--download-dbsnp=<dnSNP>`

Path to dbSNP databases

(e.g. '~/howard/databases/dbsnp/current').

`--download-dbsnp-releases=<dnSNP releases> (default: b156)`

Release of dbSNP to download

(e.g. 'b152', 'b152,b156').

`--download-dbsnp-release-default=<dnSNP release default>`

Default Release of dbSNP ('default' symlink)

(e.g. 'b156').

If None, first release to download will be assigned as default only if it does not exists.

`--download-dbsnp-url=<dbSNP url> (default: https://ftp.ncbi.nih.gov/snp/archive)`

URL where dbSNP database files can be downloaded from.
(e.g. 'https://ftp.ncbi.nih.gov/snp/archive').

`--download-dbsnp-url-files=<dbSNP url files>`

Dictionary that maps assembly names to specific dbSNP URL files.
It allows you to provide custom dbSNP URL files for specific assemblies instead of using the default file naming convention.

`--download-dbsnp-url-files-prefix=<dbSNP url files prefix> (default: GCF_000001405)`

String that represents the prefix of the dbSNP file name for a specific assembly.
It is used to construct the full URL of the dbSNP file to be downloaded.

`--download-dbsnp-assemblies-map=<dbSNP assemblies map> (default: {'hg19': '25', 'hg38': '40'})`

dictionary that maps assembly names to their corresponding dbSNP versions.
It is used to construct the dbSNP file name based on the assembly name.

`--download-dbsnp-vcf`

Generate well-formatted VCF from downloaded file:

- Add and filter contigs associated to assembly
- Normalize by splitting multiallelics
- Need genome (see `--download-genome`)

`--download-dbsnp-parquet`

Generate Parquet file from VCF.

12.10 HGMD

`--convert-hgmd=<HGMD>`

Convert HGMD databases.
Folder where the HGMD databases will be stored.
Fields in VCF, Parquet and TSV will be generated.
If the folder does not exist, it will be created.

`--convert-hgmd-file=<HGMD file>`

File from HGMD.
Name format 'HGMD_Pro_<release>_<assembly>.vcf.gz'.

`--convert-hgmd-basename=<HGMD basename>`

File output basename.
Generated files will be prefixed by basename
(e.g. 'HGMD_Pro_MY_RELEASE')
By default (None), input file name without '.vcf.gz'.

12.11 from_Annovar

`--input_annovar=<input annovar>`

Input Annovar file path.
Format file must be a Annovar TXT file, associated with '.idx'.

```
--output_annovar=<output annovar>
```

Output Annovar file path.
Format file must be either VCF compressed file '.vcf.gz'.

```
--annovar_code=<Annovar code>
```

Annovar code, or database name.
Usefull to name databases columns.

```
--annovar_to_parquet=<to parquet>
```

Parquet file conversion.

```
--annovar_reduce_memory=<reduce memory> ['auto', 'enable', 'disable'] (default: auto)
```

Reduce memory option for Annovar convert,
either 'auto' (auto-detection), 'enable' or 'disable'.

```
--annovar_multi_variant=<Annovar multi variant> ['auto', 'enable', 'disable'] (default: auto)
```

Variant with multiple annotation lines on Annovar file.
Either 'auto' (auto-detection), 'enable' or 'disable'.

12.12 from_extann

```
--input_extann=<input extann>
```

Input Extann file path.
Format file must be a Extann TXT file or TSV file.
File need to have at least the genes column.

```
--output_extann=<output extann>
```

Output Extann file path.
Output extann file, should be BED or BED.gz.

```
--refgene=<refGene>
```

Path to refGene annotation file.

```
--transcripts=<transcripts>
```

Transcripts TSV file,
with Transcript in first column, optional Gene in second column.

```
--param_extann=<param extann>
```

Param extann file path.
Param containing configuration, options to replace chars and
bedlike header description, conf vcf specs.
(e.g. '~/howard/config/param.extann.json')

```
--mode_extann=<mode extann> ['all', 'longest', 'chosen', 'gene'] (default: longest)
```

Mode extann selection.
How to pick transcript from ncbi, keep all,
keep the longest, or keep the chosen one (transcript_extann).

```
--hgnc_extann=<hgnc_extann>
```

hgnc_extann file path.
Path of HGNC file

12.13 Parameters

```
--generate-param=<param>
```

Parameter file (JSON) with all databases found.
Databases folders scanned are defined in config file.
Structure of databases follow this structure (see doc):
.../<database>/<release>/<assembly>/*. [parquet|vcf.gz|...]

```
--generate-param-description=<param description>
```

Description file (JSON) with all databases found.
Contains all databases with description of format, assembly, fields...

```
--generate-param-releases=<param release> (default: current)
```

List of database folder releases to check
(e.g. 'current', 'latest').

```
--generate-param-formats=<param formats> (default: parquet)
```

List of database formats to check
(e.g. 'parquet', 'parquet,vcf,bed,tsv').

```
--generate-param-bcftools
```

Generate parameter JSON file with BCFTools annotation for allowed formats
(i.e. 'vcf', 'bed').

13 GUI tool

Graphical User Interface tools

Usage examples:

```
howard gui
```

14 HELP tool

Help tools

Usage examples:

```
howard help --help_md=docs/help.md --help_html=docs/html/help.html --help_pdf=docs/pdf/help.pdf
```

```
howard help --help_json_input=docs/json/help.configuration.json --help_json_input_title='HOWARD  
Configuration' --help_md=docs/help.configuration.md --help_html=docs/html/help.configuration.html  
--help_pdf=docs/pdf/help.configuration.pdf --code_type='json'
```

```
howard help --help_json_input=docs/json/help.parameteres.json --help_json_input_title='HOWARD  
Parameters' --help_md=docs/help.parameteres.md --help_html=docs/html/help.parameteres.html --  
help_pdf=docs/pdf/help.parameteres.pdf --code_type='json'
```

```
howard help --help_json_input=docs/json/help.parameteres.databases.json --help_json_input_title='HOWARD  
Parameters Databases' --help_md=docs/help.parameteres.databases.md --help_html=docs/html/help.parameteres.databases.ht  
--help_pdf=docs/pdf/help.parameteres.databases.pdf --code_type='json'
```

14.1 Main options

```
--help_md=<help markdown>
```

Help Output file in MarkDown format.

```

--help_html=<help html>

Help Output file in HTML format.

--help_pdf=<help pdf>

Help Output file in PDF format.

--help_md_input=<help MarkDown input>

Help input file in MarkDown format.

--help_json_input=<help JSON input>

Help input file in JSON format.

--help_json_input_title=<help JSON input title> (default: Help)

Help JSON input title.

--code_type=<example code type>

Help example code type for input JSON format
(e.g. 'json', 'bash').

```

15 UPDATE__DATABASE tool

Update HOWARD database

Usage examples:

```

howard update__database --database clinvar --databases_folder /home1/DB/HOWARD --update_config up-
date_databases.json

```

15.1 Main options

```

--param=<param> (default: {})

Parameters JSON file (or string) defines parameters to process
annotations, calculations, prioritizations, conversions and queries.

```

15.2 Update__database

```

--databases_folder=<databases_folder> (default: ~/howard/databases)

Path of HOWARD database folder.

--database=<database> ['clinvar', 'gnomad', 'CADD', 'omim']

Which database to update.

--data_folder=<data_folder>

Path of data needed to update database.

--update_config=<update_config> (default: ~/BIOINFO/git/HOWARD/plugins/update_database/config/update

Path of json configuration file.

--current_folder=<current_folder> (default: current)

Path of json configuration file.

```

`--refseq=<refseq>`

Path of refseq file.

15.3 Options

`--show`

show variants in input file.

`--limit=<limit> [2, 5] (default: 2)`

Limit of output variants.

Either '2' or '5' lines.

16 TO_EXCEL tool

Convert VCF file to Excel '.xlsx' format.

Usage examples:

`howard to_excel --input=tests/data/example.vcf.gz --output=/tmp/example.xlsx --add_variants_view`

16.1 Main options

`--input=<input> | required`

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--output=<output> | required`

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

16.2 Add

`--add_variants_view`

Create a sheet with all INFO fields exploded.

`--add_header`

Create a sheet with all INFO fields header descriptions.

17 TRANSCRIPTS_CHECK tool

Check if a transcript list is present in a generated transcript table from a input VCF file.

Usage examples:

`howard transcripts_check --input=plugins/transcripts_check/tests/data/example.ann.transcripts.vcf.gz --param=plugins/transcripts_check/tests/data/param.transcripts.json --transcripts_expected=plugins/transcripts_check/tests/c`
`--stats=/tmp/transcripts.stats.json --transcripts_missing=/tmp/transcripts.missing.tsv`

17.1 Main options

`--input=<input> | required`

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--param=<param> (default: {}) | required`

Parameters JSON file (or string) defines parameters to process annotations, calculations, prioritizations, conversions and queries.

`--transcripts_expected=<List of transcripts (file)> | required`

File with a list of transcripts in first column.

`--transcripts_missing=<List of missing transcripts (file)>`

File with a list of missing transcripts in first column.

`--stats_json=<stats json>`

Stats Output file in JSON format.

18 GENEBe tool

GeneBe annotation using REST API (see <https://genebe.net/>).

Usage examples:

`howard genebe --input=tests/data/example.vcf.gz --output=/tmp/example.genebe.vcf.gz --genebe_use_refseq`

18.1 Main options

`--input=<input> | required`

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--output=<output> | required`

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--param=<param> (default: {})`

Parameters JSON file (or string) defines parameters to process annotations, calculations, prioritizations, conversions and queries.

`--assembly=<assembly> (default: hg19)`

Genome Assembly (e.g. 'hg19', 'hg38').

18.2 GeneBe

`--genebe_use_refseq`

Use refSeq to annotate (default).

`--genebe_use_ensembl`

Use Ensembl to annotate.

`--not_flatten_consequences`

Use exploded annotation informations.

18.3 Explode

`--explode_infos`

Explode VCF INFO/Tag into table columns (e.g. 'variants', 'transcripts').

`--explode_infos_prefix=<explode infos prefix>`

Explode VCF INFO/Tag with a specific prefix.

`--explode_infos_fields=<explode infos list> (default: *)`

Explode VCF INFO/Tag specific fields/tags.

Keyword ``*`` specify all available fields, except those already specified.

Pattern (regex) can be used, such as ``.*_score`` for fields named with `'_score'` at the end.

Examples:

- 'HGVS,SIFT,Clinvar' (list of 3 fields)
- 'HGVS,*,Clinvar' (list of 2 fields with all other fields in the middle)
- 'HGVS,.*_score,Clinvar' (list of 2 fields with all scores in the middle)
- 'HGVS,.*_score,*' (1 field, scores, all other fields at the end)

18.4 Export

`--include_header`

Include header (in VCF format) in output file.

Only for compatible formats (tab-delimiter format as TSV or BED).

`--order_by=<order by>`

List of columns to sort the result-set in ascending or descending order.

Use SQL format, and keywords ASC (ascending) and DESC (descending).

If a column is not available, order will not be considered.

Order is enable only for compatible format (e.g. TSV, CSV, JSON).

Examples: 'ACMG_score DESC', 'PZFlag DESC, PZScore DESC'.

`--parquet_partitions=<parquet partitions>`

Parquet partitioning using hive (available for any format).

This option is faster parallel writing, but memory consuming.

Use 'None' (string) for NO partition but split parquet files into a folder.

Examples: '#CHROM', '#CHROM,REF', 'None'.

19 MINIMIZE tool

Minimalize a VCF file consists in put missing value ('.') on INFO/Tags, ID, QUAL or FILTER fields. Options can also minimalize samples (keep only GT) or remove all samples. INFO/tags can be exploded before minimalize to keep tags into separated columns (useful for Parquet or TSV format to constitute a database).

Usage examples:

```
howard minimalize --input=tests/data/example.vcf.gz --output=/tmp/example.minimal.vcf.gz --minimalize_info
--minimalize_filter --minimalize_qual --minimalize_id --minimalize_samples
```

```
howard minimize --input=tests/data/example.vcf.gz --output=/tmp/example.minimal.tsv --remove_samples
--explode_infos --minimize_info
```

19.1 Main options

`--input=<input> | required`

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--output=<output> | required`

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. vcf.gz, tsv.gz).

`--param=<param> (default: {})`

Parameters JSON file (or string) defines parameters to process annotations, calculations, prioritizations, conversions and queries.

19.2 Minimalize

`--minimize_info`

Minimalize INFO field (e.g. '.' value).

`--minimize_id`

Minimalize ID field (e.g. '.' value).

`--minimize_qual`

Minimalize QUAL field (e.g. '.' value).

`--minimize_filter`

Minimalize FILTER field (e.g. '.' value).

`--minimize_samples`

Minimalize samples to keep only genotypes (i.e. 'GT').

`--remove_samples`

Remove all samples to keep only variants.

19.3 Explode

`--explode_infos`

Explode VCF INFO/Tag into table columns (e.g. 'variants', 'transcripts').

`--explode_infos_prefix=<explode infos prefix>`

Explode VCF INFO/Tag with a specific prefix.

`--explode_infos_fields=<explode infos list> (default: *)`

Explode VCF INFO/Tag specific fields/tags.

Keyword '*' specify all available fields, except those already specified.

Pattern (regex) can be used, such as ``.*_score`` for fields named with `'_score'` at the end.

Examples:

- `'HGVS,SIFT,Clinvar'` (list of 3 fields)
- `'HGVS,*,Clinvar'` (list of 2 fields with all other fields in the middle)
- `'HGVS,.*_score,Clinvar'` (list of 2 fields with all scores in the middle)
- `'HGVS,.*_score,*'` (1 field, scores, all other fields at the end)

19.4 Export

`--include_header`

Include header (in VCF format) in output file.

Only for compatible formats (tab-delimiter format as TSV or BED).

`--order_by=<order by>`

List of columns to sort the result-set in ascending or descending order.

Use SQL format, and keywords ASC (ascending) and DESC (descending).

If a column is not available, order will not be considered.

Order is enable only for compatible format (e.g. TSV, CSV, JSON).

Examples: `'ACMG_score DESC'`, `'PZFlag DESC, PZScore DESC'`.

`--parquet_partitions=<parquet partitions>`

Parquet partitioning using hive (available for any format).

This option is faster parallel writing, but memory consuming.

Use `'None'` (string) for NO partition but split parquet files into a folder.

Examples: `'#CHROM'`, `'#CHROM,REF'`, `'None'`.

20 BIGWIG tool

BigWig/BigBed converter (Under development).

Usage examples:

`howard bigwig --input=tests/data/example.vcf.gz --output=/tmp/example.bw`

`howard bigwig --input=tests/data/example.bb --output=/tmp/example.bb`

20.1 Main options

`--input=<input> | required`

Input file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. `vcf.gz`, `tsv.gz`).

`--output=<output>`

Output file path.

Format file must be either VCF, Parquet, TSV, CSV, PSV or duckDB.

Files can be compressed (e.g. `vcf.gz`, `tsv.gz`).

`--param=<param> (default: {})`

Parameters JSON file (or string) defines parameters to process

annotations, calculations, prioritizations, conversions and queries.

20.2 Options

`--show`

show variants in input file.

`--limit=<limit> [2, 5] (default: 2)`

Limit of output variants.

Either '2' or '5' lines.

21 Shared arguments

`--config=<config> (default: {})`

Configuration JSON file defined default configuration regarding resources (e.g. threads, memory), settings (e.g. verbosity, temporary files), default folders (e.g. for databases) and paths to external tools.

`--threads=<threads> (default: -1)`

Specify the number of threads to use for processing HOWARD.

It determines the level of parallelism,

either on python scripts, duckdb engine and external tools.

It and can help speed up the process/tool.

Use -1 to use all available CPU/cores.

Either non valid value is 1 CPU/core.

`--memory=<memory>`

Specify the memory to use in format FLOAT[kMG]

(e.g. '8G', '12.42G', '1024M').

It determines the amount of memory for duckDB engine and external tools (especially for JAR programs).

It can help to prevent 'out of memory' failures.

By default (None) is 80%% of RAM (for duckDB).

`--chunk_size=<chunk size> (default: 1048576)`

Number of records in batch to export output file.

The lower the chunk size, the less memory consumption.

For Parquet partitioning, files size will depend on the chunk size.

`--tmp=<Temporary folder>`

Temporary folder (e.g. '/tmp').

By default, '.tmp' for duckDB (see doc), external tools and python scripts.

`--access=<access mode> ['RW', 'RO', None, 'None']`

Access mode to variants input file in database.

Either 'RW' for Read and Write, or 'RO' for Read Only.

Read Only Access mode is usefull to not load data into database (especially input Parquet file) when it's not needed

(e.g. queries, fast annotation mode), reducing memory impact

`--duckdb_settings=<duckDB settings>`

DuckDB settings (see duckDB doc) as JSON (string or file).

These settings have priority (see options 'threads', 'tmp'...).

Examples: '{"TimeZone": "GMT", "temp_directory": "/tmp/duckdb", "threads": 8}'.

`--interactive`

Interactive mode.

```
--verbosity=<verbosity> ['CRITICAL', 'ERROR', 'WARNING', 'INFO', 'DEBUG', 'NOTSET', 'WARN', 'FATAL']
```

Verbosity level

Available: CRITICAL, ERROR, WARNING, INFO, DEBUG or NOTSET

- DEBUG: Detailed information, typically of interest only when diagnosing problems.
- INFO: Confirmation that things are working as expected.
- WARNING: An indication that something unexpected happened.
- ERROR: Due to a more serious problem.
- CRITICAL: A serious error.
- FATAL: A fatal error.
- NOTSET: All messages.

```
--log=<log>
```

Logs file

(e.g. 'my.log').

```
--quiet
```

```
==SUPPRESS==
```

```
--verbose
```

```
==SUPPRESS==
```

```
--debug
```

```
==SUPPRESS==
```