

bioinformatics.ca

bioinformaticsdotca.github.io

CC BY-SA 4.0 DEED

Attribution-ShareAlike 4.0 International

Canonical URL : https://creativecommons.org/licenses/by-sa/4.0/

See the legal code

You are free to:

Share — copy and redistribute the material in any medium or format for any purpose, even commercially.

Adapt — remix, transform, and build upon the material for any purpose, even commercially.

The licensor cannot revoke these freedoms as long as you follow the license terms.

Under the following terms:

Attribution — You must give appropriate credit , provide a link to the license, and indicate if changes were made . You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.

ShareAlike — If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.

No additional restrictions — You may not apply legal terms or technological measures that legally restrict others from doing anything the license permits.

Notices:

You do not have to comply with the license for elements of the material in the public domain or where your use is permitted by an applicable exception or limitation .

No warranties are given. The license may not give you all of the permissions necessary for your intended use. For example, other rights such as publicity, privacy, or moral rights may limit how you use the material.

Module 1: Introduction to Machine Learning

Gustavo Sganzerla Martinez

Machine Learning Foundations, Halifax, NS

October 14-16, 2026

Introductions

- Tell us about you and:
  - Your research/professional interests
  - How do you anticipate Machine Learning can assist you

Learning Objectives

- Understand the concept of supervised and unsupervised Machine Learning (ML).
- Understand what ML can and cannot do.
- Understand how to measure performance of ML models.
- Understand the concepts of overfitting and underfitting.

Supervised and Unsupervised Learning

- Essentially, every Machine Learning (ML) application can be tagged either as **Supervised Learning** or **Unsupervised Learning**.
- These are two fundamental concepts that are defined by how ML uses its data.

Supervised Learning

- Supervising learning is defined by the use of labelled data.
- You know beforehand which are the features **X** that describe a target $\mathbf{y}$.
- Supervision comes from observing $\mathbf{y}$ during training.
- The algorithm learns the relationship between **X** and $\mathbf{y}$.
- Then, it attempts to generalize the learned pattern to unseen **X.**

Supervised Learning

- Two main families of supervised learning.
- **Classification:** prediction of discrete values (classes)
- **Regression:** prediction of continuous values (numbers)

Supervised Learning

- Two main families of supervised learning.
- **Classification:** prediction of discrete values (classes)
- **Regression:** prediction of continuous values (numbers)

<u>Problem</u>: Predict whether a patient will survive 30 days

Supervised Learning

- Two main families of supervised learning.
- **Classification:** prediction of discrete values (classes)
- **Regression:** prediction of continuous values (numbers)

<u>Problem</u>: Predict how many days a patient will survive

Supervised Learning

- Two main families of supervised learning.
- **Classification:** prediction of discrete values (classes)
- **Regression:** prediction of continuous values (numbers)

<u>Problem</u>: Predict a patient's systolic blood pressure

Supervised Learning

- Two main families of supervised learning.
- **Classification:** prediction of discrete values (classes)
- **Regression:** prediction of continuous values (numbers)

<u>Problem</u>: Predict cancer stage I, II, III, or IV.

Supervised Learning

- Two main families of supervised learning.
- **Classification:** prediction of discrete values (classes)
- **Regression:** prediction of continuous values (numbers)

Problem: Predict pain-score (0-10)

Example: Supervised Learning, Classification


- **y** (binary; cat or dog; 1/0)

Cat | Dog

- **X** (features that describe y)

Ear shape

Training: We analyze n pictures of cats and dogs and try to find a ear shape that describes cats and dogs.




Unsupervised Learning

- Analyze unlabeled data sets to discover hidden patterns.
- There is no target label (**y**).
- Generally requires the involvement of someone familiar with the data.


Unsupervised Learning

- Examples of algorithms:
  - **Clustering (day 3 with Mackenzie Tapp)**



Unsupervised Learning

- Examples of algorithms:
  - **Dimensionality reduction**



Measuring Performance (classification)

- Key Performance Indicators (KPI)
  - **Confusion Matrix**
  - Track correct predictions: True Positives (TP) and True Negatives (TN)
  - Track incorrect predictions: False Positives (FP) and False Negatives (FN)


Observed \ Predicted		
	TP	FN
	FP	TN

Problem: *Prediction of having a disease*

TP: *Have* the disease, was predicted as *having*
FP: *Do not* have the disease, was predicted as *having*
FN: *Have* the disease, was predicted as *not having*
TN: *Do not* have the disease, was predicted as *not having*

Measuring Performance (classification)

- Key Performance Indicators (KPI)
  - **Confusion Matrix**
    - **Accuracy** = Overall fraction of correct predictions out of all predictions.
      - Accuracy = (TP+TN)/(TP+TN+FP+FN)
    - **Precision** = Fraction of correct positive predictions
      - Precision = TP/(TP+FN)
    - **Recall (sensitivity)** = Fraction of actual positive cases the model captured.
      - Recall = TP/(TP+FN)
    - **Specificity** = Fraction of actual negative cases the model captured.
      - Specificity = TN/(TP+FN)




Measuring Performance (Regression)

- We measure the difference between the ground truth targets (actual) and the model's predicted values (predicted).
- These differences are referred to as residuals (error).

Measuring Performance (Regression)

- **Mean Absolute Error (MAE):**
  - *It asks*: how wrong are we on average?
  - Original units as the input data.


$$\mathrm{MAE} = \frac{1}{n}\sum_{i=1}^{n} | x_i - x |$$



Measuring Performance (Regression)

- **Root Mean Square Error (RMSE):**
  - *It asks*: how wrong are we on average *if we penalize large errors heavily*?
  - Original units as the input data.


$$RMSE = \sqrt{\sum_{i=1}^{n} \frac{(\hat{y}_i - y_i)^2}{n}}$$



Measuring Performance (Regression)


- **Coefficient of Determination (R^2)**
  - *It asks*: how much variation does our model explain?
    - $R^2 \approx 1$: perfect fit; the model explains 100% of the variation.
    - $R^2 \approx 0$: no improvement over predicting the mean.
    - R2 < 0: the predictions are even worse than the class average.

$$R^2 = 1 - \frac{\sum_{i=1}^{m} (X_i - Y_i)^2}{\sum_{i=1}^{m} (\bar{Y} - Y_i)^2}$$



Over/Underfitting

- Scenario: Student training for an exam.
  - **Underfitting (the unprepared student)**
    - The student misses fundamental principles. Scores poorly on practice problems (high training error) and fail the final exam (high test error).
  - **Overfitting (the memorizer)**
    - The student memorizes every question and answer from the practice exam. Scores 100% on practice problems (low training error), but fails when given slightly modified questions (high test error).



Coffee Break & Networking Session

Workshop Sponsors