

Canadian Bioinformatics Workshops

www.bioinformatics.ca
bioinformaticsdotca.github.io



CC BY-SA 4.0 DEED

Attribution-ShareAlike 4.0 International

Canonical URL: <https://creativecommons.org/licenses/by-sa/4.0/>

[See the legal code](#)

You are free to:

Share — copy and redistribute the material in any medium or format for any purpose, even commercially.

Adapt — remix, transform, and build upon the material for any purpose, even commercially.

The licensor cannot revoke these freedoms as long as you follow the license terms.

Under the following terms:

 **Attribution** — You must give [appropriate credit](#), provide a link to the license, and [indicate if changes were made](#). You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.

 **ShareAlike** — If you remix, transform, or build upon the material, you must distribute your contributions under the [same license](#) as the original.

No additional restrictions — You may not apply legal terms or [technological measures](#) that legally restrict others from doing anything the license permits.


Notices:

You do not have to comply with the license for elements of the material in the public domain or where your use is permitted by an applicable [exception or limitation](#).

No warranties are given. The license may not give you all of the permissions necessary for your intended use. For example, other rights such as [publicity, privacy, or moral rights](#) may limit how you use the material.

RNA-Seq Module 3: HTSeq






Malachi Griffith, Obi Griffith, Isabel Risch, Vida Talebian
RNA-seq Analysis 2024. June 17-19, 2024



Alternatives to FPKM

- Raw read counts for differential expression analysis
 - Assign reads/fragments to defined genes/transcripts, get “raw counts”
 - Transcript structures could still be defined by something like Stringtie
 - HTSeq (htseq-count)
 - <https://htseq.readthedocs.io/>
- ```
htseq-count --mode intersection-strict --stranded no --minqual 1 --type
exon --idattr transcript_id accepted_hits.sam chr22.gff >
transcript_read_counts_table.tsv
```
- Caveats of ‘transcript’ analysis by htseq-count:
    - Designed for genes - ambiguous reads from overlapping transcripts may not be handled!
    - <http://seqanswers.com/forums/showthread.php?t=18068>

# HTSeq-count basically counts reads supporting a feature (exon, gene) by assessing overlapping coordinates

|                                                                                      | union     | intersection_strict | intersection_nonempty |
|--------------------------------------------------------------------------------------|-----------|---------------------|-----------------------|
|    | gene_A    | gene_A              | gene_A                |
|    | gene_A    | no_feature          | gene_A                |
|    | gene_A    | no_feature          | gene_A                |
|    | gene_A    | gene_A              | gene_A                |
|    | gene_A    | gene_A              | gene_A                |
|    | ambiguous | gene_A              | gene_A                |
|  | ambiguous | ambiguous           | ambiguous             |

Note, if gene\_A and gene\_B on opposite strands, sequence data is stranded, and correct HTSeq parameter set then this read may not be ambiguous

Whether a read is counted depends on the nature of overlap and “mode” selected

# We are on a Coffee Break & Networking Session

Workshop Sponsors:



Canadian Centre for  
Computational  
Genomics



HPC4Health



OICR  
Ontario Institute  
for Cancer Research



GenomeCanada