

Canadian Bioinformatics Workshops

www.bioinformatics.ca
bioinformaticsdotca.github.io



CC BY-SA 4.0 DEED

Attribution-ShareAlike 4.0 International

Canonical URL: <https://creativecommons.org/licenses/by-sa/4.0/>

[See the legal code](#)

You are free to:

Share — copy and redistribute the material in any medium or format for any purpose, even commercially.

Adapt — remix, transform, and build upon the material for any purpose, even commercially.

The licensor cannot revoke these freedoms as long as you follow the license terms.

Under the following terms:

 **Attribution** — You must give [appropriate credit](#), provide a link to the license, and [indicate if changes were made](#). You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.

 **ShareAlike** — If you remix, transform, or build upon the material, you must distribute your contributions under the [same license](#) as the original.

No additional restrictions — You may not apply legal terms or [technological measures](#) that legally restrict others from doing anything the license permits.



Notices:

You do not have to comply with the license for elements of the material in the public domain or where your use is permitted by an applicable [exception or limitation](#).


No warranties are given. The license may not give you all of the permissions necessary for your intended use. For example, other rights such as [publicity, privacy, or moral rights](#) may limit how you use the material.

RNA-Seq Module 2: Alignment

Malachi Griffith, Obi Griffith, Isabel Risch, Vida Talebian
RNA-seq Analysis 2024. June 17-19, 2024



Alignment is central to most genomic research



Alignment - How does it work?



- Alignment is about fitting individual pieces (reads) into the correct part of the puzzle
- The human genome project gave us the picture on the box cover (the reference genome)
- Imperfections in how the pieces fit can indicate changes to a copy of the picture

Reference: AGCCTGAGACCGTAAAAAA**A**GTCAAG

|||||

A read sequence:

GAGACCGTAAAAAA**C**GTC

↑
A variant!

RNA-seq alignment challenges

- Computational cost
 - 100's of millions of reads
- Introns!
 - Align to a transcriptome or align to a genome?
 - Spliced vs. unspliced alignments
- Can I just align my data once using one approach and be done with it?
 - Unfortunately, probably not

Three RNA-seq mapping strategies

De novo assembly




Assemble transcripts from overlapping tags



Optional: align to genome to get exon structure

Align to transcriptome



Use known and/or predicted gene models to examine individual features

Align to reference genome




Infer possible transcripts and abundance

Diagrams from Cloonan & Grimmond, Nature Methods 2010

Which alignment strategy is best?

- De novo assembly
 - If a reference genome does not exist for the species being studied
 - If complex polymorphisms/mutations/haplotypes might be missed by comparing to the reference genome
- Align to transcriptome
 - If you have short reads (< 50bp)
 - Relies on known transcripts
- Align to reference genome
 - All other cases
 - Does not rely on known transcripts – allows for discovery
- Each strategy involves different alignment/assembly tools


Which read aligner should I use?




Should I use a splice-aware or unspliced mapper?

- The fragments being sequenced in RNA-seq represent mRNA - introns are removed
- But we are usually aligning these reads back to the reference genome
- Unless your reads are short (<50bp) you should use a splice-aware aligner
 - HISAT2, STAR, MapSplice, etc.


Double-stranded genomic DNA template



Single-stranded pre-mRNA (nuclear RNA)



Mature mRNA



HISAT/HISAT2


- HISAT is a ‘splice-aware’ RNA-seq read aligner
 - HISAT = **H**ierarchical **I**ndexing for **S**pliced **A**lignments of **T**ranscripts
- Requires a reference genome
- Very fast
- Uses an indexing scheme based on the Burrows-Wheeler transform and the Ferragina-Manzini (FM) index
- Multiple types of indexes for alignment
 - a whole-genome FM index to anchor each alignment
 - numerous local FM indexes for very rapid extensions of these alignments.
 - Whole-genome indices with SNPs and known transcript structures accounted for

Kim et al. 2015. Nat Methods 12:357–360

HISAT/HISAT2 algorithm

- Uses a hierarchical indexing algorithm + several adaptive strategies
 - based on the position of a read with respect to splice sites
- 1) Find candidate locations across the whole genome first
 - mapping part of each read using the global FM index
 - Generally identifies one or a small number of candidates.
- 2) Do local alignment
 - selects one of ~48,000 local indexes for each candidate
 - uses it to align the remainder of the read.
- For paired reads, each mate is separately aligned
 - If a read fails to align, then the alignments of its mate are used as anchors to map the unaligned mate

HISAT2 Alignment



- Two exons from chr22
- Three reads

Kim et al. 2015. Nat Methods 12:357–360


HISAT2 Alignment



- 1) Search for read position with global FM index (slower)
- 2) Once at least 28bp and exactly one location switch to extension mode against reference genome (faster)

Kim et al. 2015. Nat Methods 12:357–360


HISAT2 Alignment



- 1) Search for read position with global FM index (slower)
- 2) Extend until mismatch at 93bp (faster)
- 3) Switch to local FM index to align remaining 8bp
 - index covers only a small region, so we find just one match
- 4) Check for compatibility and combine into single spliced alignment

Kim et al. 2015. Nat Methods 12:357–360

HISAT2 Alignment



- 1) global search until exactly one match of at least 28bp (slower)
- 2) Extend until mismatch at 51bp (faster)
- 3) switch to local FM index to align first 8bp of remaining read
 - If too many matches increase prefix size
- 4) Extend again
- 5) Check for compatibility and combine into single spliced alignment

Kim et al. 2015. Nat Methods 12:357–360

What is the output of HISAT2?

- A SAM/BAM file
 - SAM stands for Sequence Alignment/Map format
 - BAM is the binary version of a SAM file
- Remember, compressed files require special handling compared to plain text files
- How can I convert BAM to SAM?
 - <http://www.biostars.org/p/1701/>
- Is HISAT2 the only mapper to consider for RNA-seq data?
 - <http://www.biostars.org/p/60478/>

We are on a Coffee Break & Networking Session

Workshop Sponsors:



Canadian Centre for
Computational
Genomics



HPC4Health



GenomeCanada