

# hw06

Noel Lim (PID:A17652474)

```
# Can you improve this analysis code?  
library(bio3d)  
s1 <- read.pdb("4AKE") # kinase with drug
```

Note: Accessing on-line PDB file

```
s2 <- read.pdb("1AKE") # kinase no drug
```

Note: Accessing on-line PDB file  
PDB has ALT records, taking A only, rm.alt=TRUE

```
s3 <- read.pdb("1E4Y") # kinase with drug
```

Note: Accessing on-line PDB file


```
s1.chainA <- trim.pdb(s1, chain="A", elety="CA")  
s2.chainA <- trim.pdb(s2, chain="A", elety="CA")  
s3.chainA <- trim.pdb(s1, chain="A", elety="CA")  
s1.b <- s1.chainA$atom$b  
s2.b <- s2.chainA$atom$b  
s3.b <- s3.chainA$atom$b  
plotb3(s1.b, sse=s1.chainA, typ="l", ylab="Bfactor")
```



```
plotb3(s2.b, sse=s2.chainA, typ="l", ylab="Bfactor")
```



```
plotb3(s3.b, sse=s3.chainA, typ="l", ylab="Bfactor")
```



Q6. How would you generalize the original code above to work with any set of input protein structures?

Read PDB, isolate chain A, isolate atom B, plot

```
protein <- function(x) {
  # read pdb
  x1 <- read.pdb(x)
  # isolate chain A
  x1.A <- trim.pdb(x1, chain="A", elety="CA")
  # atom B
  x1.b <- x1.A$atom$b
  # plot
  plotb3(x1.b, sse=x1, typ="l", ylab="Bfactor")
}
```