) N →	A Siemens Business ACTIVITY Arrive at site carry out visual inspection Install necessary vibration mointoning equipment
Install recessary vibration monitoring equipment Test run unit and monitor vibration levels Analyse recorded data Verify instrumentation Isolate unit Remove coupling coupling gaurds Carry out coupling using weights as required Install coupling coupling gaurds Test run unit and monitor vibration levels Carry out coupling using weights as required Install coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupling gaurds Trial balance coupling using weights as required Install coupling using weights as required Install coupling gaurds Toard coupling using weights as required Install coupling gaurds Toard coupling using weights as required Install coupling gaurds Toard coupling using weights as required Install coupling gaurds Toard coupling using weights as required Install coupling gaurds Toard coupling using weights as required Install coupling gaurds Toard coupling using weights as required Install coupling gaurds Toard coupling using weights as required Install coupling gaurds Toard weights as required	1		Arrive at site carry out visual inspection
Analyse recorded data Verify instrumentation Isolate unit Remove coupling coupling gaurds Carry out coupling using weights as required Instalt coupling guards Trial balance coupling coupling gaurds Instalt coupling using weights as required Instalt coupling inspection Trial balance coupling gaurds Carry out coupling using weights as required Instalt coupling		ω	Test run unit and monitor vibration levels
Verify instrumentation Isolate unit Isolate unit Remove coupling coupling gaurds Carry out coupling inspection Trial balance coupling using weights as required Install coupling guards Test run unit and monitor vibration levels Analyse recorded data Isolate unit Remove coupling using weights as required Install coupling guards Test run unit and monitor vibration levels Analyse recorded data Isolate unit Trial balance coupling using weights as required Install coupling gaurds Carry out coupling gaurds Carry out coupling reception Trial balance coupling weights as required Install coupling using weights as required Install coupling using weights as required Install coupling using weights as required Install coupling gaurds Carry out coupling coupling paurds Carry out coupling neights as required Install coupling Balance coupling specifion Trial balance coupling using weights as required Install coupling gaurds Carry out coupling specifion Trial balance specifion Trial balance coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupling using weights as required Install coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupling using weights as required		4	Analyse recorded data
Isolate unit Remove coupling coupling gaurds Carry out coupling using weights as required Install coupling guards Install coupling coupling gaurds Remove coupling coupling gaurds Isolate unit Remove coupling using weights as required Install coupling using weights as required Install coupling using weights as required Install coupling gaurds Test run unit and monitor vibration levels Analyse recorded data Isolate unit Remove coupling coupling gaurds Carry out coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupling using weights as required Install coupling gaurds Carry out coupling coupling paurds Carry out coupling using weights as required Install coupling using weights as required Install coupling gaurds Carry out coupling coupling saing weights as required Install coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupling using weights as required Install coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupling using weights as required Install coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupli		Ch	Verify instrumentation
Remove coupling coupling gaurds Carry out coupling using weights as required Install coupling guards Install coupling guards Install coupling guards Analyse recorded data Isolate unit Remove coupling using weights as required Install coupling inspection Trial balance coupling gaurds Carry out coupling inspection Trial balance coupling using weights as required Install coupling using weights as required Install coupling out coupling gaurds Carry out coupling the performance Trial balance coupling coupling paurds Carry out coupling using weights as required Install coupling using weights as required Install coupling gaurds Carry out coupling surds Carry out coupling as many weights as required Install coupling gaurds Carry out coupling spection Trial balance specialist 1 1 1 1 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2		6	Isolate unit
Carry out coupling using weights as required Install coupling guards Test run unit and monitor vibration levels Analyse recorded data Install coupling coupling gaurds Carry out coupling using weights as required Install couplin guards Carry out coupling using weights as required Install couplin guards Trial balance coupling gaurds Test run unit and monitor vibration levels Install coupling gaurds Test run unit and monitor wibration levels Test run unit and monitor vibration levels Install coupling coupling gaurds Test run unit and monitor vibration levels Test run unit and monitor performance Test run un		7	Remove coupling coupling gaurds
Trial balance coupling using weights as required Install coupling guards Test run unit and monitor vibration levels Analyse recorded data Isolate unit Remove coupling coupling gaurds Carry out coupling inspection Trial balance coupling using weights as required Install couplin guards Test run unit and monitor vibration levels Install coupling gaurds Carry out coupling gaurds Test run unit and monitor vibration levels Install coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupling gaurds Search out coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupling gaurds Carry out coupling gaurds Carry out coupling using weights as required Install coupling gaurds Carry out coupling gaurds Carry out coupling using weights as required Install coupling gaurds Carry out coupling gaurds Nanpower requirements 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		00	Carry out coupling inspection
Install coupling guards Test run unit and monitor vibration levels Analyse recorded data Isolate unit Remove coupling coupling gaurds Carry out coupling inspection Trial balance coupling using weights as required Install couplin guards Test run unit and monitor vibration levels Install coupling gaurds Carry out coupling gaurds Test run unit and monitor vibration levels Install coupling gaurds Carry out coupling gaurds Install coupling using weights as required Install coupling gaurds Carry out coupling using weights as required Install coupling guards Carry out coupling using weights as required Install coupling guards Carry out coupling guards Carry out coupling guards Carry out coupling using weights as required Install coupling guards Carry out coupling guards Carry out coupling gaurds Carry out coupling using weights as required Install coupling guards Departments Nanpower requirements 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		9	Trial balance coupling using weights as required
Test run unit and monitor vibration levels Analyse recorded data Isolate unit Remove coupling coupling gaurds Carry out coupling using weights as required Install couplin guards Trial balance coupling using weights as required Install coupling gaurds Test run unit and monitor vibration levels Test run unit and monitor performance Manpower required Manpower requirements 1 1 1 1 1 1 2 2 2 2 2 2 2 2 1 2 2 2 2			Install coupling guards
Analyse recorded data Isolate unit Remove coupling coupling gaurds Carry out coupling using weights as required Install coupling using weights as required Install coupling gaurds Trial balance coupling using weights as required Install coupling gaurds Analyse recorded data Isolate unit Carry out coupling inspection Trial balance coupling using weights as required Install coupling using weights as required Operate unit fully loaded and monitor performance Manpower requirements 1 x DR Mech FSR 1 x DR Mech FSR 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		_	Test run unit and monitor vibration levels
Isolate unit Remove coupling coupling gaurds Carry out coupling using weights as required Install couplin guards Trial balance coupling using weights as required Install coupling guards Test run unit and monitor vibration levels Analyse recorded data Isolate unit Isolate u		>	Analyse recorded data
Remove coupling coupling gaurds Carry out coupling inspection Trial balance coupling using weights as required Install couplin guards Test run unit and monitor vibration levels Analyse recorded data Isolate unit Carry out coupling coupling gaurds Carry out coupling inspection Trial balance coupling using weights as required Install coupling gards Operate unit fully loaded and monitor performance Manpower requirements 1 x DR Mech FSR 1 x DR Mech FSR 1 x DR Mechanical Techs 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		-	Isolate unit
Carry out coupling inspection Trial balance coupling using weights as required Install couplin guards Test run unit and monitor vibration levels Analyse recorded data Isolate unit Isolate unit Remove coupling coupling gaurds Carry out coupling inspection Carry out coupling using weights as required Install coupling guards Carry out coupling using weights as required Install coupling guards Operate unit fully loaded and monitor performance Manpower requirements 1 1 1 1 1 1 X DR Mech FSR 1 2 2 2 2 2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3			Remove coupling coupling gaurds
Trial balance coupling using weights as required Install couplin guards Test run unit and monitor vibration levels Analyse recorded data Isolate unit Remove coupling coupling gaurds Carry out coupling inspection Trial balance coupling using weights as required Install coupling guards Operate unit fully loaded and monitor performance Manpower requirements 1 x DR Mech FSR 1 x DR Mech FSR 1 x DR Trim Balance Specialist 2 x I coal E&I 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		-	Carry out coupling inspection
Install couplin guards Test run unit and monitor vibration levels Analyse recorded data Isolate unit Remove coupling coupling gaurds Carry out coupling inspection Trial balance coupling using weights as required Install coupling guards Operate unit fully loaded and monitor performance Manpower requirements 1 x DR Mech FSR 1 x DR Mech FSR 1 1 1 1 1 2 X SPDC Mechanical Techs 2 2 2 2 2 2 3 3 3 3 3			Trial balance coupling using weights as required
Test run unit and monitor vibration levels Analyse recorded data Isolate unit Remove coupling coupling gaurds Carry out coupling inspection Trial balance coupling using weights as required Install coupling guards Operate unit fully loaded and monitor performance Manpower requirements 1 x DR Mech FSR 1 x DR Mech FSR 1 x DR Trim Balance Specialist 2 x S SPDC Mechanical Techs 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		-	
Analyse recorded data Isolate unit Remove coupling coupling gaurds Carry out coupling inspection Trial balance coupling using weights as required Install coupling guards Operate unit fully loaded and monitor performance Manpower requirements 1 1 1 1 1 1 X DR Mech FSR 1 X DR Mech FSR 1 X DR Trim Balance Specialist 2 X S PDC Mechanical Techs 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		-	Test run unit and monitor vibration levels
Isolate unit Remove coupling coupling gaurds Carry out coupling inspection Trial balance coupling using weights as required Install coupling guards Operate unit fully loaded and monitor performance Manpower requirements 1 1 1 1 1 1 X DR Mech FSR 1 X DR Trim Balance Specialist 2 X SPDC Mechanical Techs 2 2 2 2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3			Analyse recorded data
		2	Isolate unit
		N	Remove coupling gaurds
		2	Carry out coupling inspection
		N	Trial balance coupling using weights as required
		N	Install coupling guards
Manpower requirements 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		2	Operate unit fully loaded and monitor performance
Manpower requirements 1 1 1 1 1 FSR 1 1 1 1 1 3alance Specialist 1 1 1 1 1 schanical Techs 2 2 2 2 2			
FSR 3alance Specialist 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2 2 2 2 2			Manpower requirements
schanical Techs 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			1 x DR Mech FSR
schanical lechs 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			- X DX Tilli balance opecialist
			2 X SPDC Mechanical Techs

GENERAL NOTES:-

This barchart is guide only and based on the following assumptions: 10 hour working days/ 7 days a week with unrestricted access to both site and equipment. Site manpower supplied are of a competent level in line with the activities planned. All materials, tooling, crane and services required are readily available on site. There is no contingency for lost time due to logistics, PTW preparation, adequate manpower etc.

As this is still at the fault finding stage the timeline could be longer/shorter depending on results of investigation

Shoope How House