BEELEMA WELLS REQUIRING CCU INSTALLATION

| SN | WELL | OIL(NET)BBL | GAS9MMSCF/D) | BSW (%) | SLOT ACCESS |
|----|-------|-------------|--------------|------------|---------------------------|
| 01 | 105 | 4118 | 2,543 | 0.05 | OK, ACCESS AT ANY TIDE |
| 02 | 11T | 3469 | 1,777 | 0.06 | OK, ACCESS AT ANY TIDE |
| 03 | 35 | 5030 | 4,086 | 0.06 | OK, ACCESS AT ANY TIDE |
| 04 | 75 | 5006 | 3,289 | 0.06 | OK, ACCESS AT ANY TIDE |
| 05 | 10L | 1084 | 850 | 0.09 | OK, ACCESS AT ANY TIDE |
| 06 | 7L | 1377 | 968 | 0.15 | OK, ACCESS AT ANY TIDE |
| 07 | 3L | 1742 | 824 | 0.23 | OK, ACCESS AT ANY TIDE |
| 08 | 2T | 3,059 | 1,380 | 1.13 | OK, ACCESS AT ANY TIDE |
| 09 | 8T | 2502 | 1,877 | 18.21 | OK, ACCESS AT ANY TIDE |
| 10 | 15 | 2469 | 1,320 | 31.98 | OK, ACCESS AT ANY TIDE |
| 11 | 5L | 737 | 694 | 45.85 | OK, ACCESS AT ANY TIDE |
| 12 | 9T | 1313 | 630 | 53.46 | OK, ACCESS AT ANY TIDE |
| | TOTAL | 31906 | 20,238 | | |

NOTE: Compressor turndown ratio 12mmscf/d