

Laboratory Refrigerator





BPR-5V68

Technical Parameters

BPR-5V108

Model		BPR-5V68	BPR-5V108
External Size(W*D*H)mm	(W*D*H)mm	495*548*683	495*548*934
Internal Size(W*D*H)mm	W*D*H)mm	415*405*455	415*405*706
Capacity		68L	108L
Temperature Range	Range	2-8°C	
Temperature Accuracy	Accuracy	0.1°C	
Control System	E	Microprocessor Control	
Alarm		Audible and visual alarm for: High and low temperature, Door Ajar, Thermostat failure	erature, Door Ajar, Thermostat failure
Refrigeration Type	Type	Forced air refrigeration system	
Refrigerant		R600a	
Climate Type		N, SN	
Glass Door		Toughened with electric heating function, no condensation	densation
	Constructure	Polyurethane cyclopentane foams	
Construction	Construction Internal material	Spraying steel plate	
	External material	Spraying steel plate	
Consumption		92W	92W
Power Supply		AC220V±10%, 50/60Hz; AC110V±10%, 50/60Hz	H2
Shelves		2pcs, cold drawn steel wire impregnated shelf	3 pcs,cold drawn steel wire impregnated shelf
Door Lock		1 pcs	
Accesson		Standard: USB Port, LED Lamp	
6		Optional: temperature recorder, printer(USBport can not be selected at the same time)	can not be selected at the same time)
Package Size(W*D*H)mm	(W*D*H)mm	560*668*858	560*668*1109
Gross Weight(kg)	(kg)	49	61

Laboratory Refrigerator





	,		3000
	Z60L		360L
Technical Parameters	arameters		
Model		BPR-5V260	BPR-5V360
External Size(W*D*H) mm	W*D*H) mm	540*635*1900	660*655*1980
Capacity		260L	360L
Temp. Range		2℃~8℃	
Temp. Accuracy	sy e	0.1°C	
Control System	F	Microprocessor Control, Large Screen LED Display	play
Alexan		Audible and visual alarm for: High temperature & sensor failure, door ajar,	& sensor failure, door ajar,
Alarm		Power failure alarm, Low battery alarm.	
Refrigeration Type	lype	Forced air refrigeration system	
Refrigerant		R134a, CFC Free	
Condenser & Evaporator	Evaporator	Bundy tube condenser	
Defrost		Frostless design	
	Structure	Unibody design & mono-assembly foaming (Rigid polyurethane insulation material)	gid polyurethane insulation material)
Construction	Internal material	HIPS engineering plastics, abrasion and acid resistant	esistant
	External material	Cold-rolled steel coated with anti-bacteria powder	der
0		Adjustable shelves made of high quality steel wire	vire
Signa		4 pcs	5 pcs
Consumption		200W	350W
Power Supply		AC220V±10%, 50/60Hz	
Standard Accessory	ssory	LED lamp & shelves, USB, probe access port, door keys	door keys
Package Size(W*D*H) mm	(W*D*H) mm	600*670*2150	720*750*2150
Gross Weight (kg)	(kg)	87	124