

RE200-Pro

20L Industrial Digital Rotary Evaporator

A promise of safety, reliability & highest level of efficiency for large volumes



Features

- Large LCD digital display with heating temperature, rotation speed, clockwise&anticlockwise and time information
- One-click automatic motor lifting (stroke 180mm), smooth and silent
- Water/ oil heating bath with wide temperature range from RT to 180 °C
- Speed range from 10 to 150rpm, and interval operation in clockwise and anticlockwise directions for drying process
- Two-section vertical triple coil condensing tube with large area and strong evaporation capacity ensuring high-efficiency sample recovery
- The connector device allows for easy and quick installation of the evaporating flask
- PTFE double sealing ring with excellent sealing performance
- Switch valve for continuous collection without compromising the system vacuum and solvent distillation

Applications

Suitable for pilot-scale production, large-scale application in biology engineering, pharmaceutical industry, chemical industry, beauty industry, medical industry and food processing.



Large LCD display



Overheating protection



Chemical resistance



Two-section vertical triple coil condenser

large condensation area and strong evaporation capacity ensuring high efficient sample recovery



Switching valve design

switch valve for continuous collection without compromising the system vacuum and solvent distillation



Heating bath

- Water & oil bath
- Enhanced lifetime through exclusive use of corrosion-free stainless-steel
- It adopts special heat insulation structure design so the surface temperature is far lower than the temperature in the bath to avoid personnel burns

Specifications	RE200-Pro	
performance	Temperature range	Room temp. ~180°C (water and oil bath)
	Temperature control accuracy	Water: $\pm 1^{\circ}\text{C}$ Oil: $\pm 3^{\circ}\text{C}$
	Rotation Speed	10~150rpm
	Ultimate vacuum	Less 2.6mbar
	Evaporation capacity	Max.4.5L/h(75% Alcohol)
function	Temperature control	Micro processor PID control
	Display	LCD (temperature/speed/clockwise and Anti-clockwise/time)
	Time Setting Range	0-999min
	Lift stroke	Motorized 180mm
	Safety features	Motor over-current protection, earth-leakage protection, lifting overload protection, Boil-dry protection, Overheating protection
components	Evaporation flask	Round flask 20L
	Receiving flask	Round flask 10L with drain valve
	Condenser	Two-section vertical triple coil condenser, cooling surface 1.2m ²
specification	Heating bath size	Ø 450×240mm
	Hose connection	Cooling/suction nozzle outer diameter 16mm, vacuum pump nozzle outer diameter 16mm
Dimension[D×W×H]		1160×600×1860mm
Voltage/Frequency		220V/50/60Hz
Power		4600w
Heating Power		4400w

Optional Add-ons

Distillation System Connection (For RE100-Pro&RE100-S)



C410 Chemistry-design diaphragm pump

Specifications

Maximum Vacuum:13mbar
Work Mode: Continuous Operation
Nozzle Size:8mm, Power: 95W
Motor speed:1450rpm
Flow Rate:


mbar	1000	880	750	600	480	280
L/min	25	22	20	12	7.5	50

Noise:50dB

Seals and other accessories

Cat. No.	Description	
18204186	vacuum seal (PTFE+Viton)	
18204187	Evaporation bottle spring Used with 18204186	
18900190	Evaporation flask clip(red) NS29/42	
18900188	Evaporation flask clip(green) NS24/40	
18900744	Rotary Evaporator transparent safety shield(RE100-Pro)	
18900789	Rotary Evaporator transparent safety shield(RE100-S)	
18204228	Flask holder(50mL-1000mL)	
	Flask holder(1L-20L)	

Regulator /Moisture

Cat. No.	Description
18900186	Material: PVDF, PTFE, ABS, Borosilicate Glass, Stainless Steel 

Vertical

Cat. No.	Glassware type	Volume	Cooling surface
18900165	Evaporating flask(NS29/32) Receiving flask(KS35/20)	1000mL	1700cm ²
18900173	Evaporating flask(NS24/40) Receiving flask(KS35/20)	1000mL	1700cm ²
18900166	(COATED)Evaporating flask(NS29/32) Receiving flask (KS35/20)	1000mL	1700cm ²
18900174	(COATED)Evaporating flask(NS24/40) Receiving flask (KS35/20)	1000mL	1700cm ²
18202410	Evaporating flask (NS 29/32) Receiving flask (KS 35/20)	1000mL	1200cm ²
18900476	Evaporating flask (NS 24/40) Receiving flask (KS 35/20)	1000mL	1200cm ²

Diagonal

Cat. No.	Glassware type	Volume	Cooling surface
18900163	Evaporating flask(NS29/32)Receiving flask(KS35/20)	1000mL	1700cm ²
18900171	Evaporating flask(NS24/40)Receiving flask(KS35/20)	1000mL	1700cm ²
18900164	(COATED)Evaporating flask(NS29/32) Receiving flask (KS 35/20)	1000mL	1700cm ²
18900172	(COATED)Evaporating flask(NS24/40) Receiving flask (KS35/20)	1000mL	1700cm ²

Heating Bath

Cat. No.	Description	Volume
18900201	Heating bath for Rotary Evaporator RE100-Pro, 220V	5L
18900202	Heating bath for Rotary Evaporator RE100-Pro, 110V	5L
6033100210	LED heating bath, 100V-120/200-240V,50/60HZ	5L

Heating Bath Lid

Cat. No.	Description
18900547	heating Bath lid for RE100-S, improve distillation efficiency & ensure personnal safety from liquid splash

Glassware



Evaporating flask

Cat. No.	Volume	Size
18300116	50mL	NS 29/32
18300117	100mL	NS 29/32
18300118	250mL	NS 29/32
18300119	500mL	NS 29/32
18300120	1000mL	NS 29/32
18300121	2000mL	NS 29/32
18300122	3000mL	NS29/32
18300655	50mL	NS24/40
18300201	100mL	NS 24/40
18300202	250mL	NS 24/40
18300203	500mL	NS 24/40
18300204	1000mL	NS 24/40
18300205	2000mL	NS 24/40
18900204	3000mL	NS24/40
18900563	20L	RE200-Pro



Foam brake

Cat. No.	Volume	Size
18300093	250mL	NS 29/32
18300207	250mL	NS 24/40



Glass axis

Cat. No.	Volume	Size
18100998	Glass axis	NS 29/32
18203431	Thickened glass axis	NS24/40
18300206	Glass axis	NS 24/40
18204253	Thickened glass axis	NS29/32

Receiving flask

Cat. No.	Volume	Size
18300107	100mL	KS 35/20
18300108	250mL	KS 35/20
18300109	500mL	KS 35/20
18300110	1000mL	KS 35/20
18300111	2000mL	KS 35/20
18900564	10L	RE200-Pro



Distilling spider with 5 flasks(without flask)

Cat. No.	Volume	Size
18900194	/	NS 29/32, NS24/29
18900177	/	NS 29/42, NS24/40



Connector

Cat. No.	Volume	Size
18300094	/	NS 29/32, NS24/29
18300095	/	NS 29/32, NS19/26
18300096	/	NS 29/32, NS14/23
18300199	/	NS24/40, NS19/22
18300200	/	NS 24/40, NS14/20
18900193	/	NS 24/40, NS 29/42