

-60°C Freezer



Technical Parameters

Model	BDF-60V30	BDF-60V608	BDF-60V708	BDF-60V808	BDF-60V938
External Size(W*D*H) mm	470*490*1120	940*980*1920	1090*1000*1920	1090*1010*2025	1240*1000*2000
Internal Size(W*D*H) mm	270*265*400	700*680*1255	850*680*1255	850*735*1335	1000*700*1335
Capacity	30L	598L	708L	808L	938L
Type	Vertical				
Temp. Range	-25℃~-60℃				
Temp. Accuracy	0.1℃				
Control System	Microprocessor control, LED Digital Display				
Audible and Visual Alarm	High and low temperature alarm, sensor failure alarm.				
Alarm Method	Sound beeps and lights flash				
Refrigeration Type	Direct refrigeration				
Refrigerant	R404A and R23				
Construction	Foam Layer Thickness	100mm	120mm		
	Internal Material	304 stainless steel			
	External Material	Sprayed steel plate			
Consumption	400W	1100W	1100W	1150W	1150W
Power Supply	AC110V/220V±10%, 50/60Hz				
Package Size(W*D*H) mm	540*560*1285	1025*1050*2090	1220*1080*2070	1175*1075*2180	1325*1070*2170
Gross Weight	85kg	315kg	350kg	365kg	405kg

-60°C Freezer



Technical Parameters

Model	BDF-60V58	BDF-60V108	BDF-60V158	BDF-60V398
External Size(W*D*H)mm	540*620*1115	700*730*1260	700*700*1580	850*960*1860
Internal Size(W*D*H)mm	361*405*408	460*460*510	460*455*800	610*660*1200
Capacity	58L	108L	158L	408L
Temp. Range	-25℃ ~ -60℃, adjustable			
Temp. Accuracy	0.1℃			
Control System & Display	Microprocessor control, LED display			
Audio & Visual Alarm	High or low temperature alarm ;Sensor failure alarm			
Refrigeration Type	Optimized auto-cascade refrigerating system			
Refrigerant	Unique fluoride-free mixed refrigerant, CFC-Free			
Condenser & Evaporator	Optimized evaporation and condensation system, strong cooling and low energy consumption			
Structure	90mm ultra-thick foam layer			
Internal Material	304 stainless steel			
External Material	Sprayed steel plate			
Consumption	450W	480W	500W	550W
Power Supply	AC110V/220V±10%, 50/60Hz			
Package Size(W*D*H)mm	610*690*1275	785*800*1430	785*770*1750	935*1030*2030
Gross Weight	101kg	133kg	150kg	250kg