



Horizontal Laminar Flow Cabinet




LCD Display
Airflow velocity, UV timer, UV work time, system work time, real time.



Waterproof Socket
2 waterproof sockets are located in the side panel, for optimum convenience of using small devices inside the cabinet.



Gas Tap



UV Lamp
Emission of 253.7 nanometers for most efficient decontamination



Side Glass Window
The transparent side glass windows maximize light and visibility inside the cabinet, providing a bright and open working environment.

TECHNICAL PARAMETERS

Model	BBS-H1300	BBS-H1800
External Size (W*D*H)	1300*820*2040mm	1800*820*2070mm
Internal Size (W*D*H)	1200*500*570mm	1700*500*570mm
Work Surface Height	750mm	
Display	LCD Display	
Airflow Velocity	Average of 0.3~0.5m/s	
Material	Main Body: Cold-rolled steel with anti-bacteria powder coating Work Table: 304 stainless steel Side and Front Window: 5mm toughened glass, anti-UV	
Pre-Filter	Polyester fiber, washable	
HEPA Filter	99.999% efficiency at 0.3μm	
Noise	<65dB	
Front Window	Motorized	
Max Opening	430mm	
LED Lamp	12W*1	16W*2
UV Lamp	30W*1	30W*1
	Emission of 253.7 nanometers	
Consumption	400W	500W
Waterproof Socket	Two, total load≤500W	
Caster	Universal caster with leveling feet	
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	
Standard Accessory	LED lamp, UV lamp*2, Base stand, Gas Tap, Waterproof socket*2 Water tap(only for BBS-H1800)	
Optional Accessory	Electric height adjustable base stand	
Gross Weight	254kg	328kg
Package Size(W*D*H)	1450*1060*1650mm	1950*1060*1600mm