

## Split-Type Flake Ice Maker



FIM300

FIM500

### Applicable area

Various types of experiments, hospitals, schools, laboratories, medical, chemical applications, supermarkets, hotels and other seafood products stores etc.

### Technical Parameters

Model	FIM300	FIM500
Ice Making Capacity(kg/24h)	300	500
Ice Storage Capacity(kg)	150	200
Ice Shape	Small particle of irregular snow ice	
Input Current(w)	1360	2100
Way of Condensation	Air cooling	
Ambient Temperature	10~35℃	
Water Temperature	2~15℃	
Tank Shell	Stainless steel	
Refrigerant	SECOP /R404a	Embraco/R404a
Standard Accessories	Water inlet pipe*1, Drainage pipe*1, Ice spoon*1	
Optional Accessories	Filter	
Power Supply	AC 220V±10%, 50/60HZ ; 110V±10%, 60HZ	
Net Weight(kg)	95	125
Gross Weight(kg)	125	155
External Size	Head Size	600*760*740
(W*D*H)mm	Ice Tank Size	770*765*1130
Package Size	Head Size	700*850*995
(W*D*H)mm	Ice Tank Size	860*870*1050

## Cube Ice Machine



CIM-65/80/120

CIM-180/210/260

### Application

- \* Cube ice, large contact area, adjustable ice thickness.
- \* Stainless steel and ABS engineering plastic shell, beautiful shape, strong, practical.
- \* Nickel-plated copper ice plate, flowing vertical ice making, high ice making efficiency, energy saving.
- \* "Intelligent core" control system, automatic ice making, automatic ice falling, ice full detection.
- \* One-button cleaning function, convenient daily maintenance.
- \* LED screen, clear operation, accurate understanding of the machine's working conditions.
- \* The tank, sink, and water distribution pipe all meet the food grade standards, safe and hygienic.
- \* Built-in refrigerator.
- \* The three basic parts (computer board, fan, condenser) are guaranteed for five years.

### Technical Parameters

Model	CIM-65	CIM-80	CIM-120	CIM-180	CIM-210	CIM-260
Ice Making Capacity(kg/24h)	30	40	60	80	100	120
Ice Storage Capacity(kg)	15			45		
Ice Shape	Standard: Cube Ice 22*22*22mm 10g Optional: Cube Ice 28*13*23mm 7g, Cube Ice 28*28*23mm 15g Choose one of the three Types.					
Ice Grid	4*9	4*10	5*12	5*16	5*18	6*18
Way of Condensation	Standard: Air cooling    Optional: Water cooling					
Ambient Temperature	1℃~40℃					
Water Temperature	5℃~35℃					
Compressor	Wanbao					
Refrigerant	R404A/R290					
Optional Accessories	UV lamp					
Power Supply	Standard: AC220V±10%, 50Hz Optional: AC220V±10%, 60Hz    AC110V±10%, 60Hz					
Input Current(W)	280	300	360	580	600	650
Net Weight(kg)	34	34	35	54	55	56
Gross Weight(kg)	38	38	39	59	60	61
External Size(W*D*H)mm	500*450*800	500*450*800	500*450*800	660*680*930	660*680*930	660*680*930
Package Size(W*D*H)mm	580*510*850	580*510*850	580*510*850	740*750*920	740*750*920	740*750*920