

Lighting Incubator

Features:

- * Large LCD screen.
- * Forced-air convection.
- * Microprocessor controller.
- * Universal casters with lock for easy movement.
- * Double door design, outer door is with viewing window.
- * Polished stainless steel chamber.

Safety Functions:

- * Over temperature alarm.
- * Independent limit temperature alarm system.
- * Leakage current and over-voltage protector.



Large LCD screen



Mechanical lock



Test port



Outer door with observation window

Optional Accessories:

- * RS485 interface.
- * Temperature controlled switch.

Technical Parameters:

Model	BJPX-L200BK
Capacity	200L
Lighting Type	LED cold light source
Temp. Range	With illumination: 10~60°C; Without illumination: 5~60°C
Temperature Resolution	0.1°C
Temperature Fluctuation	±0.5°C
Temperature Deviation	±1.0°C
Lighting Illumination	0~12000lux (5-grade adjustable)
Ambient Temp.	0~40°C
Continuous Working Time	No less than 180h
Refrigerant	R134a (CFC- free)
Shelves	Standard: 2 pcs
Heating Power	900W
Cooling Power	300W
Power Supply	AC220V±10%, 50/60Hz(Standard); AC110±10%, 60Hz(Optional)
Internal Size(mm)	548*472*778
External Size(mm)	760*750*1500
Package Size(mm)	883*870*1645
Gross Weight(kg)	200