

-25°C Freezer



270L



350L

Technical Parameters

Model	BDF-25V270	BDF-25V350
External Size(W*D*H) mm	690*744*1631	690*744*1885
Capacity	270L	350L
Type	Vertical	
Temp. Range	-10℃~-25℃	
Temp. Accuracy	0.1℃	
Control System	Microprocessor Control & LED Display	
Alarm	High or low temperature alarm, power outage alarm,Thermostat alarm,Door switch alarm,battery switch alarm	
Refrigeration Type	Direct Refrigeration	
Refrigerant	R290, CFC free	
Compressor	International famous compressor	
Condenser & Evaporator	Wire tube condenser; Coil type evaporator	
Construction	Structure	Unibody Design & Mono-assembly foaming (Rigid polyurethane insulation material)
	Internal Material	SUS304
	External Material	Cold-rolled steel coated with bacterial powder
Shelve	3pcs	4pcs
Consumption	290W	305W
Power Supply	220V±10%, 50Hz; 110V±10%, 60Hz (Optional)	
Package Size(W*D*H) mm	810*860*1820	810*860*2100
Gross Weight	145kg	165kg

-25°C Freezer



100L



936L

Technical Parameters

Model	BDF-25V100	BDF-25V936
External Size(W*D*H) mm	540*540*880	1304*1000*2017
Internal Size(W*D*H) mm	410*410*670	1000*700*1335
Capacity	100L	936L
Type	Vertical	
Temp. Range	-10℃~-25℃	
Temp. Accuracy	0.1℃	
Control System	Microprocessor control, LED Digital Display	
Audible and Visual Alarm	High and low temperature alarm, sensor failure alarm, power failure alarm, door open alarm, etc.	High and low temperature alarm, sensor failure alarm, thermostat failure alarm, power failure alarm, door open alarm, ambient temperature alarm, condenser failure alarm, filter inspection alarm, abnormal voltage alarm, low battery alarm.
	Alarm Method	Sound beeps and lights flash
Refrigeration type		Direct refrigeration
Refrigerant		R600a
Construction	Foam Layer Thickness	75mm
	Internal Material	HIPS
	External Material	304 stainless steel
		Sprayed steel plate
Consumption	73W	1000W
Power Supply	Standard: AC220V±10%, 50/60Hz; Optional: 110V±10%, 50/60Hz	AC110V/220V±10%, 50/60Hz
Package Size (W*D*H) mm	592*597*917	1360*1135*2170
Gross Weight	34kg	421kg