

-60°C Freezer



Technical Parameters

Model	BDF-60V30		BDF-60V608	BDF-60V708	BDF-60V808	BDF-60V938
External Size(W*D*H) mm	470*490*1120		940*980*1920	1090*1000*1920	1090*1010*2025	1240*1000*2000
Internal Size(W*D*H) mm	270*265*400		700*680*1255	850*680*1255	850*735*1335	1000*700*1335
Capacity	30L		598L	708L	808L	938L
Type	Vertical					
Temp. Range	-25℃~-60℃					
Temp. Accuracy	0.1℃					
Control System	Microprocessor control, LED Digital Display					
Audible and Visual Alarm	High and low temperature alarm, sensor failure alarm.					
Alarm Method	Sound beeps and lights flash					
Refrigeration Type	Direct refrigeration					
Refrigerant	R404A and R23					
Construction	Foam Layer Thickness	100mm	120mm			
	Internal Material	304 stainless steel				
	External Material	Sprayed steel plate				
Consumption	400W	1100W		1100W	1150W	1150W
Power Supply	AC110V/220V±10%, 50/60Hz					
Package Size(W*D*H) mm	540*560*1285	1025*1050*2090		1220*1080*2070	1175*1075*2180	1325*1070*2170
Gross Weight	85kg	315kg	350kg		365kg	405kg

-60°C Freezer



Technical Parameters

Model	BDF-60V58	BDF-60V108	BDF-60V158	BDF-60V398
External Size(W*D*H)mm	540*620*1115	700*730*1260	700*700*1580	850*960*1860
Internal Size(W*D*H)mm	361*405*406	460*460*510	460*455*800	610*660*1200
Capacity	58L	108L	158L	408L
Temp.Range	-25°C ~ -60°C, adjustable			
Temp.Accuracy	0.1°C			
Control System & Display	Microprocessor control, LED display			
Audio & Visual Alarm	High or low temperature alarm ;Sensor failure alarm			
Refrigeration Type	Optimized auto-cascade refrigerating system			
Refrigerant	Unique fluoride-free mixed refrigerant, CFC-Free			
Condenser & Evaporator	Optimized evaporation and condensation system, strong cooling and low energy consumption			
Construction	Structure	90mm ultra-thick foam layer	120mm ultra-thick foam layer	150mm ultra-thick foam layer
	Internal Material	304 stainless steel		
	External Material	Sprayed steel plate		
Consumption	450W	480W	500W	550W
Power Supply	AC110V/220V±10%,50/60Hz			
Package Size(W*D*H)mm	610*690*1275	785*800*1430	785*770*1750	935*1030*2030
Gross Weight	101kg	133kg	150kg	250kg