

Laboratory Refrigerator



656L



1500L

Technical Parameters

Model	BPR-5V650	BPR-5V1500
External Size(W*D*H) mm	1220*642*1885	1800*775*1965
Capacity	656L	1500L
Temp. Range	2~8℃	
Temp. Accuracy	0.1℃	
Control System	Microprocessor Control & Large Screen LED Display	
Alarm	Audible and visual alarm for: High and low temperature, Thermostat fault, Door Ajar, Power Failure	Sensor fault, door Ajar
Refrigeration Type	Forced air refrigeration system	
Refrigerant	R290	R134a, CFC Free
Condenser&Evaporator	High efficiency air-cooled condenser, made of copper	
Defrost	Frostless design	
Construction	Structure	Unibody design & Mono-assembly foaming (rigid polyurethane insulation material)
	Internal Material	Spraying steel plate
	External Material	Spraying steel plate
Shelves	Adjustable shelves made of high quality steel wire	
	10 pcs	12 pcs
Consumption	385W	1040W
Power Supply	AC110/220V±10%, 50/60Hz	AC110/220V±10%, 50/60Hz
Standard Accessory	LED lamp, Shelves, Door keys, Testing hole, Battery	
Package Size(W*D*H) mm	1335*715*2000	1880*820*2150
Gross Weight	189kg	319kg

-25℃ Freezer



BDF-25H305

Features

1. Digital temperature display.
2. The safety lock can prevent random opening.
3. Baskets made of steel wire are convenient to store articles.
4. Round corner design of doors and the body provides luxury and elegance.
5. Delayed start and safe stop interval between restart and being terminated, ensure reliable running.

Technical Parameters

Model		BDF-25H305
External Size(W*D*H) mm		1148*740*872
Capacity		305L
Temp. Range		-10℃~-25℃
Temp. Accuracy		0.1℃
Control System		Microprocessor control&LED display
Alarm		High or low temperature alarm, sensor failure alarm, thermostat alarm, power failure alarm
Refrigeration Type		Direct refrigeration
Refrigerant		R134a
Condenser&Evaporator		Internal-mounted condenser and finned evaporator
Construction	Structure	Whole foaming, freon cyclopentane/isopentane high density polyurethane foam
	Internal Material	Spraying steel plate
	External Material	Spraying steel plate
Basket		none
Consumption		106W
Power Supply		AC220V±10%, 50/60Hz; AC110V±10%, 60Hz
Package Size(W*D*H)mm		1223*777*1005
Gross Weight		87kg