

Ergonomic Design



Audible and Visual Alarms

Audible buzzer and visible flashing light



Multiple Alarm Functions

High/low temperature, power failure, door ajar, sensor error, low battery, and remote alarm



Air Cooling, Auto Defrost

Superior cabinet temperature uniformity auto defrost



Accurate Temperature Control



Interior LED



Lockable Design

Qingdao Haier Biomedical Co., Ltd.

No.280 Feng Yuan Road, High-tech Zone, Qingdao, 266109, P.R. China Tel: +86-0532-88935593 Website: www.haiermedical.com













al Haier Biomedical

@haiermedicalint Hai

Specifications ()



Technical Data

Cabinet Type	Upright	
Climate Class	N	
Cooling Type	Forced air cooling	
Defrost Mode	Auto	
Refrigerant	HC	
Noise (dB (A))	41	

Performance

Temp Range (°C) 2~8

Control

Controller	Microprocessor	
Display	LED	

Electrical Data

Power Supply (V/Hz)	220~240/50	115/60
Power (W)	140	150
Electrical Current (A)	0.85	1.7

Dimensions

Capacity (L/Cu.Ft)	68/2.4		
Net/Gross Weight (approx)	38/40 (kg) 83.8/88.2 (lbs)		
Interior Dimensions (W*D*H)	415*385*505 (mm) 16.3*15.2*19.9 (in)		
Exterior Dimensions (W*D*H)	495*580*660 (mm) 19.5*22.8*26.0 (in)		
Packing Dimensions (W*D*H)	540*640*710 (mm) 21.3*25.2*28.0 (in)		
Container Load (20'/40'/40'H)	102/204/204		





Functions

High/Low Temp	Υ
Power Failure	Υ
Sensor Error	Υ
Low Battery	Υ
Door Ajar	Υ
Remote Alarm	Υ

Accessories

Caster	Υ
Foot	Υ
Porthole	Υ
Shelves / Drawers	2/1

Other

Certification	CE	UL	