

BRUNER

URINE STRIP READER

OP-155

FEATURES

- ✓ LCD displayer and menu-driven interface.
- ✓ Long life, high brightness, cold light source.
- ✓ New type optical sensors: high sensitivity and accuracy, good anti-interference ability.
- ✓ Automatically correct the pH effect to the result of specific gravity.
- ✓ With a high speed, low noise thermal printer.
- ✓ A RS-232C interface used for data exchanging and software upgrading when connected to a PC.
- ✓ 10000 test result can be stored.
- ✓ Each item has a normal range which can be set by the user easily. Results exceeding the range will be marked when output.
- ✓ The sensitivity of each item can be adjusted through the software.
- ✓ 3 kind of result: international, Regular and Symbol.
- ✓ A external printer can be driven directly.
- ✓ 2x USB.



SPECIFICATIONS

- ✓ Test Items: LEU, URO, BIL, NIT, Ph, SG, BLD, GLU, PRO, KET, ASSC;
- ✓ Wavelength: 470nm, 540nm, 620nm;
- ✓ Test Type: Reflectance photometer and Chromaticity analysis;
- ✓ Test mode: Single step mode 60 test per hour 120 tests per hour;
- ✓ Displayer: 192*64 LCD;
- ✓ Storage: Up to 1200 results;
- ✓ Printer: 57mm width thermal printer;
- ✓ Serial Port: RS-232C, D89 male;
- ✓ Parallel Port: DB25 Female;
- ✓ Ambient Operating Temperature range: 10-30°C;
- ✓ Ambient Operating Humidity range: <70%;
- ✓ Power Supply: AC100-240V, 50/60Hz
- ✓ Power: 30VA
- ✓ Dimensions: 253mmx237mmx171mm
- ✓ Weight: 3kg

Biosite

MEDICAL INSTRUMENTS



Manila Office: 738 Shaw Boulevard, Greenfield District,
Mandaluyong City, Metro Manila

Tel: (02)7505-7425 / (02)7505-7443
Phone: (0917)-851-2007 / (0917)-851-2008

Davao Office: 553-555 Manga St., Juna Subdivision Matina,
Davao City

Tel: +682 296-9485
Fax: +682 295-6420

www.biositemedicalinstruments.com.ph