

-86°C Freezer







Technical Parameters

Model		BDF-86V588	BDF-86V728	BDF-86V838	
External Size(W*D*H) mm		880*1080*2000	1260*890*2010	1175*1075*1990	
Internal Size(W*D*H) mm		606*738*1310	963*558*1350	894*718*1310	
Capacity		588L	728L	838L	
Туре		Vertical			
Temp. Range		-40°C~-86°C			
Temp. Accuracy		0.1℃			
Control System		Microprocessor control, LCD touch screen		Microprocessor control, LED Digital Display	
Audible and Visual Alarm		High and low temperature, Sensor failure, Door ajar, Power failure, Voltage abnormal, Ambient temperature abnormal,Low voltage, Filter blocking			
Refrigeration type		Direct refrigeration			
Refrigerant		R290 and R170			
Compressor		2 sets			
Condenser&Evaporator		Made of copper			
:	Structure	150mm ultra-thick foam layer	100mm ultra-thick foam layer	150mm ultra-thick foam layer	
Construction I	Internal Material	SS 304			
i	External Material	Sprayed steel plate			
Door		Lockable door			
Caster		4 casters			
Chamber with Inner Door		2			
Shelf		3 pcs			
Temp. Test Port		1, φ25mm	1,φ25mm	1,φ25mm	
Consumption		815W	935W	1700W	
Power Supply		AC110V/220V±10%, 50/60Hz			
Standard Accessory		72 hours battery backup for power failure alarm, USB port			
Max. Optional Storage Racks		16*LD5×5	24*LD5×4	18*LD7×5	
Max. Optional Boxes		400	480	630	
Package Size (W*D*H) mm		975*1140*2200	1320*970*2190	1270*1100*2185	
Gross Weight		368kg	401.5kg	430kg	

-150°C Freezer





Technical Parameters:

Model		BDF-150H58	BDF-150H128	
External Size(W*D*	H) mm	670*765*1040	1560*957*1178	
Internal Size(W*D*H	H) mm	410*410*385	500*450*578	
Capacity		58L	128L	
Туре		Horizontal		
Temp. Range		-100~-145℃	-40~-150℃	
Temp. Accuracy		0.1℃	0.1℃	
Control System		Microprocessor control, LED Digital Display	Microprocessor control, LCD touch screen	
Audible and Visual	Alarm	Over temperature alarm	High temperature alarm, low temperature alarm, abnormal power supply alarm, sensor failure alarm, thermostat failure alarm, filter screen inspection alarm, ambient temperature alarm, condenser failure alarm.	
Alarm Method		Sound beeps and lights flash		
Refrigeration type		Direct refrigeration		
Refrigerant		Mixed refrigerants		
Compressor		1 set	1 set	
	Foam Layer Thickness	130mm	200mm	
Construction	Internal Material	304 stainless steel		
	External Material	prayed steel plate		
Consumption		1800W	2550W	
Power Supply		AC110V/220V±10%, 50/60Hz	380V, 50Hz	
Power Supply				
Package Size (W*D	*H) mm	710*810*1080	1637*970*1383	

30 31