

## Electronic Bottle-Top Dispenser



### Features:

- \* Motor operation minimizes the grip force.
- \* Electronic control decreases the repetitive strain injury.
- \* Remote control panel prevents manual disturbance during operation.
- \* Two dispensing modes.
- \* Dispenser.
- \* Stepper function.

### Technical Parameters:

Model	DFlow
Item No.	7012300001
Volume Range	0.01~99.99ml, Max piston lift is 10ml, resolution is 10µl
Volume Accuracy	R=0.2% CV=0.07%
Operating Temperature Range	10℃~30℃
Quality Control	DIN EN ISO 8655
Contro Type	External control, including the stirrer and the burette program

## Bath / Circulator Thermostatic Water Bath



### Features:

- \* Stainless steel inner chamber and upper cover.
- \* Adopt new design structure, which could avoid the leakage of steam.
- \* PID microprocessor controller, LED display.
- \* With universal fixture for SY-1L4H and SY-1L6H.

### Technical Parameters:

Model	SY-1L1H	SY-1L2H	SY-1L4H	SY-1L6H	SY-2L4H	SY-2L6H	SY-2L8H
Capacity	3L	6L	13L	20L	11L	18L	23L
Temp. Range	RT.-100℃						
Temp. Fluctuation	±0.5℃						
Temp. Accuracy	±1℃						
Time Range	0~999min						
Power	300W	500W	1000W	1500W	1000W	1500W	2000W
Power Supply	AC110/220V±10%, 50/60Hz						
Internal Size(mm)	160*160*130	300*160*130	600*180*130	900*180*130	300*300*130	470*300*130	610*300*130
External Size(mm)	200*200*220	345*210*220	770*230*170	1060*230*170	345*345*220	500*340*220	770*370*170
Packing Size(mm)	260*260*280	460*260*280	830*300*250	1150*300*250	400*400*280	600*400*280	830*460*250
Net Weight(kg)	2	4	10	13	6.5	9	12
Gross Weight(kg)	3	5	11	14.5	7.5	10	13