

-25°C Freezer (Separate Refrigerator)



BRF-25V300



BRF-25V318



BRF-25V368



BRF-25V450

Technical Parameters

Model	BRF-25V300	BRF-25V318	BRF-25V368	BRF-25V450
External Size(W*D*H) mm	650*620*1980	741*631*1889	750*736*1884	741*881*1889
Capacity	Refrigerator:198L, internal size 565*480*759mm Freezer:102L, internal size 461*465*600mm	Refrigerator:318L Freezer:110L	Refrigerator:183L Freezer:185L	Refrigerator: 295L,internal size 590*675*746mm Freezer:155L,internal size 520*647*460mm
Temp.Range	Refrigerator: 2℃~8℃; Freezer: -10℃~-25℃			
Temp. Accuracy	0.1℃			
Control System	Microprocessor control			
Alarm	Sensor failure alarm, high or low temperature alarm,open the door alarm;Thermostat failure,power failure alarm			
Cooling Method	Direct cooling	Refrigerator: Air cooling Freezer: Direct cooling	Refrigerator: Air refrigeration Freezer: Direct cooling	Refrigerator: Air refrigeration Freezer: Direct cooling
Refrigerant	R290, CFC free			Refrigerator: R290/50g Freezer: R290/57g
Condenser	Aluminum and iron pipes	Bundy tube	Wire tube condenser	
Construction	Structure	Unibody design and thickened environmental protection foam insulation layer		
	Internal Material	PS plate	304 stainless steel	
	External Material	Pre-coated galvanized plate	Sprayed steel plate	Steel plate with powder
Shelf / Drawer	Refrigerator: 2 shelves Freezer: 3 shelves		Refrigerator:2 shelves Freezer:2 shelves	Refrigerator: 3 shelves Freezer: 1 shelve
Consumption	333W	420W	300W	395W
Power Supply	Standard:220V 50/60Hz,optional:110V 60Hz			
Package Size(W*D*H) mm	720*695*2015	880*770*2090	890*875*2052	880*950*2090
Gross Weight	120kg	178kg	195kg	197kg