Flake Ice Maker



FIM20/30/40/50

FIM60/70/85

Technical Parameters

| Model | FIM20 | FIM30 | FIM40 | FIM50 | FIM60 | FIM70 | FIM85 |
|-----------------------------|-----------------|--|----------------|---------------------------------------|-------------|-------|-------|
| Ice Making Capacity(kg/24h) | 20 | 30 | 40 | 20 | 09 | 20 | 85 |
| Ice Storage Capacity(kg) | 10 | 10 | 15 | 15 | 25 | 25 | 25 |
| Ice Shape | Small particle | Small particle of irregular snow ice | ow ice | | | | |
| Input Current(W) | 280 | 300 | 360 | 380 | 420 | 460 | 480 |
| Way of Condensation | Air cooling | | | | | | |
| Ambient Temperature | 10~35°C | | | | | | |
| Water Temperature | 2~15°C | | | | | | |
| Tank Shell | Stainless steel | <u>a</u> | | | | | |
| Compressor | Donper | | Panasonic M | Panasonic Wanbao (for FIM40-100) | 140-100) | | |
| Refrigerant | R290 | | R290 | | | | |
| Standard Accessories | Water inlet pi | Water inlet pipe*1, Drainage pipe*1, Ice spoon*1 | pipe*1, Ice sp | oon*1 | | | |
| Optional Accessories | Filter | | | | | | |
| Power Supply | AC 220V±10 | AC 220V±10%, 50/60HZ; 110V±10%, 60HZ | 0V±10%, 60HZ | | | | |
| Net Weight(kg) | 26 | | 36 | | 42 | | |
| Gross Weight(kg) | 42 | | 56 | | 62 | | |
| External Size(W*D*H)mm | 330*470*605 | | 400*543*720 | 11 | 400*510*875 | | |
| Package Size(W*D*H)mm | 460*590*740 | | 520*660*840 | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | 520*640*960 | | |

Flake Ice Maker

 \mathcal{C}



Technical Parameters

| Model | FIM100 | FIM120 | FIM150 | FIM200 | FIM250 |
|-----------------------------|--|----------------------|--------|------------------|--------|
| Ice Making Capacity(kg/24h) | 100 | 120 | 150 | 200 | 250 |
| Ice Storage Capacity(kg) | 40 | 40 | 40 | 09 | 09 |
| Ice Shape | Small particle of irregular snow ice | ular snow ice | | | |
| Input Current(w) | 520 | 550 | 089 | 1040 | 1100 |
| Way of Condensation | Air cooling | | | | |
| Ambient Temperature | 10~35°C | | | | |
| Water Temperature | 2~15°C | | | | |
| Tank Shell | Stainless steel | | | | |
| Compressor | Panasonic Wanbao Donper | Donper | | Panasonic Wanbao | bao |
| Refrigerant | R290 | | | | |
| Standard Accessories | Water inlet pipe*1, Drainage pipe*1, Ice spoon*1 | ainage pipe*1, Ice s | poon*1 | | |
| Optional Accessories | Filter | | | | |
| Power Supply | AC 220V±10%,50/60HZ; 110V±10%, 60HZ | 1Z; 110V±10%, 60F | ĮZ | | |
| Net Weight(kg) | 58 | | 09 | 80 | |
| Gross Weight(kg) | 82 | | 84 | 105 | |
| External Size(W*D*H)mm | 500*611*940 | | | 680*611*1100 | |
| Package Size(W*D*H)mm | 720*620*1160 | | | 730*790*1320 | |

Various types of experiments, hospitals, schools, laboratories medical, chemical applications, supermarkets, hotels and other seafood products stores etc.

44