

-25°C Freezer

Features

- 1.Digital temperature display.
- 2. The safety lock can prevent random opening.
- 3.Baskets made of steel wire are convenient to store articles.
- 4.Round corner design of doors and the body provides luxury and elegance.
- 5.Delayed start and safe stop interval between restart and being terminated, ensure reliable running.



BDF-25H305

Technical Parameters

Model		BDF-25H305	
External Size(W*D*H) mm		1148*740*872	
Capacity		305L	
Temp. Range		-10℃~-25℃	
Temp. Accuracy Control System		0.1℃ Microprocessor control&LED display	
Alarm		High or low temperature alarm, sensor failure alarm, thermostat alarm, power failure alarm	
Refrigeration Type		Direct refrigeration	
Refrigerant		R134a	
Condenser&Evaporator		Internal-mounted condenser and finned evaporator	
Construction	Structure	Whole foaming, freon cyclopentane/isopentane high density polyurethane foam	
	Internal Material	Spraying steel plate	
	External Material	Spraying steel plate	
Basket		none	
Consumption		106W	
Power Supply		AC220V±10%,50/60Hz; AC110V±10%,60Hz	
Package Size(W*D*H)mm		1223*777*1005	
Gross Weight		87kg	

-40°C Freezer





Technical Parameters

Model		BDF-40V90	BDF-40V268II	
External Size(W*D*H)		600*610*945mm	690*744*1631mm	
Internal Size(W*D*H)		440*447*640mm	520*567*1013mm	
Capacity		90L	268L	
Туре		Vertical all export@biobase.com		
Temp. Range		-15℃~-40℃		
Temp. Accuracy Control System		0.1℃ Microprocessor Control; LED Display		
Alarm		BDF-40V90: High or low temperature alarm,sensor	High or low temperature alarm, door ajar alarm,	
		failure alarm,power failure alarm,door open alarm.	power failure alarm, sensor failure alarm	
Refrigeration Type		Direct Refrigeration		
Refrigerant		R290	CFC free	
Compressor		Unicompressor,imported famous brand compressor	International well-known brand	
	Structure	Uniboday design		
Construction	Internal Material	304 stainless steel	Stainless steel	
	External Material	Sprayed steel plate		
Drawer/Shelf		2 pcs shelves	3pcs shelves,Stainless Steel	
Consumption		252W	335W	
Power Supply		AC220V±10%, 50/60HZ	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	
Package Size		725*735*1160mm	810*860*1820mm	
Gross Weight		83kg	165kg	

16 17