



PP Vertical Laminar Flow Cabinet

ADVANTAGE

1. Made of PP material, integrally welded
2. Resistant to strong acid, alkali and strong corrosion
3. With memory function in case of power-failure
4. Interlock function: UV Lamp and blower, LED Lamp
5. The work surface is seamlessly welded with 12mm thick PP plate, which is convenient for overall cleaning




LCD Display

Airflow velocity, UV timer, UV work time, system work time, real time.



Waterproof Socket

2 waterproof sockets are located in the side panel, for optimum convenience of using small devices inside the cabinet.



UV Lamp

Emission of 253.7 nanometers for most efficient decontamination.



Footmaster Caster

Universal caster with brake and leveling feet

TECHNICAL PARAMETERS

Model	BKCB-800P
External Size (W*D*H)	800*710*1800mm
Internal Size (W*D*H)	780*540*550mm
Work Surface Height	750mm
Material	Main Body: Made of Porcelain white PP, thickness 8mm, resistant to strong acid, alkali and anti-corrosion. Work Table: Seamlessly welded with 12mm thick PP plate
Front & Side Windows	5mm toughened glass, anti-UV, Manual
Pre-Filter	Polyester fiber, Washable
Filter Size (W*D*H)	560*340*46mm
HEPA Filter	99.995% efficiency at 0.3μm
Airflow Velocity	0.3-0.5m/s
Noise	≤65dB
Max. Opening	400mm
UV Lamp	20W*1, Emission of 253.7 nanometers, with UV time
LED Lamp	8W
Illumination	≥350lx
Caster	Foot master Caster
Waterproof Socket	Two, total load500W
Consumption	650W
Standard Accessory	UV lamp; Led lamp; Base stand; Waterproof socket*2
Optional Accessory	Water Sink; Water tap
Power Supply	220V, 50/60Hz (Standard); 110V, 60Hz(Optional)
Package Size (W*D*H)	1000*900*1300mm
Gross Weight	90kg