



Class I
Biological Safety
Cabinet



BYKG-V



BYKG-I/II



BYKG-III

ADVANTAGE

- 1. UV lamp for sterilization.
- 2. Soft touch control panel, LCD display.
- 3. Energy-saving, high efficiency, low noise.
- 4. With memory function in case of power-failure.
- 5. One piece 304 stainless steel work stable, easy for cleaning.
- 6. Stable air flow system; provide firm protection to person and environment.

TECHNICAL PARAMETERS

Model	BYKG-I	BYKG-II	BYKG-III	BYKG-V
External Size(W*D*H)	550*395*730mm	700*550*900mm	900*713*1250mm	1100*895*1924mm
Internal Size(W*D*H)	540*385*440mm	680*540*500mm	800*635*600mm	968*695*630mm
HEPA Filter	99.999% efficiency at 0.3µm			
Airflow Velocity	>0.3m/s	0.75~1.0m/s	>0.3m/s	0.75~1.0m/s
Noise	≤60dB	≤55dB	≤60dB	≤67dB
Illuminating Lamp	4W*1	8W*1	8W*1	21W*2
	LED lamp	LED lamp	LED lamp	Fluorescent lamp
	15W*1	20W*1	20W*1	20W*1
UV Lamp	Emission of 253.7 nanometers for most efficient decontamination BYKG-III has UV timer function and the display could indicate the UV life.			
Power Consumption	150W	≤160W	≤400W	≤350W
Work Surface Height	/	/	/	750mm
Caster	/	/	/	Universal castor
Main Body Construction	PMMA	PMMA	Cold-rolled steel with anti-bacteria powder coating	
Work Table	304 stainless steel			
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz			
Standard Accessory	LED lamp, UV lamp*2			Fluorescent lamp, UV lamp*2, Base stand
Optional Accessory	Electric height adjustable base stand			
Gross Weight	38kg	68kg	147kg	185kg
Package Size(W*D*H)	710*550*950mm	870*720*1170mm	1060*870*1440mm	1270*880*2230mm