

## Horizontal Cylindrical Pressure Autoclave



### Features:

- \* Drying function.
- \* Automatic sterilization process.
- \* Safety valve for over pressure protection.
- \* Over-temperature, over-pressure protection device.
- \* Interlock function.
- \* 304 stainless steel material chamber.
- \* Automatically in case of low water level.
- \* Water level sensor. The power will be cut-off.
- \* Double door optional.

### Technical Parameters:

Model	BKQ-H150	BKQ-H200	BKQ-H300	BKQ-H400	BKQ-H500
Capacity	150L	200L	280L	400L	500L
Chamber Size(mm)	φ440*1000	φ515*1000	φ600*1000	φ700*1100	φ700*1300
Working Pressure	0.22MPa				
Working Temp.	134℃				
Temperature Range	105~134℃				
Sterilization Time	0~60 min				
Drying Time	0~60 min				
Temp. Display Accuracy	≤±2℃				
Consumption	9KW		12KW	18KW	
Power Supply	Standard: 380V, 50Hz(3-phase); Optional: 220V, 50/60Hz(1-phase). Wiring Method: Air switch		Standard: 380V, 50Hz(3-phase); Optional: 220V, 60Hz(3-phase). Wiring Method: Air switch		
External Size (W*D*H) mm	1400*600*1300	1400*670*1650	1400*770*1780	1430*880*1830	1800*900*1820
Package Size (W*D*H) mm	1550*750*1850	1560*820*1850	1680*920*2100	1600*1050*2100	1850*1050*2100
Gross Weight(kg)	320	350	465	530	580

## Hot Air Sterilizer



### Application:

Hot air sterilizer is used to sterilize small surgical instrument, glass, petri dishes etc.  
This device is suitable for medical and veterinary clinics, hospitals, pharmacies, health care centers, and laboratories.

### Features:

- \* Inner door without glass, outer door with observation window, back inlet and outlet.
- \* Intelligent microcomputer P.I.D temperature controller, accurate temperature control.
- \* Stainless steel tube circular heater.
- \* The inner box adopts circular arc structure design, and the movable partition can be pulled.

### Technical Parameters:

Model	HAS-T50I	HAS-T70I	HAS-T105I	HAS-T200I
Capacity	48L	80L	105L	180L
Temp. Range	RT+10~250℃			
Temp. Precision	0.1℃			
Temp. Fluctuation	±1℃			
Ambient Temp.	5~40℃			
Timing Range	0~9999min			
Shelves No.	2 pcs			
Consumption	1000W	1500W	1600W	2450W
Power Supply	AC220V 50Hz(Standard); 110V 60Hz(Optional)			
Internal Size(W*D*H) mm	419*332*348	450*397*450	550*348*550	602*498*602
External Size(W*D*H) mm	728*595*532	750*680*635	850*620*735	900*775*785
Package Size(W*D*H) mm	780*640*655	855*735*755	925*665*860	1000*835*935
Gross Weight(kg)	60	80	115	145