



Ducted PP Fume Hood





LED Display



PP Sink resistant to acid, alkali and anti-corrosion



Water&Gas Remote Control

ADVANTAGE

- 1. It is safer to use anti-corrosive water tap.

- Microprocessor control system, LED display.
 With memory function in case of power-failure.
 Made of porcelain white PP, resistant to acid, alkali and anti-corrosion.
 Front window which is made of thick transparent toughened glass maximize light and visibility inside the fume hood, providing a bright and open working environment.

TECHNICAL PARAMETERS

Model		FH1000(P)	FH1200(P)	FH1500(P)	FH1800(P)
External Size (W*D*H)	(W*D*H)	1047*800*2450mm	1247*800*2450mm	1547*800*2450mm	1847*800*2450 mm
Internal Size (W*D*H)	W*D*H)	787*560*700mm	987*560*700mm	1287*560*700mm	1587*560*700 mm
Work Surface Height	Height	820mm			
Max Opening		740mm			
Air Velocity		0.3~0.8m/s			
Noise		s68dB			
Exhaust Duct		4.3meters, Ф250mm			
LED Lamp		24W*1	24W*1	30W*1	38W*1
Blower		Built-in PP centrifugal	blower (2 blowers for Fi	Built-in PP centrifugal blower (2 blowers for FH1800(P) only); Speed adjustable	djustable
Front Window		Resistant to acid and	alkali, Manual, 5mm tou	Resistant to acid and alkali, Manual, 5mm toughened glass, height adjustable	ustable
Power Supply	TC: MAN	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	4z; 110V±10%, 60Hz		at ave.con
Consumption		400W	400W	500W	700W
Material	Main Body	Made of Porcelain wh	ite PP, thickness 8mm,	Made of Porcelain white PP, thickness 8mm, resistant to strong acid, alkali and anti-corrosion	alkali and anti-corrosion
	Work Table	Chemical resistant phenolic resin	enolic resin		
Standard Accessory	ssory	LED light;Work table:Chemical resistant is 4.3 meters PVC dudt (2 Pcs of 4.3 meter Ppe stray2/4 Pcs of re-11800(P) only); PVV power cord (3*1.0 mm**3000mm); BW tere riap(PP); Gas tap(PP); Water Slink; PP centrifugal blower*1(2 for FH1800(P))	LED light, Work table: Chemical resistant phenolic resin; 4.3 meters PVC duct (2 Pcs of 4.3 meters PVC duct for Plyes strap*2(4 Pcs for EH1800(P) only); RVV power cod (3*1.0mm*3000mm); Base cabinet; Water tap(PP); Gas tap(PP); Water Sink; PP centrifugal blower*1(2 for FH1800(P) only)	LED light, Work table: Chemical resistant phenolic resin; 4.3 meters PVC duct (2 Pcs of 4.3 meters PVC duct for FH1800(P) only), Diameter: 250mm; Plpe strap*2(4 Pcs for FH1800(P) only); PVV power od (3*1,0mm*3000mm); Base cabinet; Waterproof socket*2; Tail insert; Water tap(PP); Gas tap(PP); Water Sink; PP centrifugal blower*1(2 for FH1800(P) only)	uly), Diameter: 250mm; et*2; Tail insert;
Optional Accessory	ssory	PP work table, epoxy: blower *1 (only need to Splicable base cabinet	PP work table, epoxy resin board or ceramic bc blower *1 (only need to select when the duct m Splicable base cabinet(only not for FH1800(P))	PP work table, epoxy resin board or ceramic board;Active carbon filler; Outer PP centrifugal blower *1 (only need to select when the duct more than 4m,2 for FH1800(P) only); Splicable base cabinet(only not for FH1800(P))	; Outer PP centrifugal 00(P) only);
Gross Weight	Main Body Base Cabinet	137kg 89kg or 80kg(Splicable)	155kg 99kg or 90kg(Splicable)	180kg 114kg or 102kg(Splicable)	206kg 140kg
	Main Body	1188*938*1612mm	1388*938*1612mm	1688*938*1612mm	1988*938*1612mm
Package Size (W*D*H)	Base Cabinet	1188*888*1000mm or 1200*1000*450mm (Splicable)	1388*888*1000mm or 1400*1000*450mm (Splicable)	1688*888*1000mm or 1700*1000*450mm (Splicable)	1988*888*1000mm

-Version 2022 055/056