# Constant-Temperature Incubator

**Features:**

＊ Microcomputer-based smart temperature controller.

＊ LCD display for settingtemperature and the temperature in the chamber, parameter memory and recoveryfunction for the purpose of protection against power failure, computer system haltand data loss; protection and alarming against excessive temperature, failure ofsensors,creepag and , over-current; sound & light alarming; timing function.

＊ Separate temperature limiting and alarming system, automatic suspension in time of exceeding temperature limit (optional).

＊ UV sterilizing system (optional).

＊ RS-485 portal, capable of being connected with printer or computer, recording variations of temperature parameters (optional).

＊ Double door (optional).

**Technical Parameters:**

| Model | BJPX-H50IV | BJPX-H80IV | BJPX-H160IV | BJPX-H270IV |
|---|---|---|---|---|
| Capacity | 50L | 80L | 160L | 270L |
| Temp.Range | RT+5~65℃ | | | |
| Temp.Resolution | 0.1 | | | |
| Temp.Fluctuation | ±0.5℃ | | | |
| Temp. Uniformity | ±1℃(37℃) | | | |
| Time Range | 1~9999mins | | | |
| Shelves(Standard) | 2pcs | | | |
| Consumption | 250W | 300W | 400W | 600W |
| PowerSupply | AC220V±10%, 50/60Hz(Standard) | | | |
| | AC110±10%, 60Hz(Optional) | | | |
| Internal Size(mm) | 350*360*410 | 400*400*500 | 500*500*650 | 600*600*750 |
| External Size(mm) | 450*520*680 | 500*560*760 | 600*620*910 | 720*690*1020 |
| Packing Size (mm) | 550*620*780 | 600*660*860 | 700*720*1010 | 820*790*1120 |
| Gross Weight (kg) | 40 | 47 | 70 | 90 |

# Constant-Temperature Incubator

**Features:**

＊ Large LED display, multiple groups of data to be displayed at a time; function of timing and over-temperature protection.

＊ Two-layer toughened-glass observation window.



BJPX-H30/48/64/123II          BJPX-H230II

**Technical Parameters:**

| Model | BJPX-H30II | BJPX-H48II | BJPX-H64II | BJPX-H123II | BJPX-H230II |
|---|---|---|---|---|---|
| Capacity | 30L | 45L | 65L | 125L | 230L |
| Temp. Range | RT+5~80°C | | | | |
| Temp. Fluctuation | ±0.2°C | | | | |
| Time Setting | 1~9999mins | | | | |
| Shelves | 2 pcs/adjustable | | | | |
| Consumption | 150W | 250W | 500W | 600W | 700W |
| Power Supply | AC220V±10%, 50/60Hz(Standard); AC110±10%, 60Hz(Optional) | | | | |
| Internal Size(mm) | 310*310*310 | 350*350*350 | 400*360*450 | 500*450*550 | 600*500*750 |
| External Size(mm) | 460*510*695 | 500*550*735 | 550*550*840 | 636*680*915 | 730*670*1220 |
| Package Size(mm) | 550*570*765 | 620*585*800 | 640*640*905 | 730*720*1000 | 900*800*1350 |
| Gross Weight(kg) | 51 | 56 | 62 | 71 | 105 |