BRUMER

URINE STRI READER

OP-1550A

FEATURES

- High speed, only 7 seconds per test;
- LCD display, operating easy with friednly interface;
- Gather the used strips automatically;
- High brightness and long live light source(LED);
- New type light sensor, high-sensitivity, good antiinterface;
- Inbuilt thermal printer;
- Touch panel;
- RS-232 Interface for data exchange and system software update;
- Parallel port fir connecting with external printer;
- Store 2000 samples;
- The sensitivity of each parameter can be adjusted through software interface;

SPECIFICATIONS

- Parameters: GLU, BIL, SG,PH,KET,BLD,PRO,URO,NIT,LEU,VC;
- Wavelength: 470nm, 540nm, 625nm;
- Principle: Reflectance photometry;
- Strip: 10 parameters, 11 parameters or more;
- Test speed: 514TEST/per hour;
- LCD model: 320x240 Dot matrix;
- Storage: 2000 test reports;
- Printing: Built in thermal printer, or external printer as an option;
- Working Temp: 10-30°C
- Relative Humidity ≤70%
- Power Supply: AC100-240V, 50/60Hz
- Power:<45VA
- Dimensions: 390x330x210mm
- Weight: 7kg







Manila Office: 738 Shaw Boulevard, Greenfield District, Mandaluyong City, Metro Manila

Tel: (02)7505-7425 / (02)7505-7443

Phone: (0917)-851-2007 / (0917)-851-2008

Davao Office: 553-555 Manga St., Juna Subdivision Matina, **Davao City**

Tel: +682 296-9485

Fax: +682 295-6420

www.biositemedicalinstruments.com.ph