-25°C Freezer

## -25°C Freezer





## Techi



ì	۲	4
i	a	נ
1	ā	;
	٤	
	g	0
i	σ	1
۵	ì	
-		
	י	֡
٠	Ė	_
1	٩	

Model		BDF-25V100	BDF-25V936
External Size(W*D*H) mm	N*D*H) mm	540*540*880	1304*1000*2017
Internal Size(W*D*H) mm	V*D*H) mm	410*410*670	1000*700*1335
Capacity		100L	936L
Туре		Vertical	
Temp. Range		-10℃~-25℃	
Temp. Accuracy	y	0.1℃	
Control System	_	Microprocessor control, LED Digital Display	
	E-mai	: export@bio	High and low temperature alarm, sensor failure alarm, thermostat
	www big	High and low temperature	failure alarm, power failure
		alarm, sensor failure alarm,	alarm, door open alarm,
Audible and Visual Alarm	sual Alarm	power failure alarm, door	ambient temperature alarm,
		open alarm, etc.	condenser failure alarm, filter
			inspection alarm, abnormal
			voltage alarm, low battery alarm.
Alarm Method		Sound beeps and lights flash	
Refrigeration type	ype	Direct refrigeration	
Refrigerant		R600a	R404A
	Foam Layer Thickness	75mm	150mm
Construction	Internal Material	HIPS	304 stainless steel
	External Material	Sprayed steel plate	
Consumption		73W	1000W
Power Supply		Standard: AC220V±10%, 50/60Hz; Optional: 110V±10%, 50/60Hz	AC110V/220V±10%, 50/60Hz
Package Size (W*D*H) mm Gross Weight	(W*D*H) mm	592*597*917 34kg	1360*1136*2170 421kg

