

-40°C Freezer



Technical Parameters

Model	BDF-40V398
External Size(W*D*H)	890*900*1780mm
Internal Size(W*D*H)	610°615*1120mm
Capacity	408L
Туре	Vertical
Temp. Range	-10°C~-40°C
Temp. Accuracy	off ill over out his book open
Control Svetom	Microprocessor Control
Collino System	LED Display Dasce, CC / WAXAVA Displayer, COM
Alarm	BDF-40V328: High or low temperature alarm, power failure alarm,
	door ajar alarm, thermostat failure alarm, sensor failure alarm
Refrigeration Type	Direct Refrigeration
Refrigerant	CFC free
Compressor	International well-known brand
Structure	Uniboday design
Material Internal	Stainless steel
External	Painted steel panel,150mm foaming insulation
Shelf	3pcs shelves, Stainless Steel
Consumption	420W
Power Supply Package Size Gross Weight	AC220V±10%, 50/60Hz, 110V±10%, 60Hz 980*1000*1950mm 215ka

-40°C Freezer



Technical Parameters

Model		BDF-40V528
External S	External Size(W*D*H)	900*819*1828mm
Internal Si	Internal Size(W*D*H)	651*631*635mm 651*631*635mm
Capacity		2581
Туре		Vertical
Temp. Range Temp. Accuracy	nge	20-40'CIII: export@biobase.com
Control System	ystem	Microprocessor Control & CC / WAVAVA, DIODASSE, COTT
Alarm		High or low temperature alarm, power failure alarm, door ajar alarm, thermostat failure alarm, sensor failure alarm (of BDF-40V528 without this alarm)
Refrigeration Type	ion Type	Direct Refrigeration
Refrigerant	ŧ	R290
Compressor	sor	Unicompressor,imported famous brand compressor
	Structure	Uniboday design
Material	Internal	Sprayed steel plate
	External	Sprayed steel plate
Drawer/Shelf	helf	18 drawers
Consumption	tion	340W
Power Supply	pply	AC220V±10%, 50/60Hz, 110V±10%, 60Hz
Package Size Gross Weight	Size	930'970"2000mm 184kg

21