

Laboratory Refrigerator



Technical Parameters

Model	BPR-SV650	BPR-SV1500
External Size(W*D*H) mm	1220*642*1885	1800*775*1965
Capacity	656L	1500L
Temp. Range	2~-8℃	
Temp. Accuracy	0.1℃	
Control System	Microprocessor Control & Large Screen LED Display	
Alarm	Audible and visual alarm for: High and low temperature, Thermostat fault, Door Ajar, Power Failure	Sensor fault, door Ajar
Refrigeration Type	Forced air refrigeration system	
Refrigerant	R290	R134a, CFC Free
Condenser&Evaporator	High efficiency air-cooled condenser, made of copper	
Defrost	Frostless design	
Structure	Unibody design & Mono-assembly foaming (rigid polyurethane insulation material)	
Construction	Internal Material External Material	Stainless steel Stainless steel
Shelves	Adjustable shelves made of high quality steel wire	
Consumption	10 pcs	12 pcs
Power Supply	385W	1040W
Standard Accessory	AC110/220V±10%, 50/60Hz	AC110/220V±10%, 50/60Hz
Package Size(W*D*H) mm	LED lamp, Shelves, Door keys, Testing hole, Battery	
Gross Weight	1335*715*2000	1880*820*2150
	189kg	319kg

-25℃ Freezer



Features

1. Digital temperature display.
2. The safety lock can prevent random opening.
3. Baskets made of steel wire are convenient to store articles.
4. Round corner design of doors and the body provides luxury and elegance.
5. Delayed start and safe stop interval between restart and being terminated, ensure reliable running.

Technical Parameters

Model	BDF-25H305
External Size(W*D*H) mm	1148*740*872
Capacity	305L
Temp. Range	-10℃~-25℃
Temp. Accuracy	0.1℃
Control System	Microprocessor control&LED display
Alarm	High or low temperature alarm, sensor failure alarm, thermostat alarm, power failure alarm
Refrigeration Type	Direct refrigeration
Refrigerant	R134a
Condenser&Evaporator	Internal-mounted condenser and finned evaporator
Construction	Structure Internal Material External Material
	Whole foaming, freon cyclopentane/isopentane high density polyurethane foam Spraying steel plate Spraying steel plate
Basket	none
Consumption	106W
Power Supply	AC220V±10%, 50/60Hz; AC110V±10%, 60Hz
Package Size(W*D*H)mm	1223*777*1005
Gross Weight	87kg