

## -40°C Freezer



## **Technical Parameters**

Model	BDF-40V398
External Size(W*D*H)	890*900*1780mm
Internal Size(W*D*H)	610*615*1120mm
Capacity	408L
Туре	Vertical
Temp. Range	-10℃~-40℃
Temp. Accuracy	0.1°C
OtI Ot	Microprocessor Control
Control System	LED Display Dase, cc. / www.biobase.com
17.17	BDF-40V398: High or low temperature alarm,sensor failure alarm;
Alarm	BDF-40V328: High or low temperature alarm, power failure alarm,
	door ajar alarm, thermostat failure alarm, sensor failure alarm
Refrigeration Type	Direct Refrigeration
Refrigerant	CFC free
Compressor	International well-known brand
Structure	Uniboday design
Material Internal	Stainless steel
External	Painted steel panel,150mm foaming insulation
Shelf	3pcs shelves,Stainless Steel
Consumption	420W
Power Supply Package Size	AC220V±10%, 50/60Hz; 110V±10%, 60Hz 980*1000*1950mm
Gross Weight	215kg

## -40°C Freezer



## **Technical Parameters**

Toolinear arameters			
Model		BDF-40V528	
External Size(W*D*H)		900*819*1828mm	
Internal Size(W*D*H)		651*631*635mm 651*631*635mm	
Capacity		528L	
Туре		Vertical	
Temp. Range Temp. Accuracy		-20~-40°cil: export@biobase.com	
Control System		Microprocessor Control  LED Display	
Alarm		High or low temperature alarm, power failure alarm, door ajar alarm, thermostat failure alarm,	
		sensor failure alarm (of BDF-40V528 without this alarm)	
Refrigeration Type		Direct Refrigeration	
Refrigerant		R290	
Compressor		Unicompressor,imported famous brand compressor	
Material	Structure	Uniboday design	
	Internal	Sprayed steel plate	
	External	Sprayed steel plate	
Drawer/Shelf		18 drawers	
Consumption		340W	
Power Supply		AC220V±10%, 50/60Hz; 110V±10%, 60Hz	
Package Size Gross Weight		930°970°2000mm 184ka	
Cross Worgin		loang	

20 21