

# BA-B Series Electronic Analytical Balance (External Calibration)

### Features:

- \* Humanized design, novel design and five-side full-transparent windshield.
- \* A new-generation electromagnetic balance weighing sensor guarantees high precision.
- \* Application programs such as automatic fault detection, four-point linear calibration and over-load protection.
- \* Ultra-large LCD display brings clearer and more comfortable visual sense to operate.



### Functions:

- \* Multiple functions guarantee easy and reliable operation, including auto-counting, unit conversion (metric carat, gold ounce, etc.), stability, full-scale faring, zero-memory, etc.
- \* Built-in RS232C output interface guarantees direct connection to external equipment such as computer and printer.
- \* Built-in lower weighing hook guarantees convenient use.

Power Supply: AC110/220V±10%, 50/60Hz; Power Cord, no battery.

### Technical Parameters:

Model	Capacity	Readability	Scale Size	N.W.	External Size	Package Size	Work Space Height	Calibration
BA504B	0~50g	0.1mg	Ф80mm	6.8kg	350*215*340mm	480*375*515mm	240mm	External Cal
BA604B	0~60g							
BA1004B	0~100g							
BA1104B	0~110g							
BA1204B	0~120g							
BA1604B	0~160g							
BA2004B	0~200g							
BA2204B	0~220g							
BA2104B	0~210g							
BA2104S	0~60g							
	60~210g	/ 1mg						

### Standard Accessory:

Balance body, adapter, weight, windshield, cleaning cloth, tweezers and brush.

## BP-B/P Series Electronic Precision Balance

### Features:

- \* Humanized design, novel design and five-side full-transparent windshield.
- \* A new-generation electromagnetic balance weighing sensor guarantee high precision.
- \* Application programs such as automatic fault detection, four-point linear calibration and over-load protection.
- \* Ultra-large LCD display brings clearer and more comfortable visual sense to operate.
- \* Built-in lower weighing hook guarantees convenient use.



### Functions:

- \* Multiple functions guarantee easy and reliable operation, including auto-counting, unit conversion (metric carat, gold ounce, etc.), stability, full-scale faring, zero-memory, etc.
- \* Built-in RS232C output interface guarantees direct connection to external equipment such as computer and printer.
- \* Built-in lower weighing hook guarantees convenient use.

Power Supply: AC110/220V±10%, 50/60Hz; Power Cord, no battery.

### Technical Parameters:

Model	Capacity	Readability	Scale Size	N.W.	External Size	Package Size	Work Space Height	Calibration
BP1003B	0~100g	1mg	Ф80mm	6.8kg	350*215*340mm	480*375*515mm	240mm	External Cal
BP1203B	0~120g							
BP2003B	0~200g							
BP3003B	0~300g							
BP4103B	0~410g		Ф110mm					
BP5003B	0~500g							
BP10003	0~1000g			6kg				
BP1003P	0~100g		Ф80mm	6.8kg				
BP2003P	0~200g							

### Standard Accessory:

Balance body, adapter, weight, windshield, cleaning cloth, tweezers and brush.

143