



Ducted Fume Hood

ADVANTAGE

1. Adjustable air speed: 9 levels.
2. Microprocessor control system, LED display.
3. Resistant to moderate acid and alkali.
4. With memory function in case of power-failure.
5. Manual front glass window, height adjustable.
6. Built-in PP centrifugal blower; low noise, easy installation.

TECHNICAL PARAMETERS

Model	FH1000(E)	FH1200(E)	FH1500(E)	FH1800(E)
External Size(W*D*H)	1000*800*2515mm	1200*800*2515mm	1500*800*2515mm	1800*800*2515mm
Internal Size(W*D*H)	790*600*870mm	990 *600*870mm	1290*600*870mm	1590*600*870mm
Work Surface Height	900mm			
Max Opening	750mm			
Air Velocity	0.3~0.8m/s			
System Exhaust Volume	570 m³/h	710 m³/h	930 m³/h	1140 m³/h
Noise	≤68dB			
Exhaust Duct	PVC Standard length; 4.3 meters.Ø300mm			
Pipe Strap	2 pcs			
LED Lamp	20W *1	40W *1		
Blower	Built-in PP centrifugal blower			
Front Window	Manual, 5mm toughened glass, height adjustable			
Power Supply	220V±10%, 60/50Hz, 110V±10%, 60Hz			
Consumption	400W	400W	500W	500W
Material	Exterior	1.0mm cold-rolled steel with bacteria power coating.		
	Interior	Compact laminate board with good acid and alkali resistance function		
	Work table	Chemical resistant phenolic resin		
Standard Accessory	Wall-fed air cock(except FH1000(E));Air supply flow control valve(except FH1000(E)); PP Water sink; LED lamp; Total load of 2 waterproof sockets: 500w, Built-in PP blower;4.3 meters Exhaust duct,φ300mm;Base cabinet;Pipe strap(φ280-φ320mm); Water tap;Water supply flow control valve Wall water supply cock (green);Water supply flow control valve			
Optional Accessory	Gas tap			
Gross Weight	270kg	305kg	335kg	365kg
Package	Main Body	1140*940*1900mm	1340*940*1900mm	1640*940*1900mm
	Base Cabinet	1140*940*1050mm	1340*940*1050mm	1640*940*1050mm

