

Blood Bank Refrigerator (Double Door)



Introduction:

Blood bank refrigerator series products are applied to places needing storage at constant temperature, such as hospitals, epidemic prevention stations, blood banks, scientific research institutions, colleges and universities, biological pharmacies, genetic engineering, etc. The storing temperature in the body can be regulated by the temperature button on the control panel. The application is convenient and the performance is reliable.

Advantage:

1. Multiple sensors design: make sure the precise monitoring and programming.
2. Electric heated glass semi-foamed door, easy to observe, also keep a better cooling temperature.
3. Forced air refrigeration system, ensure inner temperature constant and uniform.
4. Adjustable shelves, improve space utilization; blood storage baskets can be classified.
5. Individual transparent inner door, effectively reduce cool air loss when opening the door.

Technical Parameters

Model	BBR-4V626	BBR-4V966
Capacity	626L	966L
Temp. Range	4±2℃	
Temp. Accuracy	0.1℃	
Control System	Microprocessor control	
Display	LED display	
Alarm	Audio and visual alarm for: High or low temperature, Sensor & system failure; Door ajar, Power failure, Low battery	
Refrigeration Type	Forced air refrigeration system	
Refrigerant	R134a, CFC-Free	
Defrost	Frostless Design	
Construction	Unibody Design, Mono-assembly foaming (Rigid polyurethane insulation material)	
Material	Internal Material	Stainless steel
	External Material	Cold-rolled steel with anti-bacteria powder coating
Door	Electric heated glass semi-foamed door with lock, Heating film preventing frosting, Sealing joint strip with magnetic force. Transparent plastic inner door*6	
Shelves	6*2, Adjustable shelves	
Casters	4 casters	
Consumption	550W	560W
Power Supply	AC110V/220V±10%, 50/60Hz	
Blood Bags (450ml)	10*36=360 pcs	16*36=576 pcs
Standard Accessory	Temperature printer, 12 shelves, 36 baskets, LED lamp, probe access port, door key	
Optional Accessory	Temperature recorder	
External Size (W*D*H) mm	1220*665*1885	1220*895*1885
Package Size (W*D*H) mm	1345*770*2020	1345*975*2020
Gross Weight	255kg	330kg