



formation.tech



Formation PHPUnit

Romain Bohdanowicz

Twitter : @bioub

<http://www.formation.tech/>



- Introduction
- PHPUnit
- Assertions
- Types de tests
- Doubles
- Zend Framework 2



Introduction



- ▶ **Romain Bohdanowicz**
Ingénieur EFREI 2008, spécialité en Ingénierie Logicielle
- ▶ **Expérience**
Formateur/Développeur Freelance depuis 2006
Plus de 5000 heures de formation
- ▶ **Langages**
Expert : HTML / CSS / JavaScript / PHP / Java
Notions : C / C++ / Objective-C / C# / Python / Bash / Batch
- ▶ **Certifications**
PHP 5 / PHP 5.3 / PHP 5.5 / Zend Framework 1
- ▶ **Et vous ?**
Langages ? Expérience ? Utilité de cette formation ?



Tests automatisés



▸ Vérification manuelle

- Ecrire une recette de tests et demander à une personne de la rejouer à des étapes clés (nouvelle version)
- Ecrire le test sous la forme de code, et vérifier visuellement que les résultats attendus soit les bons

▸ Tests automatisés

- Le test est codé, la vérification se fait dans un rapport


▸ Historique

- sUnit en 1994 (SmallTalk), JUnit en 1997 (Java)
- Les frameworks s'inspirant de jUnit sont catégorisés xUnit (PHPUnit, CUnit...)



► Types de tests

- **Unitaire** : tests des méthodes d'une classe
- **Intégration** : teste l'intégration entre plusieurs classes
- **Fonctionnels** : teste l'application du point de vue du client (HTTP dans le cas du web)
- **End-to-End (E2E)** : teste l'application dans le client (y compris JavaScript, CSS...)





PHPUnit

PHPUnit - Introduction




- ▶ Créé en 2001 par Sebastian Bergmann
- ▶ Framework de tests de référence en PHP
Utilisé, même étendu par Symfony et Zend Framework

- ▶ Documentation
<https://phpunit.de/documentation.html>

- ▶ Open Source
Licence BSD Modifiée

- ▶ Concurrents :
atoum (FR), Behat (BDD), SimpleTest





▸ PHAR

- Dernière Version
<https://phar.phpunit.de/phpunit.phar>
- Version spécifique
<https://phar.phpunit.de/phpunit-X.Y.Z.phar>

▸ Composer

- Dernière Version
`composer global require phpunit/phpunit`
- Version spécifique
`composer global require phpunit/phpunit:5.0.*`
- Penser à ajouter le répertoire bin global au PATH, sur UNIX :
`~/ .composer/vendor/bin`



► Composer

- Dernière Version
`composer require phpunit/phpunit --dev`
- Version spécifique
`composer require phpunit/phpunit:5.0.* --dev`
- Ou en éditant directement le fichier `composer.json` puis `composer update`

```
{  
  "require-dev" : {  
    "phpunit/phpunit": "5.1.*"  
  }  
}
```

- Exécution depuis la racine du projet :
`./vendor/bin/phpunit`



► Conventions

- Un test PHPUnit est une méthode dont le nom commence par test :
testMaFonction()
- Cette méthode se trouve dans une classe dont le nom se termine par Test et qui hérite de `\PHPUnit_Framework_TestCase` ou `\PHPUnit\Framework\TestCase`

► Bonnes pratiques

- Ne pas hésiter à être le plus verbeux possible dans le nom des méthodes
- L'arborescence du répertoire test correspond au répertoire src (ex : src/MonNamespace/MaClasse.php -> tests/MonNamespaceTest/MaClasseTest.php)

PHPUnit - Exemple



```
<?php

namespace FormationTechTest\Entity;

use FormationTech\Entity\CompteBancaire;

class CompteBancaireTest extends \PHPUnit_Framework_TestCase
{
    public function testCrediter()
    {
        $compte = new CompteBancaire(0);
        $compte->crediter(1000);
        $this->assertEquals(1000, $compte->getSolde());

        $compte->crediter(500);
        $this->assertEquals(1500, $compte->getSolde());
    }
}
```

```
MBP-de-Romain:PrepaFormationPHPUnit romain$ ./vendor/bin/phpunit tests/Entity/CompteBancaireTest.php --colors
PHPUnit 5.1.3 by Sebastian Bergmann and contributors.
```

```
.
```

```
1 / 1 (100%)
```

```
Time: 39 ms, Memory: 1.50Mb
```

```
OK (1 test, 2 assertions)
```



- ▶ PHPUnit peut appeler des méthodes avant et après chaque test
 - setUp
 - tearDown
- ▶ Avant ou après chaque classe (méthodes statiques)
 - setUpBeforeClass
 - tearDownAfterClass

PHPUnit - Ligne de commande



```
MBP-de-Romain:PrepaFormationPHPUnit romain$ ./vendor/bin/phpunit -h
PHPUnit 5.1.3 by Sebastian Bergmann and contributors.
```

```
Usage: phpunit [options] UnitTest [UnitTest.php]
       phpunit [options] <directory>
```

Code Coverage Options:

<code>--coverage-clover <file></code>	Generate code coverage report in Clover XML format.
<code>--coverage-crap4j <file></code>	Generate code coverage report in Crap4J XML format.
<code>--coverage-html <dir></code>	Generate code coverage report in HTML format.
<code>--coverage-php <file></code>	Export PHP_CodeCoverage object to file.
<code>--coverage-text=<file></code>	Generate code coverage report in text format. Default: Standard output.
<code>--coverage-xml <dir></code>	Generate code coverage report in PHPUnit XML format.
<code>--whitelist <dir></code>	Whitelist <dir> for code coverage analysis.

Logging Options:

<code>--log-junit <file></code>	Log test execution in JUnit XML format to file.
<code>--log-tap <file></code>	Log test execution in TAP format to file.
<code>--log-teamcity <file></code>	Log test execution in TeamCity format to file.
<code>--log-json <file></code>	Log test execution in JSON format.
<code>--testdox-html <file></code>	Write agile documentation in HTML format to file.
<code>--testdox-text <file></code>	Write agile documentation in Text format to file.
<code>--reverse-list</code>	Print defects in reverse order

PHPUnit - Ligne de commande



Test Selection Options:

<code>--filter <pattern></code>	Filter which tests to run.
<code>--testsuite <pattern></code>	Filter which testsuite to run.
<code>--group ...</code>	Only runs tests from the specified group(s).
<code>--exclude-group ...</code>	Exclude tests from the specified group(s).
<code>--list-groups</code>	List available test groups.
<code>--test-suffix ...</code>	Only search for test in files with specified suffix(es). Default: Test.php,.phpt

Configuration Options:

<code>--bootstrap <file></code>	A "bootstrap" PHP file that is run before the tests.
<code>-c --configuration <file></code>	Read configuration from XML file.
<code>--no-configuration</code>	Ignore default configuration file (phpunit.xml).
<code>--no-coverage</code>	Ignore code coverage configuration.
<code>--include-path <path(s)></code>	Prepend PHP's include_path with given path(s).
<code>-d key[=value]</code>	Sets a php.ini value.

Miscellaneous Options:

<code>-h --help</code>	Prints this usage information.
<code>--version</code>	Prints the version and exits.
<code>--atleast-version <min></code>	Checks that version is greater than min and exits.

PHPUnit - Ligne de commande



Test Execution Options:

<code>--report-useless-tests</code>	Be strict about tests that do not test anything.
<code>--strict-coverage</code>	Be strict about unintentionally covered code.
<code>--strict-global-state</code>	Be strict about changes to global state
<code>--disallow-test-output</code>	Be strict about output during tests.
<code>--disallow-resource-usage</code>	Be strict about resource usage during small tests.
<code>--enforce-time-limit</code>	Enforce time limit based on test size.
<code>--disallow-todo-tests</code>	Disallow @todo-annotated tests.
<code>--process-isolation</code>	Run each test in a separate PHP process.
<code>--no-globals-backup</code>	Do not backup and restore \$GLOBALS for each test.
<code>--static-backup</code>	Backup and restore static attributes for each test.
<code>--colors=<flag></code>	Use colors in output ("never", "auto" or "always").
<code>--columns <n></code>	Number of columns to use for progress output.
<code>--columns max</code>	Use maximum number of columns for progress output.
<code>--stderr</code>	Write to STDERR instead of STDOUT.
<code>--stop-on-error</code>	Stop execution upon first error.
<code>--stop-on-failure</code>	Stop execution upon first error or failure.
<code>--stop-on-warning</code>	Stop execution upon first warning.
<code>--stop-on-risky</code>	Stop execution upon first risky test.
<code>--stop-on-skipped</code>	Stop execution upon first skipped test.
<code>--stop-on-incomplete</code>	Stop execution upon first incomplete test.
<code>-v --verbose</code>	Output more verbose information.
<code>--debug</code>	Display debugging information during test execution.
<code>--loader <loader></code>	TestSuiteLoader implementation to use.
<code>--repeat <times></code>	Runs the test(s) repeatedly.
<code>--tap</code>	Report test execution progress in TAP format.
<code>--teamcity</code>	Report test execution progress in TeamCity format.
<code>--testdox</code>	Report test execution progress in TestDox format.
<code>--printer <printer></code>	TestListener implementation to use.

PHPUnit - phpunit.xml



```
<?xml version="1.0" encoding="UTF-8"?>
<phpunit colors="true">

  <testsuites>
    <testsuite name="AllTests">
      <directory>tests/Mapper</directory>
    </testsuite>
  </testsuites>

  <filter>
    <blacklist>
      <directory suffix=".php"></directory>
      <file></file>
      <exclude>
        <directory suffix=".php"></directory>
        <file></file>
      </exclude>
    </blacklist>
    <whitelist processUncoveredFilesFromWhitelist="true">
      <directory suffix=".php">classes</directory>
      <file></file>
      <exclude>
        <directory suffix=".php"></directory>
        <file></file>
      </exclude>
    </whitelist>
  </filter>

  <logging>
    <log type="coverage-clover" target="logs/phpunit-coverage.xml"/>
    <log type="junit" target="logs/phpunit-log.xml" logIncompleteSkipped="false"/>
  </logging>

</phpunit>
```



- Un fichier de bootstrap peut être exécuté au démarrage de PHPUnit
- Intérêts :
 - Autochargement de classe (sauf si phpunit a été installé avec Composer et que l'autoloader est celui de composer)
 - Modification du `include_path`
 - Chargement de fichiers de configuration



► PHPStorm

The screenshot shows the PHPStorm IDE interface with the following components:

- Project View (Left):** Displays the project structure including folders like `Mapper`, `Writer`, `logs`, `tests`, and `vendor`. The `Database.php` file is selected.
- Code Editor (Center):** Shows the PHP code for `Database.php` with the following content:

```
<?php
namespace FormationTech\Entity;

class Database
{
    protected $name;

    public function __construct($name)
    {
        $this->name = $name;
    }

    public function getName()
    {
        return $this->name;
    }
}
```
- Coverage PHPUnit (Right):** Displays coverage statistics for the 'Entity' namespace. The table shows:

Element	Statistics, %
CompteBancaire.php	
Database.php	60% lines
- Run PHPUnit (Bottom):** Shows the execution of tests. The output indicates that all 9 tests passed in 400ms. The test results list includes:
 - `testFindAllWithDummyProphecy` (80ms)
 - `testFindAllWithFake` (20ms)
 - `testFindAllWithMock` (20ms)
 - `testFindAllWithMockProphecy` (60ms)
 - `testFindAllWithMySQL` (40ms)
 - `testFindAllWithSpyProphecy` (50ms)
 - `testFindAllWithStubFromClass` (30ms)
 - `testFindAllWithStubFromInterface` (50ms)
 - `testFindAllWithStubProphecy` (50ms)

PHPUnit - Intégration continue



► JUnit Plugin

Jenkins

BuildApp #26 FormationTechTest\Mapper\DatabaseMapperTest [Jenkins]

Test Result :
FormationTechTest\Mapper\DatabaseMapperTest

0 failures

9 tests
Took 0.36 sec.
[add description](#)


All Tests

Test name	Duration	Status
testFindAllWithDummyProphecy	0.1 sec	Passed
testFindAllWithFake	12 ms	Passed
testFindAllWithMock	15 ms	Passed
testFindAllWithMockProphecy	52 ms	Passed
testFindAllWithMySQL	33 ms	Passed
testFindAllWithSpyProphecy	34 ms	Passed
testFindAllWithStubFromClass	17 ms	Passed
testFindAllWithStubFromInterface	53 ms	Passed
testFindAllWithStubProphecy	43 ms	Passed

PHPUnit - Intégration continue



► Clover PHP plugin





Assertions



- ▶ Dans un framework xUnit, les assertions sont les méthodes qui vérifient qu'un résultat espéré corresponde au résultat attendu
- ▶ Le test échoue et s'arrête à la première assertion qui n'est pas vérifiée
- ▶ Bonnes pratiques :
 - Plusieurs assertions par test
 - Utiliser la méthode d'assertion la plus précise possible pour avoir un message d'erreur clair :
Ex : `assertEmpty($tableau)`
plutôt que `assertEquals(0, count($tableau))`
 - Si possible ajouter un message personnalisé

Assertions - Basiques



- `assertContains`
- `assertEquals`
- `assertFalse`
- `assertGreaterThan`
- `assertGreaterThanOrEqual`
- `assertInfinite`
- `assertInternalType`
- `assertLessThan`
- `assertLessThanOrEqual`
- `assertNan`
- `assertRegExp`
- `assertSame`
- `assertStringEndsWith`
- `assertStringMatchesFormat`
- `assertStringStartsWith`
- `assertThat`
- `assertTrue`



- ▶ `assertArrayHasKey`
- ▶ `assertArraySubset`
- ▶ `assertCount`
- ▶ `assertContains`
- ▶ `assertContainsOnly`
- ▶ `assertContainsOnlyInstancesOf`
- ▶ `assertEmpty`



▸ Fichiers

- `assertFileEquals`
- `assertFileExists`
- `assertStringEqualsFile`
- `assertStringMatchesFormatFile`

▸ JSON

- `assertJsonFileEqualsJsonFile`
- `assertJsonStringEqualsJsonFile`
- `assertJsonStringEqualsJsonString`

▸ XML

- `assertEqualXMLStructure`
- `assertXmlFileEqualsXmlFile`
- `assertXmlStringEqualsXmlFile`
- `assertXmlStringEqualsXmlString`

Assertions - Classes et Objets



- `assertClassHasAttribute`
- `assertClassHasStaticAttribute`
- `assertInstanceOf`
- `assertObjectHasAttribute`
- `assertNull`



Types de tests

Types de tests - Test Unitaire



```
<?php

namespace FormationTech\Entity;

class CompteBancaire
{
    protected $solde;

    public function __construct($solde = 0)
    {
        $this->solde = (double) $solde;
    }
    public function getSolde()
    {
        return $this->solde;
    }

    public function debiter($montant)
    {
        $this->solde -= (double) $montant;
    }

    public function crediter($montant)
    {
        $this->solde += (double) $montant;
    }
}
```


```
<?php

namespace FormationTechTest\Entity;

use FormationTech\Entity\CompteBancaire;

class CompteBancaireTest extends
    \PHPUnit_Framework_TestCase
{
    public function testCrediter()
    {
        $compte = new CompteBancaire(0);
        $compte->crediter(1000);
        $this->assertEquals(1000, $compte->getSolde());

        $compte->crediter(500);
        $this->assertEquals(1500, $compte->getSolde());
    }
}
```



```
MBP-de-Romain:PrepaFormationPHPUnit romain$ ./vendor/bin/phpunit tests/Entity/CompteBancaireTest.php --colors
PHPUnit 5.1.3 by Sebastian Bergmann and contributors.
```

.

1 / 1 (100%)

Time: 39 ms, Memory: 1.50Mb

OK (1 test, 2 assertions)

Types de tests - Test d'intégration



```
<?php

namespace FormationTech\Logger;

use FormationTech\Writer\WriterInterface;
use Psr\Log\LoggerInterface;
use Psr\Log\LoggerTrait;

class Logger implements LoggerInterface
{
    use LoggerTrait;

    protected $writer;

    public function __construct(WriterInterface $writer)
    {
        $this->writer = $writer;
    }

    public function log($level, $message, array $context = array())
    {
        $datetime = date('Y-m-d H:i:s');
        $logMessage = "[$level] - $datetime - $message";

        $this->writer->write($logMessage);
    }
}
```

```
<?php

namespace FormationTech\Writer;

class FileWriter implements WriterInterface
{
    protected $fic;

    public function __construct($filePath)
    {
        $this->fic = fopen($filePath, 'a');
    }

    public function write($message)
    {
        fwrite($this->fic, "$message\n");
    }

    public function __destruct()
    {
        fclose($this->fic);
    }
}
```

- Exemple de communication entre 2 classes :
 - Logger dépend de Writer (WriterInterface) et est compatible PSR-4
 - FileWriter implémente WriterInterface et sa méthode write

Types de tests - Test d'intégration



```
<?php

namespace FormationTechTest\Logger;

use FormationTech\Logger\Logger;
use FormationTech\Writer\FileWriter;
use Psr\Log\LogLevel;

class LoggerTest extends \PHPUnit_Framework_TestCase
{
    public function testLogWithFileWriter()
    {
        $testFile = __DIR__ . '/../../tests.log';
        $fw = new FileWriter($testFile);
        $logger = new Logger($fw);

        $logger->log(LogLevel::NOTICE, 'Un message');
        $content = file_get_contents($testFile);

        $this->assertRegExp('/\[notice\] - \d{4}-\d{2}-\d{2} \d{2}:\d{2}:\d{2} - Un message\n/',
        $content);
    }
}
```

```
MBP-de-Romain:PrepaFormationPHPUnit romain$ ./vendor/bin/phpunit tests/Logger/LoggerTest.php --colors
PHPUnit 5.1.3 by Sebastian Bergmann and contributors.
```

```
.
```

```
1 / 1 (100%)
```

```
Time: 38 ms, Memory: 1.50Mb
```

```
OK (1 test, 1 assertion)
```


Types de tests - Test fonctionnel



```
<?php
require_once __DIR__ . '/vendor/autoload.php';

$pdo = new \PDO('mysql:host=localhost', 'root', '');
$gateway = new \FormationTech\Gateway\DatabaseGateway($pdo);
$dbList = $gateway->listDbs();
?>
<!DOCTYPE html>
<html>
    <head>
        <meta charset="UTF-8">
        <title>Database list</title>
    </head>
    <body>
        <h2>Database list</h2>
        <ul>
            <?php foreach ($dbList as $db) : ?>
            <li><?=htmlspecialchars($db)?></li>
            <?php endforeach; ?>
        </ul>
    </body>
</html>
```

- Démarrage du PHP Built-in Server
php -S localhost:8080

Types de tests - Test fonctionnel



```
<?php

namespace FormationTechTest\Fonctionnal;

use Goutte\Client;

class DatabaseListTest extends \PHPUnit_Framework_TestCase
{
    public function testListDbs()
    {
        $client = new Client();
        $crawler = $client->request('GET', 'http://localhost:8080/database-list.php');

        $this->assertEquals(200, $client->getResponse()->getStatusCode());
        $this->assertEquals('Database list', $crawler->filter('h2')->text());
        $this->assertCount(13, $crawler->filter('ul > li'));
    }
}
```

```
MBP-de-Romain:PrepaFormationPHPUnit romain$ ./vendor/bin/phpunit tests/Logger/LoggerTest.php --colors
PHPUnit 5.1.3 by Sebastian Bergmann and contributors.
```

```
.                                                    1 / 1 (100%)
```

```
Time: 38 ms, Memory: 1.50Mb
```

```
OK (1 test, 1 assertion)
```



Doubles



- ▶ Le code PHP fait souvent appel à des composants externes :
 - Accès aux entrées/sorties
 - Accès à une base de données
 - Accès à un Service Web
- ▶ Certaines classes ne peuvent être testées de manières unitaires car elles dépendent d'autres classes.
- ▶ Solutions : les Doubles

Objets ou fonctions qui ressemblent et se comportent comme le composant qu'ils imitent, mais qui sont en réalité des versions simplifiées qui permettent de faciliter l'écriture du test.




- ▶ 5 types de Doubles :
 - Fake (une classe créée par l'utilisateur qui fera les opérations en mémoire)
 - Dummy (une classe générée dont les méthodes ne font rien)
 - Stub (une classe générée dont les méthodes ont le même comportement)
 - Mock (Stub + vérification que les méthodes soient bien appelée)
 - Spy (Dummy + vérification que les méthodes soient bien appelée à posteriori)
- ▶ Bonnes pratiques :
 - Injection de Dépendance (pas de composition)
 - Registre ou Container d'injection de Dépendance

Double - Classes d'exemple



- Un DataMapper

<http://martinfowler.com/eaCatalog/dataMapper.html>



Double - Classes d'exemple



► Entité

```
<?php
namespace FormationTech\Entity;

class Database
{
    protected $name;

    public function __construct($name)
    {
        $this->name = $name;
    }

    public function getName()
    {
        return $this->name;
    }
}
```

Double - Classes d'exemple



► Gateway

```
<?php

namespace FormationTech\Gateway;

class DatabaseGateway implements DatabaseGatewayInterface
{
    protected $pdo;

    public function __construct($pdo)
    {
        $this->pdo = $pdo;
    }

    public function listDbs()
    {
        $stmt = $this->pdo->query('SHOW DATABASES');

        return $stmt->fetchAll(\PDO::FETCH_COLUMN);
    }
}
```

```
<?php

namespace FormationTech\Gateway;

interface DatabaseGatewayInterface
{
    public function listDbs();
}
```


Double - Classes d'exemple



- ▶ Mapper (classe à tester unitairement)

```
<?php

namespace FormationTech\Mapper;

use FormationTech\Entity\Database;
use FormationTech\Gateway\DatabaseGatewayInterface;

class DatabaseMapper
{
    protected $gateway;

    public function __construct(DatabaseGatewayInterface $gateway)
    {
        $this->gateway = $gateway;
    }

    public function findAll()
    {
        $dbsArray = $this->gateway->listDbs();
        $dbsObj = [];

        if (!$dbsArray) {
            return $dbsObj;
        }

        foreach ($dbsArray as $dbName) {
            $dbsObj[] = new Database($dbName);
        }

        return $dbsObj;
    }
}
```



► Test sans double

```
<?php

namespace FormationTechTest\Mapper;

use FormationTech\Entity\Database;
use FormationTech\Gateway\DatabaseGateway;
use FormationTech\Mapper\DatabaseMapper;

class DatabaseMapperTest extends \PHPUnit_Framework_TestCase
{
    public function testFindAllWithMySQL()
    {
        $pdo = new \PDO('mysql:host=localhost', 'root', '');
        $gateway = new DatabaseGateway($pdo);
        $mapper = new DatabaseMapper($gateway);

        $dbs = $mapper->findAll();

        $this->assertCount(13, $dbs);
        $this->assertContainsOnlyInstancesOf(Database::class, $dbs);
    }
}
```

- Problème : changement dans la base de données ?
- Solution : fixture dans un setUp ? double ?

Double - Fake



► Fake

```
<?php
namespace FormationTech\Gateway;

class DatabaseGatewayFake implements DatabaseGatewayInterface
{
    protected $dbs;

    public function __construct(Array $dbs)
    {
        $this->dbs = $dbs;
    }

    public function listDbs()
    {
        return $this->dbs;
    }
}
```

```
<?php
namespace FormationTechTest\Mapper;

use FormationTech\Entity\Database;
use FormationTech\Gateway\DatabaseGatewayFake;
use FormationTech\Mapper\DatabaseMapper;

class DatabaseMapperTest extends \PHPUnit_Framework_TestCase
{
    public function testFindAllWithFake()
    {
        $gateway = new DatabaseGatewayFake(['db1', 'db2', 'db3']);
        $mapper = new DatabaseMapper($gateway);

        $dbs = $mapper->findAll();

        $this->assertCount(3, $dbs);
        $this->assertContainsOnlyInstancesOf(Database::class, $dbs);
    }
}
```



- ▶ Sebastian Bergman à propos de l'API de Mock de PHPUnit :
<https://thephp.cc/news/2015/02/phpunit-4-5-and-prophecy>
- ▶ L'ancien API continue d'exister pour rester compatible avec les anciens tests
- ▶ PHPUnit depuis la version 4.5 intègre un framework de test moderne : Prophecy
- ▶ Documentation
<https://github.com/phpspec/prophecy>

Double - Prophecy Dummy



```
<?php

namespace FormationTechTest\Mapper;

use FormationTech\Entity\Database;
use FormationTech\Gateway\DatabaseGateway;
use FormationTech\Mapper\DatabaseMapper;

class DatabaseMapperTest extends \PHPUnit_Framework_TestCase
{
    // ...

    public function testFindAllWithDummyProphecy()
    {
        $dummy = $this->prophesize(DatabaseGateway::class);

        $mapper = new DatabaseMapper($dummy->reveal());

        $dbs = $mapper->findAll();

        $this->assertEmpty($dbs);
    }

    // ...
}
```

Double - Prophecy Stub



```
<?php

namespace FormationTechTest\Mapper;

use FormationTech\Entity\Database;
use FormationTech\Gateway\DatabaseGateway;
use FormationTech\Mapper\DatabaseMapper;

class DatabaseMapperTest extends \PHPUnit_Framework_TestCase
{
    // ...

    public function testFindAllWithStubProphecy()
    {
        $stub = $this->prophesize(DatabaseGateway::class);

        $stub->listDbs()->willReturn(['db1', 'db2', 'db3', 'db4']);

        $mapper = new DatabaseMapper($stub->reveal());

        $dbs = $mapper->findAll();

        $this->assertCount(4, $dbs);
        $this->assertContainsOnlyInstancesOf(Database::class, $dbs);
    }

    // ...
}
```

Double - Prophecy Mock



```
<?php

namespace FormationTechTest\Mapper;

use FormationTech\Entity\Database;
use FormationTech\Gateway\DatabaseGateway;
use FormationTech\Mapper\DatabaseMapper;

class DatabaseMapperTest extends \PHPUnit_Framework_TestCase
{
    // ...

    public function testFindAllWithMockProphecy()
    {
        $mock = $this->prophesize(DatabaseGateway::class);

        $mock->listDbs()->willReturn(['db1', 'db2']->shouldBeCalledTimes(1);

        $mapper = new DatabaseMapper($mock->reveal());

        $dbs = $mapper->findAll();

        $this->assertCount(2, $dbs);
        $this->assertContainsOnlyInstancesOf(Database::class, $dbs);
    }

    // ...
}
```

Double - Prophecy Spy



```
<?php

namespace FormationTechTest\Mapper;

use FormationTech\Entity\Database;
use FormationTech\Gateway\DatabaseGateway;
use FormationTech\Mapper\DatabaseMapper;

class DatabaseMapperTest extends \PHPUnit_Framework_TestCase
{
    // ...

    public function testFindAllWithSpyProphecy()
    {
        $mock = $this->prophesize(DatabaseGateway::class);

        $mapper = new DatabaseMapper($mock->reveal());

        $dbs = $mapper->findAll();

        $this->assertEmpty($dbs);

        $mock->listDbs()->shouldHaveBeenCalledTimes(1);
    }

    // ...
}
```




- ▶ Mockery

<https://github.com/padraic/mockery>

<http://docs.mockery.io/en/latest/>

- ▶ Phake

<https://github.com/mlively/Phake>

<http://phake.readthedocs.org/en/2.1/>



Zend Framework 2



- ▶ **Zend\Test**
 - Apparu dans Zend Framework 2.1
 - Simplifie l'écriture des tests des contrôleurs
 - Ajoute des assertions
- ▶ **2 classes pour tester les contrôleurs Web ou Console**
 - `Zend\Test\PHPUnit\Controller\AbstractHttpControllerTestCase`
 - `Zend\Test\PHPUnit\Controller\AbstractConsoleControllerTestCase`



▸ Requêtes

- `assertModulesLoaded(array $modules)`
- `assertModuleName($module)`
- `assertControllerName($controller)`
- `assertControllerClass($controller)`
- `assertActionName($action)`
- `assertMatchedRouteName($route)`



▶ CSS Selector

- `assertQuery($path)`
- `assertQueryContentContains($path, $match)`
- `assertQueryContentRegex($path, $pattern)`
- `assertQueryCount($path, $count)`
- `assertQueryCountMin($path, $count)`
- `assertQueryCountMax($path, $count)`



▸ XPath

- `assertXPathQuery($path)`
- `assertNotXPathQuery($path)`
- `assertXPathQueryCount($path, $count)`
- `assertNotXPathQueryCount($path, $count)`
- `assertXPathQueryCountMin($path, $count)`
- `assertXPathQueryCountMax($path, $count)`
- `assertXPathQueryContentContains($path, $match)`
- `assertNotXPathQueryContentContains($path, $match)`
- `assertXPathQueryContentRegex($path, $pattern)`
- `assertNotXPathQueryContentRegex($path, $pattern)`



▸ Redirect

- `assertRedirect()`
- `assertRedirectTo($url)`
- `assertRedirectRegex($pattern)`

▸ Response Header

- `assertResponseStatusCode($code)`
- `assertResponseHeader($header)`
- `assertResponseHeaderContains($header, $match)`
- `assertResponseHeaderRegex($header, $pattern)`

Zend Framework 2 - Test Fonctionnel



```
class AlbumControllerTest extends AbstractHttpControllerTestCase
{
    public function testListActionContainsName()
    {
        $repositoryMock = $this->getMockBuilder('AddressBook\Entity\Repository>ContactRepository')
            ->disableOriginalConstructor()
            ->getMock();

        $entityMock = $this->getMockBuilder('AddressBook\Entity>Contact')
            ->getMock();

        $entityMock->expects($this->any())
            ->method('getId')
            ->will($this->returnValue(1));

        $entityMock->expects($this->any())
            ->method('getPrenom')
            ->will($this->returnValue("Romain"));

        $entityMock->expects($this->any())
            ->method('getNom')
            ->will($this->returnValue("Bohdanowicz"));

        $repositoryMock->expects($this->once())
            ->method('findBy')
            ->will($this->returnValue(array($entityMock)));

        $serviceManager = $this->getApplicationServiceLocator();
        $serviceManager->setAllowOverride(true);
        $serviceManager->setService('AddressBook\Entity\Repository>ContactRepository', $repositoryMock);

        $this->dispatch('/');
        $this->assertQueryContentContains('tr td', 'Romain Bohdanowicz');
    }
}
```