

## *CSCE 580: Introduction to AI* *CSCE 581: Trusted AI*

# Lecture 18: Explanation, Machine Learning – Unsupervised

---

PROF. BIPLAV SRIVASTAVA, AI INSTITUTE

26<sup>TH</sup> OCT 2023

**Carolinian Creed: “I will practice personal and  
academic integrity.”**

**Credits: Copyrights of all material reused acknowledged**

# Organization of Lecture 18

---

- Introduction Segment
  - Recap of Lecture 17
  - Mid-course poll
- Main Segment
  - Trust/ Explanations, LIME - Recap
  - Unsupervised ML
  - Algorithms
- Concluding Segment
  - Course Project Discussion
  - Quiz 3
  - About Next Lecture – Lecture 19
  - Ask me anything

# Introduction Section

---

# Recap of Lecture 17


---

- Topic discussed
  - Building Chatbots
  - Rasa
  - SafeChat Framework

# Mid-Course Poll

How satisfied are you with the course?

4 responses



- Very satisfied
- Satisfied
- Neutral - Neither satisfied or dissatisfied
- Dissatisfied
- Very dissatisfied

- Do you like the pace of the course ? [Yes; 4/4]
- Do you like the content on which the course is focusing? [Yes; 4/4]
- Should the number of Quizzes or weightage be reduced? [No; 4/4]

What more topic(s) will you like to be covered or to be dropped? 4 responses

- More on the login and PL
- I think the content being covered is good. Maybe a bit more on deep learning/neural networks(which we are now getting to)
- Application / how to know what AI method to use best.
- face recognition

What would you like, if anything, to be changed in the course?

4 responses

- More details on the expectations for the presentations
- Maybe an example of image processing
- I am a little bit frustrated that the final project was limited to a chatbot. I wish that we could have expanded our horizons to something else.
- no

Any other comments?


- A more detailed rubric for presentation and project requirements

# Actions Based on Poll


---

- DL/ NN => 2 classes (DL, LLM); CSCE 580 for more details
- Project rubric => Will be shared; (consideration: voting by students?)
- Application: What AI method to best use? => No general answer but patterns emerging, needs careful experimentation. Will emphasize as we discuss topics
- Image processing => noted.
- Focus on chatbots => T-shaped focus of skill – deep in chatbots, student-driven projects, a range of topics in class (data, reasoning, representation, search, learning, trust, planning/MDP).

# Intelligent Agent Model



# Relationship Between Main AI Topics





# Where We Are in the Course

## CSCE 580/ 581 – In This Course

- Week 1: Introduction, Aim: Chatbot / Intelligence Agent
- Weeks 2-3: Data: Formats, Representation and the Trust Problem
- Week 4-5: Search, Heuristics - Decision Making
- Week 6: Constraints, Optimization – Decision Making
- Week 7: Classical Machine Learning – Decision Making, Explanation
- Week 8: Machine Learning - Classification
- Week 9: Machine Learning - Classification – Trust Issues and

### Mitigation Methods

- Topic 10: Learning neural network, deep learning, Adversarial attacks
- Week 11: Large Language Models – Representation, Issues
- Topic 12: Markov Decision Processes, Hidden Markov models -  
Decision making
- Topic 13: Planning, Reinforcement Learning – Sequential decision  
making
- Week 14: AI for Real World: Tools, Emerging Standards and Laws;  
Safe AI/ Chatbots

# Main Section

---

**Credit:** Retrieved from internet

# Recap: AI Trust/ Explanations

---


# Types of Explanations

---

- **Feature-based**: from the features of the data, which feature(s) were most important for given decision output
  - Example: For a loan, is it income or the person's age ?
- **Sample-based**: from data in training, which data points were important for given test point; helps understand sampling and its representation in wider population
  - Example: For a loan, what instances similar to the loan application would have gotten the loan ?
- **Counter-factual**: what-ifs – what do you change about the input to change the decision output
  - Example: For a loan, does getting an additional borrower insurance increase chance of getting the loan?
- Natural language

**Source:** Explainable Machine Learning in Deployment, FAT\* 2020

# EXPLAINABILITY TAXONOMY & GUIDANCE



## Explanation Taxonomy

Figure Credit: Diptikalyan Saha and Vijay Arya, Oct 2021

# A Step Towards Fairness

## Broad classes

- **Individual fairness:** similar individuals to be treated similarly
- **Group fairness:** statistical property of decision as a group should be representative of the population
- **Both individual and group fairness, and use a single metric:** generalized entropy index

**Guidance:** *Selection of metric is application driven*

Name	Closest relative	Note	Reference
Statistical parity	Independence	Equivalent	Dwork et al. (2011)
Group fairness	Independence	Equivalent	
Demographic parity	Independence	Equivalent	
Conditional statistical parity	Independence	Relaxation	Corbett-Davies et al. (2017)
Darlington criterion (4)	Independence	Equivalent	Darlington (1971)
Equal opportunity	Separation	Relaxation	Hardt, Price, Srebro (2016)
Equalized odds	Separation	Equivalent	Hardt, Price, Srebro (2016)
Conditional procedure accuracy	Separation	Equivalent	Berk et al. (2017)
Avoiding disparate mistreatment	Separation	Equivalent	Zafar et al. (2017)
Balance for the negative class	Separation	Relaxation	Kleinberg, Mullainathan, Raghavan (2016)
Balance for the positive class	Separation	Relaxation	Kleinberg, Mullainathan, Raghavan (2016)
Predictive equality	Separation	Relaxation	Chouldechova (2016)
Equalized correlations	Separation	Relaxation	Woodworth (2017)
Darlington criterion (3)	Separation	Relaxation	Darlington (1971)
Cleary model	Sufficiency	Equivalent	Cleary (1966)
Conditional use accuracy	Sufficiency	Equivalent	Berk et al. (2017)
Predictive parity	Sufficiency	Relaxation	Chouldechova (2016)
Calibration within groups	Sufficiency	Equivalent	Chouldechova (2016)
Darlington criterion (1), (2)	Sufficiency	Relaxation	Darlington (1971)

# Machine Learning – Insights from Data

---

- Descriptive analysis
  - Describe a past phenomenon
  - **Methods:** classification (feedback from label), clustering, dimensionality reduction, anomaly detection, neural methods, reinforcement learning (feedback from hint/ reward)
- Predictive analysis
  - Predict about a new situation
  - **Methods:** time-series, neural networks
- Prescriptive analysis
  - What an agent should do
  - **Methods:** simulation, reinforcement learning, reasoning
- New areas
  - Counterfactual analysis
  - Causal Inferencing
  - Scenario planning

# Unsupervised Machine Learning

---

- Group data into clusters/ classes without supervision
  - Limited supervision
- What is a good cluster ?
  - Samples within a cluster should be “**near**” to each other (**cohesiveness**)
  - Samples in a cluster should be “**far**” from other samples in other clusters. (**distinctiveness**)



# Data Representation

---

- Data matrix representation
  - N objects (data rows) x p attributes (columns)
  - Similar to classification
- Dissimilarity matrix
  - Object x Object structure
  - $D(i, j)$  is difference or dissimilarity between  $(i, j)$ , 0 means similar and 1 means dissimilar

# Clustering for Data Understanding and Applications

- Biology: taxonomy of living things: kingdom, phylum, class, order, family, genus and species
- Information retrieval: document clustering
- Land use: Identification of areas of similar land use in an earth observation database
- Marketing: Help marketers discover distinct groups in their customer bases, and then use this knowledge to develop targeted marketing programs
- City-planning: Identifying groups of houses according to their house type, value, and geographical location
- Earth-quake studies: Observed earth quake epicenters should be clustered along continent faults
- Climate: understanding earth climate, find patterns of atmospheric and ocean
- Economic Science: market resarch

**Content:** Jiawei Han, Micheline Kamber and Jian Pei  
Data Mining: Concepts and Techniques, 3<sup>rd</sup> ed.

## Clustering as a Preprocessing Tool (Utility)

- Summarization:
  - Preprocessing for regression, PCA, classification, and association analysis
- Compression:
  - Image processing: vector quantization
- Finding K-nearest Neighbors
  - Localizing search to one or a small number of clusters
- Outlier detection
  - Outliers are often viewed as those “far away” from any cluster

**Content:** Jiawei Han, Micheline Kamber and Jian Pei  
Data Mining: Concepts and Techniques, 3<sup>rd</sup> ed.

# Considerations for a Clustering Algorithm

---

- Need a distance measure for *far* and *near*
- Be able to explain what a cluster means
- Handle different types of attributes: numeric, categorical (nominal, ordinal), binary
- Detect different shapes of clusters
- Handle noisy data
- Scale
  - Size
  - Dimensions

# Major Clustering Approaches (I)

---

## Partitioning approach:

- Construct various partitions and then evaluate them by some criterion, e.g., minimizing the sum of square errors
- Typical methods: **k-means**, k-medoids, CLARANS

## Hierarchical approach:

- Create a hierarchical decomposition of the set of data (or objects) using some criterion
- Typical methods: Diana, Agnes, **BIRCH**, CAMELEON

## Density-based approach:

- Based on connectivity and density functions
- Typical methods: **DBSCAN**, OPTICS, DenClue

## Grid-based approach:

- based on a multiple-level granularity structure
- Typical methods: STING, WaveCluster, CLIQUE

**Content:** Jiawei Han, Micheline Kamber and Jian Pei  
Data Mining: Concepts and Techniques, 3<sup>rd</sup> ed.

# Major Clustering Approaches (II)

---

## Model-based:

- A model is hypothesized for each of the clusters and tries to find the best fit of that model to each other
- Typical methods: **EM**, SOM, COBWEB

## Frequent pattern-based:

- Based on the analysis of frequent patterns
- Typical methods: p-Cluster

## User-guided or constraint-based:

- Clustering by considering user-specified or application-specific constraints
- Typical methods: COD (obstacles), constrained clustering

## Link-based clustering:

- Objects are often linked together in various ways
- Massive links can be used to cluster objects: **SimRank**, LinkClus

**Content:** Jiawei Han, Micheline Kamber and Jian Pei  
Data Mining: Concepts and Techniques, 3<sup>rd</sup> ed.

## Partitioning Algorithms: Basic Concept


Partitioning method: Partitioning a database ***D*** of ***n*** objects into a set of ***k*** clusters, such that the sum of squared distances is minimized (where  $c_i$  is the centroid or medoid of cluster  $C_i$ )

$$E = \sum_{i=1}^k \sum_{p \in C_i} (p - c_i)^2$$

Given  $k$ , find a partition of  $k$  clusters that optimizes the chosen partitioning criterion

- Global optimal: exhaustively enumerate all partitions
- Heuristic methods: *k-means* and *k-medoids* algorithms
- *k-means* (MacQueen'67, Lloyd'57/'82): Each cluster is represented by the center of the cluster
- *k-medoids* or PAM (Partition around medoids) (Kaufman & Rousseeuw'87): Each cluster is represented by one of the objects in the cluster

# An Example of *K-Means* Clustering





## Comments on the *K-Means* Method


- **Strength:** *Efficient:*  $O(tkn)$ , where  $n$  is # objects,  $k$  is # clusters, and  $t$  is # iterations. Normally,  $k, t \ll n$ .
  - Comparing: PAM:  $O(k(n-k)^2)$ , CLARA:  $O(ks^2 + k(n-k))$
- **Comment:** Often terminates at a *local optimal*.
- **Weakness**
  - Applicable only to objects in a continuous  $n$ -dimensional space
  - Using the k-modes method for categorical data
  - In comparison, k-medoids can be applied to a wide range of data
  - Need to specify  $k$ , the *number* of clusters, in advance (there are ways to automatically determine the best  $k$  (see Hastie et al., 2009)
  - Sensitive to noisy data and *outliers*
  - Not suitable to discover clusters with *non-convex shapes*

# Exercise: Weka

---

- Use K-means on weather.arff
- Vary k

# Snapshot of Clustering Methods



A comparison of the clustering algorithms in scikit-learn

**Credit:**

<https://scikit-learn.org/stable/modules/clustering.html>

# Snapshot of Clustering Methods

## Credit:

<https://scikit-learn.org/stable/modules/clustering.html>

Method name	Parameters	Scalability	Usecase	Geometry (metric used)
K-Means	number of clusters	Very large <code>n_samples</code> , medium <code>n_clusters</code> with <a href="#">MiniBatch code</a>	General-purpose, even cluster size, flat geometry, not too many clusters, inductive	Distances between points
Affinity propagation	damping, sample preference	Not scalable with <code>n_samples</code>	Many clusters, uneven cluster size, non-flat geometry, inductive	Graph distance (e.g. nearest-neighbor graph)
Mean-shift	bandwidth	Not scalable with <code>n_samples</code>	Many clusters, uneven cluster size, non-flat geometry, inductive	Distances between points
Spectral clustering	number of clusters	Medium <code>n_samples</code> , small <code>n_clusters</code>	Few clusters, even cluster size, non-flat geometry, transductive	Graph distance (e.g. nearest-neighbor graph)
Ward hierarchical clustering	number of clusters or distance threshold	Large <code>n_samples</code> and <code>n_clusters</code>	Many clusters, possibly connectivity constraints, transductive	Distances between points
Agglomerative clustering	number of clusters or distance threshold, linkage type, distance	Large <code>n_samples</code> and <code>n_clusters</code>	Many clusters, possibly connectivity constraints, non Euclidean distances, transductive	Any pairwise distance
DBSCAN	neighborhood size	Very large <code>n_samples</code> , medium <code>n_clusters</code>	Non-flat geometry, uneven cluster sizes, outlier removal, transductive	Distances between nearest points
HDBSCAN	minimum cluster membership, minimum point neighbors	large <code>n_samples</code> , medium <code>n_clusters</code>	Non-flat geometry, uneven cluster sizes, outlier removal, transductive, hierarchical, variable cluster density	Distances between nearest points
OPTICS	minimum cluster membership	Very large <code>n_samples</code> , large <code>n_clusters</code>	Non-flat geometry, uneven cluster sizes, variable cluster density, outlier removal, transductive	Distances between points
Gaussian mixtures	many	Not scalable	Flat geometry, good for density estimation, inductive	Mahalanobis distances to centers
BIRCH	branching factor, threshold, optional global clusterer.	Large <code>n_clusters</code> and <code>n_samples</code>	Large dataset, outlier removal, data reduction, inductive	Euclidean distance between points
Bisecting K-Means	number of clusters	Very large <code>n_samples</code> , medium <code>n_clusters</code>	General-purpose, even cluster size, flat geometry, no empty clusters, inductive, hierarchical	Distances between points

# Course Project

---

# Project Discussion: What Problem Fascinates You ?

---

- Data
  - Water
  - Finance
  - ...
- Analytics
  - Search, Optimization, Learning, Planning, ...
- Application
  - Building chatbot
- Users
  - Diverse demographics
  - Diverse abilities
  - Multiple human languages

## Project execution in sprints

- Sprint 1: (Sep 12 – Oct 5)
  - **Solving**: Choose a decision problem, identify data, work on solution methods
  - **Human interaction**: Develop a basic chatbot (no AI), no problem focus
- Sprint 2: (Oct 10 – Nov 9)
  - **Solving**: Evaluate your solution on problem
  - **Human interaction**: Integrated your choice of chatbot (rule-based or learning-based) and methods
- Sprint 3: (Nov 14 – 30)
  - **Evaluation**: Comparison of your solver chatbot with an LLM-based alternative, like ChatGPT

# Project Discussion: Dates and Deliverables

---

## Project execution in sprints

- Sprint 1: (Sep 12 – Oct 5)
  - **Solving**: Choose a decision problem, identify data, work on solution methods
  - **Human interaction**: Develop a basic chatbot (no AI), no problem focus
- Sprint 2: (Oct 10 – Nov 9)
  - **Solving**: Evaluate your solution on problem
  - **Human interaction**: Integrated your choice of chatbot (rule-based or learning-based) and methods
- Sprint 3: (Nov 14 – 30)
  - **Evaluation**: Comparison of your solver chatbot with an LLM-based alternative, like ChatGPT

- Oct 12, 2023
  - Project checkpoint
  - In-class presentation
- Nov 30, 2023
  - Project report due
- Dec 5 / 7, 2023
  - In-class presentation

# Skeleton: A Basic Chatbot

- Run in an infinite loop until the user wants to quit
- Handle any user response
  - User can quit by typing “Quit” or “quit” or just “q”
  - User can enter any other text and the program has to handle it. The program should write back what the user entered and say – “I do not know this information”.
- Handle known user query types // Depends on your project
  - “Tell me about N-queens”, “What is N ?”
  - “Solve for N=4?”
  - “Why is this a solution? ”
- Handle chitchat // Support at least 5, extensible from a file
  - “Hi” => “Hello”
  - ...
- *Store session details in a file*

## Illustrative Project

1. **Title:** Solve and explain solving of n-queens puzzle
2. **Key idea:** Show students how a course project will look like
3. **Who will care when done:** students of the course, prospective AI students and teachers
4. **Data need:** n: the size of game; interaction
5. **Methods:** search
6. **Evaluation:** correctness of solution, quality of explanation, appropriateness of chat
7. **Users:** with and without AI background; with and without chess background
8. **Trust issue:** user may not believe in the solution, may find interaction offensive (why queens, not kings? ...)



# Project Discussion: Illustration

1. Create a private Github repository called “CSCE58x-Fall2023-<studentname>-Repo”. Share with Instructor (biplav-s) and TA (kausik-l)
2. Create Google folder called “CSCE58x-Fall2023-<studentname>-SharedInfo”. Share with Instructor ([prof.biplav@gmail.com](mailto:prof.biplav@gmail.com)) and TA ([lakkarajukaushik90@gmail.com](mailto:lakkarajukaushik90@gmail.com))
3. Create a Google doc in your Google repo called “Project Plan” and have the following by next class (Sep 5, 2023)

1. **Title:** Solve and explain solving of n-queens puzzle
2. **Key idea:** Show students how a course project will look like
3. **Who will care when done:** students of the course, prospective AI students and teachers
4. **Data need:** n: the size of game; interaction
5. **Methods:** search
6. **Evaluation:** correctness of solution, quality of explanation, appropriateness of chat
7. **Users:** with and without AI background; with and without chess background
8. **Trust issue:** user may not believe in the solution, may find interaction offensive (why queens, not kings? ...)

# Project Illustration: N-Queens

---

- Sprint 1: (Sep 12 – Oct 5)
  - **Solving**: Choose a decision problem, identify data, work on solution methods
    - Method 1: Random solution
    - Method 2: Search – BFS
    - Method 3: Search - ...
  - **Human interaction**: Develop a basic chatbot (no AI) as outlined
  - Deliverable
    - Code structure in Github
      - ./data
      - ./code
      - ./docs
      - ./test
    - Presentation: Make sprint presentation on Oct 12, 2023

# Reference: Project Rubric

- **Project results – 60%**
  - Working system ? – 30%
  - Evaluation with results superior to baseline? – 20%
  - Considered related work? – 10%
- **Project efforts – 40%**
  - Project report – 20%
  - Project presentation (updates, final) – 20%
- **Bonus**
  - Challenge level of problem – 10%
  - Instructor discretion – 10%
- **Penalty**
  - Lack of timeliness as per announced policy (right) - up to 30%

## Milestones and Penalties

- Oct 12, 2023
  - Project checkpoint
  - In-class presentation
  - **Penalty: presentation not ready by Oct 10, 2023 [-10%]**
- Nov 30, 2023
  - Project report due
  - **Project report not ready by date [-10%]**
- Dec 5 / 7, 2023
  - In-class presentation
  - **Project presentations not ready by Dec 4, 2023 [-10%]**

# Quiz 3

---

Discussion on Quiz 3; due on Tuesday (Nov 2, 2023)

# Lecture 18: Summary

---

- We talked about
  - Building Chatbots
  - Rasa
  - SafeChat Framework

# Concluding Section

---

# About Next Lecture – Lecture 19

---

# Lecture 19: Machine Learning - NN, Deep Learning

---

- Neural Networks
- Deep Learning
- Trust Issues