

CSCE 580: Introduction to AI
CSCE 581: Trusted AI

Lecture 9: Search Continued – Local Search

PROF. BIPLAV SRIVASTAVA, AI INSTITUTE

21ST SEP 2023

Carolinian Creed: “I will practice personal and academic integrity.”

Credits: Copyrights of all material reused acknowledged


Organization of Lecture 9

- Introduction Segment
 - Recap of Lecture 8
- Main Segment
 - Hill climbing
 - Simulated Annealing
 - Genetic programming
 - Search in complex environments
- Concluding Segment
 - Course Project Discussion
 - About Next Lecture – Lecture 9
 - Ask me anything

Introduction Section

Recap of Lecture 8


- Informed Search
- Heuristics and Properties
- Designing Heuristics



Intelligent Agent Model



Relationship Between Main AI Topics



Where We Are in the Course

CSCE 580/ 581 – In This Course


- Week 1: Introduction, Aim: Chatbot / Intelligence Agent
- Weeks 2-3: Data: Formats, Representation and the Trust Problem
- Week 4-5: Search, Heuristics - Decision Making
- Week 6: Constraints, Optimization – Decision Making
- Week 7: Classical Machine Learning – Decision Making, Explanation
- Week 8: Machine Learning - Classification
- Week 9: Machine Learning - Classification – Trust Issues and Mitigation Methods
- Topic 10: Learning neural network, deep learning, Adversarial attacks
- Week 11: Large Language Models – Representation, Issues
- Topic 12: Markov Decision Processes, Hidden Markov models - Decision making
- Topic 13: Planning, Reinforcement Learning – Sequential decision making
- Week 14: AI for Real World: Tools, Emerging Standards and Laws; Safe AI/ Chatbots

Main Section

Local Search

- Systematic search
 - Path matters [Store search trajectory]
- Non-systematic search
 - Solution matters, not path
- Settings
 - States: Discrete, continuous
 - Non-deterministic actions
 - Partial observability


State Space Landscape



- Setup: find maxima

Adapted from:
Russell & Norvig, AI: A Modern Approach

Hill Climbing /Greedy Local Search




```
function HILL-CLIMBING(problem) returns a state that is a local maximum
  current  $\leftarrow$  problem.INITIAL
  while true do
    neighbor  $\leftarrow$  a highest-valued successor state of current
    if VALUE(neighbor)  $\leq$  VALUE(current) then return current
    current  $\leftarrow$  neighbor
```


At each step, replace the current node with the best neighbor.

Adapted from:
Russell & Norvig, AI: A Modern Approach

Hill Climbing Illustration



(a)



(b)

Figure 4.3 (a) The 8-queens problem: place 8 queens on a chess board so that no queen attacks another. (A queen attacks any piece in the same row, column, or diagonal.) This position is almost a solution, except for the two queens in the fourth and seventh columns that attack each other along the diagonal. (b) An 8-queens state with heuristic cost estimate $h = 17$. The board shows the value of h for each possible successor obtained by moving a queen within its column. There are 8 moves that are tied for best, with $h = 12$. The hill-climbing algorithm will pick one of these.

State representation:

- Complete state formulation

Next Action:

- Any queen in the same column
($8 \times 7 = 56$ children)

State space: $8^8 = 17$ million (appx)

Steepest ascent:


- * Gets stuck 86% times in 3 steps
- * Solves 14% times in 4 steps

Adapted from:
Russell & Norvig, AI: A Modern Approach

Hill Climbing Variations

- **Stochastic hill climbing:** chooses an uphill node with prob. depending on steepness of increase
- **First-choice hill climbing:** choose first that is uphill
- **Random-restart hill climbing:** restart after a few tries
 - If p is chance of success. restarts needed = $1/p$
 - For 8-queens, $p=.14$
 - Restart needed = 7 (6 failure, 1 success)
 - Total steps for finding a solution = $4 + ((1-p) / p) * 3 = 22$ steps

Simulated Annealing



```
function SIMULATED-ANNEALING(problem, schedule) returns a solution state
  current  $\leftarrow$  problem.INITIAL
  for  $t = 1$  to  $\infty$  do
     $T \leftarrow$  schedule( $t$ )
    if  $T = 0$  then return current
    next  $\leftarrow$  a randomly selected successor of current
     $\Delta E \leftarrow$  VALUE(current) – VALUE(next)
    if  $\Delta E > 0$  then current  $\leftarrow$  next
    else current  $\leftarrow$  next only with probability  $e^{-\Delta E/T}$ 
```

- Setup: find minima
- T: temperature
- A bad successor is chosen will prob. that decreases with temperature
- Schedule: cooling schedule

Adapted from:
Russell & Norvig, AI: A Modern Approach


Related Algorithms

- **Local beam search:** keeps track of k states rather than 1
 - Generate k randomly generated states
 - Repeat
 - Generate all successors of k states generated
 - If one is a goal, done
 - Select k best successors
- **Stochastic beam search**
 - Chooses k successors with probability proportional to the successors value

Evolutionary Algorithms (EAs)

Basic idea

- A population of individuals (states)
- Fittest (highest value) produce offsprings (successor states) - recombination
 - Cross-over
 - mutation



Digit strings representing 8-queens states. The initial population in (a) is ranked by a fitness function in (b) resulting in pairs for mating in (c). They produce offspring in (d), which are subject to mutation in (e).

Fitness function: non-attacking pairs of queens

Adapted from:
Russell & Norvig, AI: A Modern Approach

Comparing EA with Local Search

- Idea of cross-over
 - Useful if traits of parents are useful in children
- Idea of mutation
 - Random changes can help escape local minima
- Selection of parameters (e.g., generations) affects performance
- # Parents
 - =1 : stochastic beam search
 - =2 : similar to nature
 - > 2 : not common in nature, but possible to simulate

Adapted from:
Russell & Norvig, AI: A Modern Approach

```
function GENETIC-ALGORITHM(population, fitness) returns an individual
  repeat
    weights  $\leftarrow$  WEIGHTED-BY(population, fitness)
    population2  $\leftarrow$  empty list
    for i = 1 to SIZE(population) do
      parent1, parent2  $\leftarrow$  WEIGHTED-RANDOM-CHOICES(population, weights, 2)
      child  $\leftarrow$  REPRODUCE(parent1, parent2)
      if (small random probability) then child  $\leftarrow$  MUTATE(child)
      add child to population2
    population  $\leftarrow$  population2
  until some individual is fit enough, or enough time has elapsed
  return the best individual in population, according to fitness

function REPRODUCE(parent1, parent2) returns an individual
  n  $\leftarrow$  LENGTH(parent1)
  c  $\leftarrow$  random number from 1 to n
  return APPEND(SUBSTRING(parent1, 1, c), SUBSTRING(parent2, c + 1, n))
```

Figure 4.7 A genetic algorithm. Within the function, *population* is an ordered list of individuals, *weights* is a list of corresponding fitness values for each individual, and *fitness* is a function to compute these values.

Local Search With Non-Deterministic Actions

- Systematic search
 - Path matters [Store search trajectory]
- Non-systematic search
 - Solution matters, not path
- Settings
 - States: Discrete, continuous
 - **Non-deterministic actions***
 - Partial observability*

Erratic Vacuum World

- When applied to a dirty square, the robot cleans that room and sometimes the adjacent room
- When applied to a clean square, the robot throws dirt in the room


Adapted from:
Russell & Norvig, AI: A Modern Approach

* Solutions are not nodes but conditional plans/ strategies.

Local Search With Non-Deterministic Actions

Erratic Vacuum World

- When applied to a dirty square, the robot cleans that room and sometimes the adjacent room
- When applied to a clean square, the robot throws dirt in the room




Adapted from:
Russell & Norvig, AI: A Modern Approach


Local Search With Non-Deterministic Actions

Erratic Vacuum World


- When applied to a dirty square, the robot cleans that room and sometimes the adjacent room
- When applied to a clean square, the robot throws dirt in the room



Adapted from:
Russell & Norvig, AI: A Modern Approach



Local Search With Non-Deterministic Actions



function AND-OR-SEARCH(*problem*) **returns** a conditional plan, or *failure*
return OR-SEARCH(*problem*, *problem*.INITIAL, [])

function OR-SEARCH(*problem*, *state*, *path*) **returns** a conditional plan, or *failure*
if *problem*.IS-GOAL(*state*) **then** **return** the empty plan
if IS-CYCLE(*path*) **then** **return** *failure*
for each *action* **in** *problem*.ACTIONS(*state*) **do**
 plan ← AND-SEARCH(*problem*, RESULTS(*state*, *action*), [*state*] + *path*)
 if *plan* ≠ *failure* **then** **return** [*action*] + *plan*
return *failure*

function AND-SEARCH(*problem*, *states*, *path*) **returns** a conditional plan, or *failure*
for each *s_i* **in** *states* **do**
 plan_i ← OR-SEARCH(*problem*, *s_i*, *path*)
 if *plan_i* = *failure* **then** **return** *failure*
return [*if s₁ then plan₁ else if s₂ then plan₂ else ... if s_{n-1} then plan_{n-1} else plan_n*]

Adapted from:
 Russell & Norvig, AI: A Modern Approach

Coding Example

- 8-Puzzle – code notebook
 - <https://github.com/biplav-s/course-ai-tai-f23/blob/main/sample-code/Class6-To-Class9-search.md>

Course Project

Project Discussion: What Problem Fascinates You ?

- Data
 - Water
 - Finance
 - ...
- Analytics
 - Search, Optimization, Learning, Planning, ...
- Application
 - Building chatbot
- Users
 - Diverse demographics
 - Diverse abilities
 - Multiple human languages

Project execution in sprints

- Sprint 1: (Sep 12 – Oct 5)
 - **Solving**: Choose a decision problem, identify data, work on solution methods
 - **Human interaction**: Develop a basic chatbot (no AI), no problem focus
- Sprint 2: (Oct 10 – Nov 9)
 - **Solving**: Evaluate your solution on problem
 - **Human interaction**: Integrated your choice of chatbot (rule-based or learning-based) and methods
- Sprint 3: (Nov 14 – 30)
 - **Evaluation**: Comparison of your solver chatbot with an LLM-based alternative, like ChatGPT

Project Discussion: Dates and Deliverables

Project execution in sprints

- Sprint 1: (Sep 12 – Oct 5)
 - **Solving**: Choose a decision problem, identify data, work on solution methods
 - **Human interaction**: Develop a basic chatbot (no AI), no problem focus
- Sprint 2: (Oct 10 – Nov 9)
 - **Solving**: Evaluate your solution on problem
 - **Human interaction**: Integrated your choice of chatbot (rule-based or learning-based) and methods
- Sprint 3: (Nov 14 – 30)
 - **Evaluation**: Comparison of your solver chatbot with an LLM-based alternative, like ChatGPT

- Oct 12, 2023
 - Project checkpoint
 - In-class presentation
- Nov 30, 2023
 - Project report due
- Dec 5 / 7, 2023
 - In-class presentation

Skeleton: A Basic Chatbot

- Run in an infinite loop until the user wants to quit
- Handle any user response
 - User can quit by typing “Quit” or “quit” or just “q”
 - User can enter any other text and the program has to handle it. The program should write back what the user entered and say – “I do not know this information”.
- Handle known user query types // Depends on your project
 - “Tell me about N-queens”, “What is N ?”
 - “Solve for N=4?”
 - “Why is this a solution? ”
- Handle chitchat // Support at least 5, extensible from a file
 - “Hi” => “Hello”
 - ...
- *Store session details in a file*

Illustrative Project

1. **Title:** Solve and explain solving of n-queens puzzle
2. **Key idea:** Show students how a course project will look like
3. **Who will care when done:** students of the course, prospective AI students and teachers
4. **Data need:** n: the size of game; interaction
5. **Methods:** search
6. **Evaluation:** correctness of solution, quality of explanation, appropriateness of chat
7. **Users:** with and without AI background; with and without chess background
8. **Trust issue:** user may not believe in the solution, may find interaction offensive (why queens, not kings? ...)

Project Discussion: Illustration

1. Create a private Github repository called “CSCE58x-Fall2023-<studentname>-Repo”. Share with Instructor (biplav-s) and TA (kausik-l)
2. Create Google folder called “CSCE58x-Fall2023-<studentname>-SharedInfo”. Share with Instructor (prof.biplav@gmail.com) and TA (lakkarajukausik90@gmail.com)
3. Create a Google doc in your Google repo called “Project Plan” and have the following by next class (Sep 5, 2023)

1. **Title:** Solve and explain solving of n-queens puzzle
2. **Key idea:** Show students how a course project will look like
3. **Who will care when done:** students of the course, prospective AI students and teachers
4. **Data need:** n: the size of game; interaction
5. **Methods:** search
6. **Evaluation:** correctness of solution, quality of explanation, appropriateness of chat
7. **Users:** with and without AI background; with and without chess background
8. **Trust issue:** user may not believe in the solution, may find interaction offensive (why queens, not kings? ...)

Project Illustration: N-Queens

- Sprint 1: (Sep 12 – Oct 5)
 - **Solving**: Choose a decision problem, identify data, work on solution methods
 - Method 1: Random solution
 - Method 2: Search – BFS
 - Method 3: Search - ...
 - **Human interaction**: Develop a basic chatbot (no AI) as outlined
 - Deliverable
 - Code structure in Github
 - ./data
 - ./code
 - ./docs
 - ./test
 - Presentation: Make sprint presentation on Oct 12, 2023

Reference: Project Rubric

- **Project results – 60%**
 - Working system ? – 30%
 - Evaluation with results superior to baseline? – 20%
 - Considered related work? – 10%
- **Project efforts – 40%**
 - Project report – 20%
 - Project presentation (updates, final) – 20%
- **Bonus**
 - Challenge level of problem – 10%
 - Instructor discretion – 10%
- **Penalty**
 - Lack of timeliness as per announced policy (right) - up to 30%

Milestones and Penalties

- Oct 12, 2023
 - Project checkpoint
 - In-class presentation
 - **Penalty: presentation not ready by Oct 10, 2023 [-10%]**
- Nov 30, 2023
 - Project report due
 - **Project report not ready by date [-10%]**
- Dec 5 / 7, 2023
 - In-class presentation
 - **Project presentations not ready by Dec 4, 2023 [-10%]**

Lecture 9: Summary

- We talked about
 - Hill climbing
 - Simulated Annealing
 - Genetic programming
 - Search in complex environments

Concluding Section

About Next Lecture – Lecture 10

Lecture 10: Adversarial Games

- Game tree
- Adversarial games