

CSCE 771: Computer Processing of Natural Language

Lecture 22: Sentiment Analysis

PROF. BIPLAV SRIVASTAVA, AI INSTITUTE

7TH NOVEMBER, 2024

Carolinian Creed: “I will practice personal and academic integrity.”

Organization of Lecture 22

- Opening Segment
 - Announcements

- Main Lecture




Main Section


- Sentiment Analysis
- Methods
 - Lexicon-based Methods
 - Learning-based Methods
- Usability considerations - Ethical Issues

- Concluding Segment
 - About Next Lecture – Lecture 23

Main Lecture

Sentiment Detection





Ekman 6 Basic Emotion (1971)

Top-left-to-right: anger, fear, disgust

Bottom-left-to-right: surprise, happy, sadness


<https://psycnet.apa.org/record/1971-07999-001>

Slide Courtesy: Shabnam Tafreshi

Plutchik Wheel of Emotions (1984)

The Complex, Probabilistic Sequence of Events Involved In the Development of an Emotion^[5]

	Stimulus event	Inferred cognition	Feeling	Behavior	Effect
	Threat	"Danger"	Fear, terror	Running, or flying away	Protection
	Obstacle	"Enemy"	Anger, rage	Biting, hitting	Destruction
	Potential mate	"Possess"	Joy, ecstasy	Courting, mating	Reproduction
	Loss of valued person	"Isolation"	Sadness, grief	Crying for help	Reintegration
	Group member	"Friend"	Acceptance, trust	Grooming, sharing	Affiliation
	Gruesome object	"Poison"	Disgust, Loathing	Vomiting, pushing away	Rejection
	New territory	"What's out there?"	Anticipation	Examining, mapping	Exploration
	Sudden novel object	"What is it?"	Surprise	Stopping, alerting	Orientation



Credits:

- https://en.wikipedia.org/wiki/Robert_Plutchik
- Shabnam Tefreshi slide
- <https://www.6seconds.org/2022/03/13/plutchik-wheel-emotions/>

Sentiment Analysis Definition (Liu 2010)

Sentiment analysis is defined by the 5-tuple

$\langle E, F, S, H, T \rangle$, where

- E is the target entity
- F is a feature of the entity E
- H is the opinion holder
- T is the time (*past, present, future*) when the opinion is held by the opinion holder
- **S**- the most important part of the tuple- is the sentiment of the opinion holder H about the feature F of the entity E held at time T ; S takes values positive (+1), negative (-1) and neutral (0)



Slide courtesy: Prof. Pushpak B's talk at UoSC

Types of Sentiment Tasks

- Sentence-level Models
 - Input: Set of sentences, each made up of a set of words
 - Output: A set of labels (positive, negative, neutral)
- Document-level Models
 - Input: Set of documents, each made up of a set of sentences, each made up of a set of words
 - Output: A set of labels (positive, negative, neutral)
- Fine-grained sentiment labels
 - (e.g., sentiment strength)

Applications

- Understanding people
 - Personality Traits
 - Situational Awareness
- Understanding business
 - Stock Market
 - Business intelligence
 - Product Analysis
- Understanding societies
 - Public Health
 - Politics
 - Emotion in Social Media
- More powerful when used in conjunction with other AI techniques
 - Translators
 - Summarization
 - Machine comprehension
- Understand
 - Past
 - Present

Methods

- Rule and lexicon based
- Learning based
 - Deep learning based

A Simple Rule-Based Sentiment Engine

- Process input to get tokens
 - Perform: Stemming, tokenization, part-of-speech tagging and semantic parsing.
- Use lexicons to find polarity of words
- Use a method to aggregate over polarity of words
- Optional: use vector representation for efficiency

SentiWordNet

Stefano Baccianella, Andrea Esuli, and Fabrizio Sebastiani. 2010 SENTIWORDNET 3.0: An Enhanced Lexical Resource for Sentiment Analysis and Opinion Mining. LREC-2010

- Home page: <https://github.com/aesuli/SentiWordNet>
- All WordNet synsets automatically annotated for degrees of positivity, negativity, and objectivity
- $\# \text{ObjScore} = 1 - (\text{PosScore} + \text{NegScore})$

Examples (from):

https://raw.githubusercontent.com/aesuli/SentiWordNet/master/data/SentiWordNet_3.0.0.txt

- a 00006032 0.25 0.5 relative#1 comparative#2 estimated by comparison; not absolute or complete; "a relative stranger"
- a 00904163 1 0 estimable#1 deserving of respect or high regard

Source: Jurafsky & Martin

Scherer's Typology of Affective States

Emotion: relatively brief episode of synchronized response of all or most organismic subsystems in response to the evaluation of an event as being of major significance

angry, sad, joyful, fearful, ashamed, proud, desperate

Mood: diffuse affect state ...change in subjective feeling, of low intensity but relatively long duration, often without apparent cause

cheerful, gloomy, irritable, listless, depressed, buoyant

Interpersonal stance: affective stance taken toward another person in a specific interaction, coloring the interpersonal exchange

distant, cold, warm, supportive, contemptuous

Attitudes: relatively enduring, affectively colored beliefs, preferences predispositions towards objects or persons

liking, loving, hating, valuing, desiring

Personality traits: emotionally laden, stable personality dispositions and behavior tendencies, typical for a person

nervous, anxious, reckless, morose, hostile, envious, jealous

Source: Jurafsky & Martin

The General Inquirer

Philip J. Stone, Dexter C Dunphy, Marshall S. Smith, Daniel M. Ogilvie. 1966. The General Inquirer: A Computer Approach to Content Analysis. MIT Press

- Home page: <http://www.wjh.harvard.edu/~inquirer>
- List of Categories: <http://www.wjh.harvard.edu/~inquirer/homecat.htm>
- Spreadsheet: <http://www.wjh.harvard.edu/~inquirer/inquirerbasic.xls>

Categories:

- Positiv (1915 words) and Negativ (2291 words)
- Strong vs Weak, Active vs Passive, Overstated versus Understated
- Pleasure, Pain, Virtue, Vice, Motivation, Cognitive Orientation, etc

Free for Research Use


Source: Jurafsky & Martin

Learning Based

A Learning-Based Sentiment Engine

- Process input to get tokens
 - Perform: Stemming, tokenization, part-of-speech tagging and semantic parsing.
- Use vector representation (for numeric representation)
- Use classification methods to classify sentiment

DL Based Automation of Emotion Classification



Stanford Sentiment Resources

- IMDB:
 - Dataset and paper (ACL 2011)
 - <https://ai.stanford.edu/~amaas/data/sentiment/>
- Highlights
 - The dataset has 50,000 reviews from IMDB, allowing no more than 30 reviews per movie.
 - The dataset has even number number of positive and negative movie reviews.
 - The dataset contains highly polar movie reviews data. A negative review has a score ≤ 4 out of 10, and a positive review has a score ≥ 7 out of 10.
 - The dataset is evenly divided into training and test sets.
 - This dataset is widely used to benchmark new work.

Credit: Fawad Kirmani

Sentiment Analysis with Treebank

- Treebank
 - Details: <https://nlp.stanford.edu/sentiment/index.html>
 - Demo: <https://nlp.stanford.edu/sentiment/treebank.html?w=bad&nb=5>
- Code courtesy Karan Agarwal, IIT-D
 - <https://github.com/karan109/Sentiment-Analysis>

Sentiment Analysis Code Examples

- Using lexicon-based methods

<https://github.com/biplav-s/course-d2d-ai/blob/7f90f154729115a31f449702dbdf84d63be7a844/sample-code/l23-textrepresent/Basic%20Sentiment.ipynb>

- Using Language Models

<https://github.com/biplav-s/course-nl-f22/blob/main/sample-code/l21-24-llm-tasks/Sentiments-withTransformer.ipynb>

Ethical Issues With Sentiment Systems

Sentiment and Bias

- Consider example:
 - ‘This **man** made me feel angry’
 - ‘This **woman** made me feel angry’
- Authors find bias based on gender and race in 219 automatic systems that participated in SemEval-2018

Template	#sent.
<i>Sentences with emotion words:</i>	
1. <Person> feels <emotional state word>.	1,200
2. The situation makes <person> feel <emotional state word>.	1,200
3. I made <person> feel <emotional state word>.	1,200
4. <Person> made me feel <emotional state word>.	1,200
5. <Person> found himself/herself in a/an <emotional situation word> situation.	1,200
6. <Person> told us all about the recent <emotional situation word> events.	1,200
7. The conversation with <person> was <emotional situation word>.	1,200
<i>Sentences with no emotion words:</i>	
8. I saw <person> in the market.	60
9. I talked to <person> yesterday.	60
10. <Person> goes to the school in our neighborhood.	60
11. <Person> has two children.	60
Total	8,640

Examining Gender and Race Bias in Two Hundred Sentiment Analysis Systems,
Svetlana Kiritchenko and Saif M. Mohammad, <https://www.aclweb.org/anthology/S18-2.pdf>
Download data from: <http://saifmohammad.com/WebPages/Biases-SA.html>

Problem of Bias with Sentiments


- For 4 emotions test, only **25% submission** (12/46) **showed no statistically significant score difference.**
- 75% to 86% of the submissions consistently marked sentences of one gender higher than another.
- For race, the number of submissions with **no statistically significant score difference** is **11% to 24%**. **Lower than gender. [See paper]**

Examining Gender and Race Bias in Two Hundred Sentiment Analysis Systems,
Svetlana Kiritchenko and Saif M. Mohammad, <https://www.aclweb.org/anthology/S18-2.pdf>


Task	Bias group	#Subm.	Avg. score diff.	
			F↑-M↓	F↓-M↑
Anger intensity prediction				
	F=M not significant	12	0.042	-0.043
	F↑-M↓ significant	21	0.019	-0.014
	F↓-M↑ significant	13	0.010	-0.017
	All	46	0.023	-0.023
Fear intensity prediction				
	F=M not significant	11	0.041	-0.043
	F↑-M↓ significant	12	0.019	-0.014
	F↓-M↑ significant	23	0.015	-0.025
	All	46	0.022	-0.026
Joy intensity prediction				
	F=M not significant	12	0.048	-0.049
	F↑-M↓ significant	25	0.024	-0.016
	F↓-M↑ significant	8	0.008	-0.016
	All	45	0.027	-0.025
Sadness intensity prediction				
	F=M not significant	12	0.040	-0.042
	F↑-M↓ significant	18	0.023	-0.016
	F↓-M↑ significant	16	0.011	-0.018
	All	46	0.023	-0.023
Valence prediction				
	F=M not significant	5	0.020	-0.018
	F↑-M↓ significant	22	0.023	-0.013
	F↓-M↑ significant	9	0.012	-0.014
	All	36	0.020	-0.014

T-test: The null hypothesis that the true mean difference between the paired samples is zero can be rejected if the calculated p-value falls below 0.05/438.

ROSE: Visualizations for Sentiment Analysis System (SAS)



Sentiment scores of sentences having the word 'annoying' using all 6 SASs



Average sentiment scores of sentences calculated using all 6 SASs with male pronouns as object

- All the connected scatterplots have been constructed using d3.js
- Link to access ROSE - <https://ai4society.github.io/sentiment-rating/>
- Youtube Demo Link for ROSE - <https://youtu.be/QsL3nWkRGXU/>

Sentiment Detection from Multimodal Media

- Multiple genre / tasks
 - blog posts, news headlines, and movie reviews
 - https://github.com/shabnamt/jointMultitaskEmo/tree/master/data/emo_multigenre
- Multiple media / data types
 - Combine text and numeric score
 - <https://stackabuse.com/python-for-nlp-creating-multi-data-type-classification-models-with-keras/>

Key References

- EMNLP 2016, **Neural Networks for Sentiment Analysis**
 - [Yue Zhang](#) and [Duy Tin Vo](#)
 - <https://mirror.aclweb.org/emnlp2016/tutorials/zhang-vo-t4.pdf>
- MonkeyLearn blog: <https://monkeylearn.com/sentiment-analysis/>

Resources

ML models

<https://machinelearningmastery.com/predict-sentiment-movie-reviews-using-deep-learning/>
<https://machinelearningmastery.com/regression-tutorial-keras-deep-learning-library-python/>
<https://huggingface.co/transformers/training.html>
<https://mccormickml.com/2019/07/22/BERT-fine-tuning/>
<https://towardsdatascience.com/elmo-embeddings-in-keras-with-tensorflow-hub-7eb6f0145440>

Word-Embedding

<https://fasttext.cc/docs/en/crawl-vectors.html> (traditional statis)
<https://allennlp.org/elmo> (contextualized bi-directional)
<https://github.com/google-research/bert> (feature-based from transformers)

Datasets

<https://github.com/shabnamt/jointMultitaskEmo/tree/master/data> (categorical multigenre)
<https://www.aclweb.org/anthology/E17-2092.pdf> (Github provided in the paper)
<https://www.aclweb.org/anthology/P17-1067.pdf> (Request for tweet IDs from the author)
<https://competitions.codalab.org/competitions/17751> (Affect in tweets, SemEval 2018)


Case Study of Sentiment in Business

Clarity: Data-Driven Competitive Analysis


1. Sheema Usmani, Mariana Bernagozzi, Yufeng Huang, Michelle Morales, Amir Sabet Sarvestani, Biplav Srivastava, Clarity: Data-driven Automatic Assessment of Product Competitiveness, IAAI/AAAI 2020, **Deployed Application Award**
2. (Demo paper) Data-driven ranking and visualization of products by competitiveness, Sheema Usmani, Mariana Bernagozzi, Yufeng Huang, Michelle Morales, Amir Sabet Sarvestani, Biplav Srivastava, AAAI 2020
3. [Yufeng Huang](#), [Mariana Bernagozzi](#), [Michelle Morales](#), [Sheema Usmani](#), Biplav Srivastava, [Michelle Mullins](#), Clarity 2.0: Improved Assessment of Product Competitiveness from Online Content. [AI Mag. 42\(2\)](#): 59-70 (2021)

Competitive Analysis: Before & After

Today's Manual Process




New Process



Steps


1. Prepare review data of products p_1 to p_N from sources d_1 to d_M (offline)
2. Process request for analysis for product p_i (online)
3. Visualize analysis results (online, optional)

Illustrative Output




Clarity Score and Trends

Methodology



Sentiment Analysis



Lecture 21: Concluding Comments

- We looked at Sentiment Analysis methods
- Methods
 - Lexicon-based Methods
 - Learning-based Methods
- Usability considerations - Ethical Issues
- Application in a business setting

About Next Lecture – Lecture 23

Lecture 23 Outline

- Text summarization
 - Extractive summarization
 - Abstractive summarization

18	Oct 22 (Tu)	Entity extraction, linking
19	Oct 24 (Th)	Events extraction, spatio-temporal analysis
20	Oct 29 (Tu)	Topic Analysis
21	Oct 31 (Th)	PROJ REVIEW
	Nov 5 (Tu)	
22	Nov 7 (Th)	NLP Task: Sentiment
23	Nov 12 (Tu)	NLP Task: Summarization
24	Nov 14 (Th)	Conversation Agents
25	Nov 19 (Tu)	Ethical Concerns with NLP, Trusted AI and Societal Impact
26	Nov 21 (Th)	Working with LLMs for NLP Tasks - programming, Quiz