

# PRACTICAL 8

2520090008\_Sathish kumar

Spring Boot Application Running Successfully

```
2026-09-30T18:42:32.479+05:30 INFO 12212 --- [student-records]
[main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tom
cat started on port 8080 (http) with context path '/'
2026-09-30T18:42:32.486+05:30 INFO 12212 --- [student-records]
[main] c.e.s.StudentRecordsApplication : Sta
rted StudentRecordsApplication in 4.066 seconds (process running
for 4.735)
```

Registering the user:

```
PS C:\WINDOWS\system32> cd "C:\Users\DELL\OneDrive\Documents\S D
BE&DBD\Practical\student-records\student-records"
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-
records\student-records> Invoke-RestMethod -Uri "http://localhos
t:8080/auth/register" -Method POST -ContentType "application/json
" -Body '{"username":sathish , "password":"secret123"}'

message
-----
registered successfully
```

User Login and JWT Token Generation:

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-
records\student-records> Invoke-RestMethod -Uri "http://localhos
t:8080/auth/login" -Method POST -ContentType "application/json"
-Body '{"username":"sathish","password":"secret123"}'

token
-----
eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJhbmFueWEiLCJpYXQiOiJECJh5Yk8Z...
```

Saving the JWT Token:

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-
records\student-records> $token = "eyJhbGciOiJIUzI1NiJ9.eyJzdWIi
OiJhbmFueWEiLCJpYXQiOiJECJh5Yk8Z..."
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-
records\student-records> $headers = @{
>> Authorization = "Bearer $token"
>> }
```

GET All Students Records:

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-records\student-records> Invoke-RestMethod -Uri "http://localhost:8080/students" -Method GET -Headers $headers
```

```
id      : 6ab0d6e94bd72bb2efd336e4
name    : Sathish
age     : 18
course  : AI&DS
email   : ananyamaraju@klh.edu.in
```

Student Record Updated Successfully:

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-records\student-records>
> Invoke-RestMethod -Uri "http://localhost:8080/students/6ab0d6e94bd72bb2efd336e4" -Method PUT -Headers $headers -ContentType "application/json" -Body '{"name": "Sathish", "age": 19, "course": "AI&DS", "email": "ananyamaraju@klh.edu.in"}'
```

```
id      : 6ab0d6e94bd72bb2efd336e4
name    : Sathish
age     : 19
course  : AI&DS
email   : ananyamaraju@klh.edu.in
```

Test Validation: Student Input Validation and Error Handling

```
PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-records\student-records> Invoke-RestMethod -Uri "http://localhost:8080/students" -Method POST -Headers $headers -ContentType "application/json" -Body '{"name":"","age":10,"course":"","email":"wrong-email"}'
```

```
Invoke-RestMethod : The remote server returned an error: (400) Bad Request.
```

```
At line:1 char:1
```

```
+ Invoke-RestMethod -Uri "http://localhost:8080/students" -Method POST ...
```

```
+ ~~~~~
```

```
+ CategoryInfo          : InvalidOperation: (System.Net.HttpWebRequest:HttpWebRequest) [Invoke-RestMethod], WebException
```

```
+ FullyQualifiedErrorId : WebCmdletWebResponseException,Microsoft.PowerShell.Commands.InvokeRestMethodCommand
```

Student Records Stored in MongoDB

```

test> use student_records
switched to db student_records
student_records> show collections
students
users
student_records> db.students.find().pretty()
[
  {
    _id: ObjectId('6ab0d6e94bd72bb2efd336e4'),
    name: 'ASathish',
    age: 19,
    course: 'AI&DS',
    email: 'ananyamaraju@klh.edu.in',
    _class: 'com.example.student_records.entity.Student'
  }
]
student_records> |

```

Delete the student record

```

PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-records\student-records> Invoke-RestMethod -Uri "http://localhost:8080/students/6ab0d6e94bd72bb2efd336e4" -Method DELETE -Headers $headers

```

Output on PowerShell 1: [Student Record Deleted Successfully]

```

2026-09-30T20:41:01.852+05:30 INFO 14660 --- [student-records]
[nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Completed initialization in 2 ms
JWT VALID
JWT VALID

```

Student data deletion verification

```

PS C:\Users\DELL\OneDrive\Documents\S DBE&DBD\Practical\student-records\student-records> Invoke-RestMethod -Uri "http://localhost:8080/students" -Method GET -Headers $headers

```

MongoDB Records After Deletion

```

test> use student_records
switched to db student_records
student_records> db.students.find().pretty()

student_records> exit

```

Folder Structure:

Week-8\_Practical\_Student\_Records/

|

```
├── students-records
|   ├── pom.xml
|   ├── mvnw
|   ├── mvnw.cmd
|   ├── .mvn/
|   ├── src/
|   |   ├── main/
|   |   |   ├── java/
|   |   |   |   ├── com/
|   |   |   |   |   ├── example/
|   |   |   |   |   |   ├── student_records/
|   |   |   |   |   |   |   ├── StudentRecordsApplication.java
|   |   |   |   |   |   |   ├── controller/
|   |   |   |   |   |   |   ├── dto/
|   |   |   |   |   |   |   ├── entity/
|   |   |   |   |   |   |   ├── exception/
|   |   |   |   |   |   |   ├── repository/
|   |   |   |   |   |   |   ├── security/
|   |   |   |   |   |   |   ├── service/
|   |   |   |   |   |   |   └──
|   |   |   └── resources/
|   |   |       ├── application.properties
|   |   |       └──
|   |   └── target/
```

## Codes:

### 1. Main Application

· StudentRecordsApplication.java

```
package com.example.student_records;
```

```
import org.springframework.boot.SpringApplication;
```

```
import org.springframework.boot.autoconfigure.SpringBootApplication;
```

```
@SpringBootApplication
public class StudentRecordsApplication {

    public static void main(String[] args) {
        SpringApplication.run(StudentRecordsApplication.class, args);
    }

}
```

## 2. Entity

· Student.java

```
package com.example.student_records.entity;

import org.springframework.data.annotation.Id;
import org.springframework.data.mongodb.core.mapping.Document;

@Document(collection="students")
public class Student {

    @Id
    private String id;

    private String name;
    private Integer age;
    private String course;
    private String email;

    public String getId() {
        return id;
    }

    public void setId(String id) {
        this.id = id;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

}
```

```

    public Integer getAge() {
        return age;
    }

    public void setAge(Integer age) { this.age =
        age;
    }

    public String getCourse() {
        return course;
    }

    public void setCourse(String course) { this.course
        = course;
    }

    public String getEmail() {
        return email;
    }

    public void setEmail(String email) { this.email =
        email;
    }
}
· User.java

```

```

package com.example.student_records.entity;

```

```

import org.springframework.data.annotation.Id;
import org.springframework.data.mongodb.core.index.Indexed; import
org.springframework.data.mongodb.core.mapping.Document;

```

```

@Document(collection = "users")
public class User {

```

```

    @Id
    private String id;

```

```

    @Indexed(unique = true)
    private String username;

```

```

    private String password;

```

```

    public String getId() {
        return id;
    }
}

```

```

    public void setId(String id) {
        this.id = id;
    }

    public String getUsername() {
        return username;
    }

    public void setUsername(String username) {
        this.username = username;
    }

    public String getPassword() {
        return password;
    }

    public void setPassword(String password) {
        this.password = password;
    }
}

```

### 3. DTO

```

· StudentRequest.java
package com.example.student_records.dto;

import jakarta.validation.constraints.Email; import
jakarta.validation.constraints.Min;
import jakarta.validation.constraints.NotBlank; import
jakarta.validation.constraints.NotNull;

public class StudentRequest {

    @NotBlank(message = "name is required")
    private String name;

    @NotNull(message = "age is required")
    @Min(value = 16, message = "age must be at least 16") private Integer
    age;

    @NotBlank(message = "course is required")
    private String course;

    @NotBlank(message = "email is required")
    @Email(message = "a valid email is required") private

```

```

String email;

public String getName() {
    return name;
}

public void setName(String name) {
    this.name = name;
}

public Integer getAge() {
    return age;
}

public void setAge(Integer age) {
    this.age = age;
}

public String getCourse() {
    return course;
}

public void setCourse(String course) {
    this.course = course;
}

public String getEmail() {
    return email;
}

public void setEmail(String email) {
    this.email = email;
}
}

```

· RegisterRequest.java

```

package com.example.student_records.dto;

import jakarta.validation.constraints.NotBlank;
import jakarta.validation.constraints.Size;

public class RegisterRequest {

    @NotBlank
    private String username;

```

```

    @NotBlank
    @Size(min = 6, message = "password must be at least 6 characters") private String
    password;

    public String getUsername() {
        return username;
    }

    public void setUsername(String username) {
        this.username = username;
    }

    public String getPassword() {
        return password;
    }

    public void setPassword(String password) {
        this.password = password;
    }
}

```

· LoginRequest.java

```

package com.example.student_records.dto;
import jakarta.validation.constraints.NotBlank;

public class LoginRequest {

    @NotBlank
    private String username;

    @NotBlank
    private String password;

    public String getUsername() {
        return username;
    }

    public void setUsername(String username) {
        this.username = username;
    }

    public String getPassword() {
        return password;
    }
}

```

```

        public void setPassword(String password) {
            this.password = password;
        }
    }
}

```

## 4. Repository

· StudentRepository.java

```

package com.example.student_records.repository;

import com.example.student_records.entity.Student;
import org.springframework.data.mongodb.repository.MongoRepository;

public interface StudentRepository extends MongoRepository<Student, String> {
}

```

· UserRepository.java

```

package com.example.student_records.repository;

import com.example.student_records.entity.User;
import org.springframework.data.mongodb.repository.MongoRepository; import
java.util.Optional;

public interface UserRepository extends MongoRepository<User, String> {

    Optional<User> findByUsername(String username);
}

```

## 5. Service

· StudentService.java

```

package com.example.student_records.service;

import com.example.student_records.dto.StudentRequest;
import com.example.student_records.entity.Student;
import com.example.student_records.repository.StudentRepository; import
org.springframework.stereotype.Service;

import java.util.List;
import java.util.Optional;

```

@Service

public class StudentService {

private final StudentRepository repository;

public StudentService(StudentRepository repository) {  
 this.repository = repository;  
 }

public Student create(StudentRequest r) {

Student s = new Student();

apply(s, r);

return repository.save(s);  
 }

public List<Student> getAll() {  
 return repository.findAll();  
 }

public Optional<Student> getById(String id) {  
 return repository.findById(id);  
 }

public Optional<Student> update(String id, StudentRequest r) {  
 return repository.findById(id).map(s -> {  
  
 apply(s, r);  
  
 return repository.save(s);  
 });  
 }

public boolean delete(String id) {

if (!repository.existsById(id)) {  
 return false;  
 }

repository.deleteById(id);

return true;  
 }

```

private void apply(Student s, StudentRequest r) {

    s.setName(r.getName());
    s.setAge(r.getAge());
    s.setCourse(r.getCourse());
    s.setEmail(r.getEmail());
}
}

```

## 6. Controller

· StudentController.java

```

package com.example.student_records.controller;

import com.example.student_records.dto.StudentRequest; import
com.example.student_records.entity.Student; import
com.example.student_records.service.StudentService;

import jakarta.validation.Valid;

import org.springframework.http.ResponseEntity; import
org.springframework.web.bind.annotation.*;

import java.util.List;

@RestController
@RequestMapping("/students")
public class StudentController {

    private final StudentService service;

    public StudentController(StudentService service) { this.service =
        service;
    }

    @PostMapping
    public ResponseEntity<Student> create(
        @Valid @RequestBody StudentRequest r) {

        return ResponseEntity
            .status(201)
            .body(service.create(r));
    }
}

```

```

    @GetMapping
    public List<Student> getAll() {
        return service.getAll();
    }

    @GetMapping("/{id}")
    public ResponseEntity<Student> getById(
        @PathVariable String id) {

        return service.getById(id)
            .map(ResponseEntity::ok)
            .orElse(ResponseEntity.notFound().build());
    }

    @PutMapping("/{id}")
    public ResponseEntity<Student> update(
        @PathVariable String id,
        @Valid @RequestBody StudentRequest r) {

        return service.update(id, r)
            .map(ResponseEntity::ok)
            .orElse(ResponseEntity.notFound().build());
    }

    @DeleteMapping("/{id}")
    public ResponseEntity<Void> delete(
        @PathVariable String id) {

        return service.delete(id)
            ? ResponseEntity.noContent().build()
            : ResponseEntity.notFound().build();
    }
}

```

· AuthController.java

```

package com.example.student_records.controller;

import com.example.student_records.dto.LoginRequest;
import com.example.student_records.dto.RegisterRequest;
import com.example.student_records.entity.User;
import com.example.student_records.repository.UserRepository; import
com.example.student_records.security.JwtUtil;

import jakarta.validation.Valid;

```

```

import org.springframework.http.ResponseEntity;

import org.springframework.security.authentication.AuthenticationManager; import
org.springframework.security.authentication.UsernamePasswordAuthenticationToken;

import org.springframework.security.crypto.password.PasswordEncoder; import

org.springframework.web.bind.annotation.*;

import java.util.Map;

@RestController
@RequestMapping("/auth")
public class AuthController {

    private final UserRepository users;
    private final PasswordEncoder encoder;
    private final AuthenticationManager manager;
    private final JwtUtil jwt;

    public AuthController(
        UserRepository users,
        PasswordEncoder encoder,
        AuthenticationManager manager,
        JwtUtil jwt) {

        this.users = users;
        this.encoder = encoder;
        this.manager = manager;
        this.jwt = jwt;
    }

    @PostMapping("/register")
    public ResponseEntity<?> register(
        @Valid @RequestBody RegisterRequest r) {

        if (users.findByUsername(r.getUsername()).isPresent()) {

            return ResponseEntity
                .badRequest()
                .body(Map.of(
                    "error",
                    "username already taken"
                ));
        }
    }

```

```

        User user = new User();

        user.setUsername(r.getUsername());

        user.setPassword(
            encoder.encode(r.getPassword())
        );

        users.save(user);

        return ResponseEntity
            .status(201)
            .body(Map.of(
                "message",
                "registered successfully"
            ));
    }

    @PostMapping("/login")
    public ResponseEntity<?> login(
        @Valid @RequestBody LoginRequest r) {

        manager.authenticate(
            new UsernamePasswordAuthenticationToken(
                r.getUsername(),
                r.getPassword()
            )
        );

        return ResponseEntity.ok(
            Map.of(
                "token",
                jwt.generateToken(r.getUsername())
            )
        );
    }
}

```

## 7. Security

· SecurityConfig.java

```

package com.example.student_records.security;

import org.springframework.context.annotation.Bean;

```

```

import org.springframework.context.annotation.Configuration;

import org.springframework.security.authentication.AuthenticationManager; import
org.springframework.security.config.annotation.authentication.configuration
.AuthenticationConfiguration;

import
org.springframework.security.config.annotation.web.builders.HttpSecurity; import
org.springframework.security.config.http.SessionCreationPolicy;

import org.springframework.security.crypto.bcrypt.BCryptPasswordEncoder; import
org.springframework.security.crypto.password.PasswordEncoder;

import org.springframework.security.web.SecurityFilterChain; import
org.springframework.security.web.authentication.UsernamePasswordAuthenticat ionFilter;

@Configuration
public class SecurityConfig {

    private final JwtAuthFilter jwtAuthFilter;

    public SecurityConfig(JwtAuthFilter jwtAuthFilter) {
        this.jwtAuthFilter = jwtAuthFilter;
    }

    @Bean
    public PasswordEncoder passwordEncoder() {
        return new BCryptPasswordEncoder();
    }

    @Bean
    public AuthenticationManager authenticationManager(
        AuthenticationConfiguration configuration)
        throws Exception {

        return configuration.getAuthenticationManager();
    }

    @Bean
    public SecurityFilterChain filterChain(
        HttpSecurity http)
        throws Exception {

        return http
            .csrf(csrf -> csrf.disable())

            .sessionManagement(session ->

```

```

        session.sessionCreationPolicy(
            SessionCreationPolicy.STATELESS
        )
    )

    .authorizeHttpRequests(auth ->
        auth
            .requestMatchers("/auth/**")
            .permitAll()

            .anyRequest()
            .authenticated()
    )

    .addFilterBefore(
        jwtAuthFilter,
        UsernamePasswordAuthenticationFilter.class
    )

    .build();
}
}

```

· JwtUtil.java

```

package com.example.student_records.security;

import io.jsonwebtoken.*;
import io.jsonwebtoken.security.Keys;

import org.springframework.beans.factory.annotation.Value;
import org.springframework.stereotype.Component;

import javax.crypto.SecretKey;
import java.nio.charset.StandardCharsets;
import java.util.Date;

@Component
public class JwtUtil {

    @Value("${jwt.secret}")
    private String secret;

    @Value("${jwt.expiration-ms}")
    private long expirationMs;

```

```

private SecretKey key() {

    return Keys.hmacShaKeyFor(
        secret.getBytes(StandardCharsets.UTF_8)
    );
}

public String generateToken(String username) {

    Date now = new Date();

    return Jwts.builder()
        .setSubject(username)
        .setIssuedAt(now)
        .setExpiration(
            new Date(now.getTime() + expirationMs)
        )
        .signWith(key(), SignatureAlgorithm.HS256)
        .compact();
}

public String extractUsername(String token) {

    return Jwts.parserBuilder()
        .setSigningKey(key())
        .build()
        .parseClaimsJws(token)
        .getBody()
        .getSubject();
}

public boolean isValid(String token) {
    try {

        Jwts.parserBuilder()
            .setSigningKey(key())
            .build()
            .parseClaimsJws(token);

        return true;

    } catch (JwtException | IllegalArgumentException e) {

        return false;
    }
}
}

```

· JwtAuthFilter.java

```
package com.example.student_records.security;

import jakarta.servlet.*;
import jakarta.servlet.http.*;

import
org.springframework.security.authentication.UsernamePasswordAuthenticationToken;
import org.springframework.security.core.context.SecurityContextHolder; import
org.springframework.security.core.userdetails.UserDetailsService; import
org.springframework.security.web.authentication.WebAuthenticationDetailsSource;
import org.springframework.stereotype.Component;
import org.springframework.web.filter.OncePerRequestFilter; import

java.io.IOException;

@Component
public class JwtAuthFilter extends OncePerRequestFilter {

    private final JwtUtil jwtUtil;
    private final UserDetailsService userDetailsService;

    public JwtAuthFilter(
        JwtUtil jwtUtil,
        UserDetailsService userDetailsService) {

        this.jwtUtil = jwtUtil;
        this.userDetailsService = userDetailsService;
    }

    @Override
    protected void doFilterInternal(
        HttpServletRequest request,
        HttpServletResponse response,
        FilterChain chain)
        throws ServletException, IOException {

        String header = request.getHeader("Authorization");

        if (header != null && header.startsWith("Bearer ")) { String token =

            header.substring(7);
```

```

        if (jwtUtil.isValid(token)) {

            System.out.println("JWT VALID");

            String username =
                jwtUtil.extractUsername(token);

            var details =
                userDetailsService.loadUserByUsername(username);

            var authentication =
                new UsernamePasswordAuthenticationToken(
                    details,
                    null,
                    details.getAuthorities()
                );

            authentication.setDetails(
                new WebAuthenticationDetailsSource()
                    .buildDetails(request)
            );

            SecurityContextHolder
                .getContext()
                .setAuthentication(authentication);

        } else {

            System.out.println("JWT INVALID");

        }
    }
    chain.doFilter(request, response);
}
}

```

· CustomUserDetailsService.java

```

package com.example.student_records.security;

import com.example.student_records.repository.UserRepository;

import org.springframework.security.core.userdetails.*;
import org.springframework.stereotype.Service;

@Service
public class CustomUserDetailsService implements UserDetailsService { private final

```

```

    UserRepository userRepository;

    public CustomUserDetailsService(UserRepository userRepository) {
        this.userRepository = userRepository;
    }

    @Override
    public UserDetails loadUserByUsername(String username)
        throws UsernameNotFoundException {

        var user = userRepository
            .findByUsername(username)
            .orElseThrow(() ->
                new UsernameNotFoundException("User not found"));

        return User.withUsername(user.getUsername())
            .password(user.getPassword())
            .authorities("USER")
            .build();
    }
}

```

## 8. Exception Handling

· GlobalExceptionHandler.java

```

package com.example.student_records.exception;

import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.MethodArgumentNotValidException;
import org.springframework.web.bind.annotation.ExceptionHandler; import
org.springframework.web.bind.annotation.RestControllerAdvice;

import java.util.HashMap;
import java.util.Map;

@RestControllerAdvice
public class GlobalExceptionHandler {

    @ExceptionHandler(MethodArgumentNotValidException.class)
        public ResponseEntity<Map<String, Object>> handleValidation(
            MethodArgumentNotValidException ex) {

        Map<String, String> errors = new HashMap<>();

        ex.getBindingResult()

```

```

        .getFieldErrors()
        .forEach(error ->
            errors.put(
                error.getField(),
                error.getDefaultMessage()
            )
        );

    Map<String, Object> body = new HashMap<>();

    body.put("error", "VALIDATION_ERROR");
    body.put("details", errors);

    return ResponseEntity.badRequest().body(body);
}
}

```

## 9. Configuration

application.properties

spring.application.name=student-records

spring.data.mongodb.uri=mongodb://localhost:27017/student\_records

jwt.secret=replace-this-with-a-long-random-secret-at-least-32-characters

jwt.expiration-ms=3600000

server.port=8080

## 10. Maven Configuration

· pom.xml

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<project xmlns="http://maven.apache.org/POM/4.0.0"
```

```
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
        xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
```

```
    https://maven.apache.org/xsd/maven-4.0.0.xsd">
```

```
<modelVersion>4.0.0</modelVersion>
```

```
<parent>
```

```
    <groupId>org.springframework.boot</groupId>
```

```
    <artifactId>spring-boot-starter-parent</artifactId>
```

```
    <version>3.5.6</version>
```

```
        <relativePath/>
    </parent>

    <groupId>com.example</groupId>
    <artifactId>student-records</artifactId>
    <version>0.0.1-SNAPSHOT</version>
    <name>student-records</name>
    <description>Student Records Application</description>

    <properties>
        <java.version>17</java.version>
    </properties>

    <dependencies>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-web</artifactId>
        </dependency>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-data-mongodb</artifactId>
        </dependency>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-validation</artifactId>
        </dependency>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-security</artifactId> </dependency>

        <dependency>
            <groupId>io.jsonwebtoken</groupId>
            <artifactId>jjwt-api</artifactId>
            <version>0.11.5</version>
        </dependency>

        <dependency>
            <groupId>io.jsonwebtoken</groupId>
            <artifactId>jjwt-impl</artifactId>
            <version>0.11.5</version>
            <scope>runtime</scope>
        </dependency>
    </dependencies>

```

```
<dependency>
  <groupId>io.jsonwebtoken</groupId>
  <artifactId>jjwt-jackson</artifactId>
  <version>0.11.5</version>
  <scope>runtime</scope>
</dependency>

<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-test</artifactId>
  <scope>test</scope>
</dependency>

</dependencies>

<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId> </plugin>
    </plugins>
  </build>

</project>
```