

OPERATORS

CSC100 Introduction to programming in C/C++ (Spring 2024)

Marcus Birkenkrahe

February 27, 2025

Contents

1	README	2
2	Preamble	2
3	Operators in C	5
4	Operators in other languages	6
5	PRACTICE Build a simple calculator	7
6	Boolean algebra	9
7	Exploring Boolean algebra	10
8	PRACTICE Boolean logic test	13
9	Expanding Boolean algebra	16
10	Order of operator operations (codealong)	19
11	PRACTICE Predict the output	21
12	Booleans in C	23
13	! operator (logical NOT)	23
14	&& operator (logical AND)	24
15	 operator (logical OR)	25

16 PRACTICE Logical operators	25
17 Proving Boolean equivalence with code	28
18 Checking for upper and lower case	30
19 PRACTICE Checking for upper and lower case	31
20 PRACTICE ASCII code of letters	33
21 Checking for a range of values	34
22 PRACTICE Checking for a range of values	35
23 PRACTICE Chained expression	37
24 PRACTICE Upload your practice files as a ZIP archive	39
25 References	40

1 README

- In this section of the course, we go beyond simple statements and turn to program flow and evaluation of logical conditions
- This section follows chapter 3 in the book by Davenport/Vine (2015) and chapters 4 and 5 in the book by King (2008)
- Practice workbooks, input files and PDF solution files in GitHub

2 Preamble

- **Algorithms** are the core of programming
- Example for an algorithm: *"When you come to a STOP sign, stop."*
- The human form of algorithm is **heuristics**
- Example for a heuristic: *"To get to the college, go straight."*
- For **programming**, you need both algorithms and heuristics
- Useful tools to master when designing algorithms:



Figure 1: City, telephone room, 1955 (Flickr.com)



Figure 2: Photo: Alan Levine, public domain. Source: Flickr.com

- **Pseudocode** (task flow description)
- **Visual modeling** (task flow visualization)

3 Operators in C

- Mathematically, operators are really functions: `f(i,j)=i+j`
- C has many operators, both **unary**, with one argument, like `-1`, and **binary**, with two arguments, like `1+1`.
- A list of types of operators in C:

Table 1: Operator types in C

OPERATOR	WHY USE IT	EXAMPLES	EXPRESSION
Arithmetic	compute	<code>* + - / %</code>	<code>i * j + k</code>
Relational	compare	<code>< > <= >=</code>	<code>i > j</code>
Equality	compare (in/equality)	<code>== !=</code>	<code>i == j</code>
Logical	confirm (truth)	<code>&&</code>	<code>i && j</code>
Assignment	change	<code>=</code>	<code>i = j</code>
Increment/decrement	change stepwise	<code>++, +-</code>	<code>++i</code>

- Note: there is no exponential operator (though there is a power function `pow` in `math.h`¹ - you need to use `*` instead.
- **Conditional** operators used in C are important for program flow:

Table 2: Conditional operators in C

OPERATOR	DESCRIPTION	EXPRESSION	BOOLEAN VALUE
<code>==</code>	Equal	<code>5 == 5</code>	true
<code>!=</code>	Not equal	<code>5 != 5</code>	false
<code>></code>	Greater than	<code>5 > 5</code>	false
<code><</code>	Less than	<code>5 < 5</code>	false
<code>>=</code>	Greater than or equal to	<code>5 >= 5</code>	true
<code><=</code>	Less than or equal to	<code>5 <= 5</code>	true

- Conditional = the operator tests a condition:

`x == y // is x equal to y? if yes, then return TRUE`

¹See here for more information.

- The value of an evaluated conditional operator is **Boolean** (logical) - e.g. `2==2` evaluates as **TRUE** or **1**.
- The only **unary** operator is **!** also known as **NOT**: It merely inverts the Boolean or truth value of its argument.

```
int x = 1; // defining x
printf("If x = %d, then: NOT x = %d\n",x, !x);
printf("If x = !%d, then: x = %d\n",!x, x);
```

```
If x = 1, then: NOT x = 0
If x = !0, then: x = 1
```

4 Operators in other languages



Figure 3: Photo: Jack Delano, Sawmill (1939). Source: Library of Congress

- Different programming languages differ greatly rgd. operators. For example, in the language R, the `|>` operator ("pipe") passes a data set to a function².

```
## pipe data set into function
mtcars |> head(n=2)
## use data set as function argument
head(mtcars,n=2)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4	21	6	160	110	3.9	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21	6	160	110	3.9	2.875	17.02	0	1	4	4
	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4	21	6	160	110	3.9	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21	6	160	110	3.9	2.875	17.02	0	1	4	4

- You already met the `>` and `»` operators of the `bash` shell language that redirects standard output to a file:

```
> empty # create empty file called "empty"
ls -l empty # shows the result
```

```
echo 100 > input
cat input
```

5 PRACTICE Build a simple calculator

- Execute this exercise using the Google Cloud Shell, the `nano` editor, and the `gcc` compiler. Put your result in a file `calc.c`
- Write a simple calculator for integer values.
- `#include <stdio.h>` and use the following pseudocode inside `main`:

```
// declare two integer variables a, b

// ask user for input
```

²Only from R version 4.1 - before that, you have to use the magrittr pipe operator `%>%`.

```
// get two integer values as input (from the keyboard)

// compute and print results for +, -, *, /, %
```

- You can also first declare & define two static values (i=125, j=5), test the calculator, and then add the `scanf` statement for keyboard input.
- Sample input: 125 5
- Sample output:

```
: Enter two numbers: 125 5
: 125 + 5 = 130
: 125 - 5 = 120
: 125 * 5 = 625
: 125 / 5 = 25
: 125 % 5 = 0
```

5.1 Solution:

Input:

```
echo "125 5" > input
cat input
```

```
125 5
```

```
#include <stdio.h>
```

```
int main() {
    int a, b;
    printf("Enter two numbers: ");
    scanf("%d%d", &a, &b);
    printf("%d %d\n", a, b);

    printf("%d + %d = %d\n", a, b, a + b);
    printf("%d - %d = %d\n", a, b, a - b);
    printf("%d * %d = %d\n", a, b, a * b);
    printf("%d / %d = %d\n", a, b, a / b);
    printf("%d %% %d = %d\n", a, b, a % b);
```



```
    return 0;
}
```

```
Enter two numbers: 125 5
125 + 5 = 130
125 - 5 = 120
125 * 5 = 625
125 / 5 = 25
125 % 5 = 0
```

6 Boolean algebra

- What is algebra about?³
- Why algebra? Algebra allows you to form small worlds with fixed laws so that you know exactly what's going on - what the output must be for a given input. This certainty is what is responsible for much of the magic of mathematics.
- Boole's (or Boolean) algebra, or the algebra of **logic**, uses the values of **TRUE** (or 1) and **FALSE** (or 0) and the operators **AND** (or "conjunction"), **OR** (or "disjunction"), and **NOT** (or "negation").
- **Truth tables** are one way of showing Boolean relationships (there are many other ways, some more intuitive than others⁴):

Table 3: Conjunction: 'p AND q' for all values of p,q

p	q	p AND q
TRUE	TRUE	TRUE
TRUE	FALSE	FALSE
FALSE	TRUE	FALSE
FALSE	FALSE	FALSE

³Algebra is a branch of mathematics that deals with **symbols** and the **rules** for combining them to express **relationships** and solve **equations**.

⁴**Logic Gates** represent Boolean expressions through digital circuits - the basis of computers. **Set theory** interprets Boolean operations as union, intersection, and complement. **Venn diagrams** visualize Boolean operations using overlapping circles. **Binary arithmetic** uses Boolean values 0 and 1 in computational operations = truth tables.

Table 4: Disjunction: ‘p OR q’ for all values of p,q

p	q	p OR q
TRUE	TRUE	TRUE
TRUE	FALSE	TRUE
FALSE	TRUE	TRUE
FALSE	FALSE	FALSE

Table 5: Inverse: ‘p’ and ‘NOT p’ for all values of p

p	NOT p
TRUE	FALSE
FALSE	TRUE

7 Exploring Boolean algebra

Let’s explore Boolean algebra in three different ways to help absolutely everyone get a picture of what it means.

7.1 Conjunction: Logic gates (digital circuits)

- Go to CircuitVerse (circuitverse.org) and sign up for free with your Google Mail account.
- Create a logic gate that represents the operation **p AND q** for varying values of **p** and **q**:
 1. Select two **input** values.
 2. Select the "Logical conjunction" gate ("D").
 3. Select an **output** value.
 4. Combine the elements.
 5. Run through the truth values of the table.
 6. If you want to keep it, save it as a project.
- Your logic gate should look like this:
(Project link)

7.2 Disjunction: Set theory (vector algebra)

- Set up the sets in an R language code block




Figure 4: Source: CircuitVerse project

```
p <- c(TRUE, TRUE, FALSE, FALSE) # set of p values
q <- c(TRUE, FALSE, TRUE, FALSE) # set of q values
tt <- data.frame("p"=p,"q"=q)    # truth table setup
print(tt,row.names=FALSE)
```

```
      p      q
TRUE  TRUE
TRUE FALSE
FALSE TRUE
FALSE FALSE
```

- Compute the

```
tt["p OR q"] <- p | q # check p OR q for every row of the table
print(tt,row.names=FALSE)
```

```
      p      q p OR q
TRUE  TRUE  TRUE
TRUE FALSE  TRUE
FALSE TRUE   TRUE
FALSE FALSE FALSE
```

7.3 Inverse: Set theory diagram (Euler diagram)

- The box is the universe.

p is represented by a circle inside the box.




Figure 5: Euler diagram: p in the universe

- What is $\text{NOT } p$ ($\neg p$)?

$\text{NOT } p$ is the universe outside of p .




Figure 6: Euler diagram: p and $\text{NOT } p$ in the universe

- Therefore, what is the Boolean equation for the universe?

The universe is $p \text{ AND } (\text{NOT } P)$.

8 PRACTICE Boolean logic test

- Go to Google Cloud shell (ide.cloud.google.com) and run the following command on the shell (-0 is a big-Oh, not a zero):




Figure 7: Euler diagram: $p \text{ AND } (\text{NOT } p) = \text{Universe}$

```
wget -O boolean.c tinyurl.com/predict-boolean
```

- Open the file `boolean.c` in the `nano` editor.
- Write the answer you expect in the place of the `XX` characters. Then compile and run the program to see if you were right or wrong.
- Code template (this will NOT compile!):

```
#include <stdio.h>

int main() {
    int x = 1, y = 0, z = 5;

    // Below, replace '?' by what you expect the Boolean expression
    // result in - for example for the first statement, compute (in
    // your head) '1 && 0' (which is 1 AND 0 in the truth table, and
    // replace '?' by what you think the result will be.
    // EXAMPLE: x && x = 1 && 1 = TRUE = 1
    // printf("%d == %d\n", x && y, 1);

    printf("%d == %d\n", x && y, ?);
    printf("%d == %d\n", x || y, ?);
    printf("%d == %d\n", x == y, ?);
    printf("%d == %d\n", !x, ?);
    printf("%d == %d\n", z > x && y < z, ?);

    return 0;
}
```

8.1 Solution:

```
#include <stdio.h>

int main() {
    int x = 1, y = 0, z = 5;

    // Below, replace '?' by what you expect the Boolean expression
    // result in - for example for the first statement, compute (in
    // your head) '1 && 0' (which is 1 AND 0 in the truth table, and
    // replace '?' by what you think the result will be.
```

```
// EXAMPLE: x && x = 1 && 1 = TRUE = 1
// printf("%d == %d\n", x && y, 1);

printf("%d == %d\n", x && y, 0);
printf("%d == %d\n", x || y, 1);
printf("%d == %d\n", x == y, 0);
printf("%d == %d\n", !x, 0);
printf("%d == %d\n", z > x && y < z, 1);

return 0;
}

0 == 0
1 == 1
0 == 0
0 == 0
1 == 1
```

9 Expanding Boolean algebra

- Using the three basic operators, other operators can be built. In electronics, and modeling, the "exclusive OR" operator or "XOR", is e.g. equivalent to $(p \text{ AND NOT } q) \text{ OR } (\text{NOT } p \text{ AND } q)$.

Table 6: Exclusive OR: 'p XOR q' and its derivation

p	q	p XOR q	P = p AND (NOT q)	Q = (NOT p) AND q	P OR Q
TRUE	TRUE	FALSE	FALSE	FALSE	FALSE
TRUE	FALSE	TRUE	TRUE	FALSE	TRUE
FALSE	TRUE	TRUE	FALSE	TRUE	TRUE
FALSE	FALSE	FALSE	FALSE	FALSE	FALSE

- XOR is the operator that I've used in BPMN models for pseudocode as a gateway operator - only one of its outcomes can be true but never both of them:

[width=.9]../img/problem_solving

- How could you show the truth of the equivalence of $p \text{ XOR } q$ and $(p \text{ AND NOT } q) \text{ OR } (\text{NOT } p \text{ AND } q)$?

You can show this computationally by going through all $p, q \in \{0,1\}$ - we're using a `for` loop here but we could also do it manually with values $p0=0, q0=0, p1=0, q1=1$ or as array values.

- In R (vectorized Boolean operations):

```
## set up truth table with values for p and q
tt <- data.frame("p"=c(TRUE,TRUE,FALSE,FALSE),"q"=c(TRUE,FALSE,TRUE,FALSE))

## compute (p AND NOT q) OR (NOT p AND q) and add it to the table
tt["p XOR q"] <- (p & !q) | (!p & q)

## print resulting truth table
print(tt,row.names=FALSE)
```

p	q	p XOR q
TRUE	TRUE	FALSE
TRUE	FALSE	TRUE
FALSE	TRUE	TRUE
FALSE	FALSE	FALSE

- In C, TRUE is 1 and FALSE is 0 (we're going to analyze this later):

```
// non-loop approach without arrays
int p0=0,q0=0,p1=0,q1=1,p2=1,q2=0,p3=1,q3=1;
printf("\n%d %d %d %d\n",
      (p0 && !q0) || (!p0 && q0),
      (p1 && !q1) || (!p1 && q1),
      (p2 && !q2) || (!p2 && q2),
      (p3 && !q3) || (!p3 && q3));

// print p XOR q - the answer should be 0 1 1 0
for (int i=0;i<2;++i) { // 00 01 10 11
  for (int j=0;j<2;++j) {
    printf("%d ", (i && !j) || (!i && j)); //
  }
}
```

```
// declare truth values p,q as array
```

```

int a[] = {0,1};
printf("\n%d %d %d %d\n",
      (a[0] && !a[0]) || (!a[0] && a[0]),
      (a[0] && !a[1]) || (!a[0] && a[1]),
      (a[1] && !a[0]) || (!a[1] && a[0]),
      (a[1] && !a[1]) || (!a[1] && a[1]));

```

```

0 1 1 0
0 1 1 0
0 1 1 0

```

- Result:

Each row shows the results of (p AND NOT q) OR (NOT p AND q) from left to right for all values of p and q: the same as p XOR q:

Table 7: ‘p XOR q’ with Boolean values and in C (with 0,1)

p	q	p XOR q	printf
TRUE	TRUE	FALSE	0
TRUE	FALSE	TRUE	1
FALSE	TRUE	TRUE	1
FALSE	FALSE	FALSE	0

- In R:

```

## set up truth table with values for p and q
tt <- data.frame("p"=c(TRUE,TRUE,FALSE,FALSE),"q"=c(TRUE,FALSE,TRUE,FALSE))

```

```

## compute (p AND NOT q) OR (NOT p AND q) and add it to the table
tt["p XOR q"] <- (p & !q) | (!p & q)

```

```

## print resulting truth table
print(tt,row.names=FALSE)

```

```

      p      q p XOR q
TRUE TRUE  FALSE
TRUE FALSE  TRUE
FALSE TRUE   TRUE
FALSE FALSE FALSE

```

- Algebraic operations are way more elegant and insightful than truth tables. Watch "Proving Logical Equivalences without Truth Tables" (2012) as an example.

10 Order of operator operations (codealong)

- In compound operations (multiple operators), you need to know the order of operator precedence.
- C has almost 50 operators - more than keywords. The most unusual are compound increment/decrement operators⁵:

Table 8: Compound prefix and postfix operators in C

STATEMENT	COMPOUND	PREFIX	POSTFIX
<code>i = i + 1;</code>	<code>i += 1;</code>	<code>++i;</code>	<code>i++;</code>
<code>j = j - 1;</code>	<code>j -= 1;</code>	<code>--i;</code>	<code>i--;</code>

- `++` and `--` have side effects: they modify the values of their operands: the *prefix* operator `++i` increments `i+1` and then fetches the value `i`:

```
int i = 1;
printf("i is %d\n", ++i); // increments i, then prints "i is 2"
printf("i is %d\n", i);   // prints "i is 2"
```

```
i is 2
i is 2
```

- The *postfix* operator `j++` also means `j = j + 1` but here, the value of `j` is fetched, and then incremented.

```
int j = 1;
printf("j is %d\n", j++); // prints "j is 1" then increments
printf("j is %d\n", j);   // prints "j is 2"
```

```
j is 1
j is 2
```

⁵These operators were inherited from Ken Thompson's earlier B language. They are not faster just shorter and more convenient.

- Here is another illustration with an assignment of post and prefix increment operators:

```
int num1 = 10, num2 = 0;
puts("start: num1 = 10, num2 =0");

num2 = num1++; // assign num1 to num2 and then add 1 to num1
printf("postfix: num2 = num1++, so num2 = %d, num1 = %d\n", num2, num1);

num1 = 10;      // reset num1 to 10
num2 = ++num1;  // add 1 to num1 and then assign it to num2
printf("prefix:  num2 = ++num1, so num2 = %d, num1 = %d\n", num2, num1);

start: num1 = 10, num2 =0
postfix: num2 = num1++, so num2 = 10, num1 = 11
prefix:  num2 = ++num1, so num2 = 11, num1 = 11
```

- The table below shows a partial list of operators and their order of precedence from 1 (highest precedence, i.e. evaluated first) to 5 (lowest precedence, i.e. evaluated last)

Table 9: Order of precedence of arithmetic operators in C

ORDER	OPERATOR	SYMBOL	ASSOCIATIVITY
1	increment (postfix)	++	left
	decrement (postfix)	--	
2	increment (prefix)	++	right
	decrement (prefix)	--	
	unary plus	+	
	unary minus	-	
3	multiplicative	* / %	left
4	additive	+ -	left
5	assignment	= *= /= %= += -=	right

- Left/right *associativity* means that the operator groups from left/right. Examples:
- Write some of these out yourself and run examples. I found %= quite challenging: a modulus and assignment operator. `i %= j` computes `i%j` (i modulus j) and assigns it to `i`.

Table 10: Associativity of operators in C

EXPRESSION	EQUIVALENCE	ASSOCIATIVITY
$i - j - k$	$(i - j) - k$	left
$i * j / k$	$(i * j) / k$	left
$- + j$	$- (+j)$	right
$i \% = j$	$i = (i \% j)$	right
$i += j$	$i = (j + 1)$	right

- What is the value of `i = 10` after running the code below?

```
int i = 10, j = 5;
i %= j; // compute modulus of i and j and assigns it to i
printf("i was 10 and is now %d = 10 %% 5\n", i);
```

i was 10 and is now 0 = 10 % 5

11 PRACTICE Predict the output

- Go to Google Cloud shell (ide.cloud.google.com) and run the following command on the shell (-0 is a big-Oh, not a zero):

```
wget -0 predict.c tinyurl.com/predict-output
```

- Open the file `predict.c` in the `nano` editor.
- Write the answer you expect in the place of the `XX` characters. Then compile and run the program to see if you were right or wrong.
- Code template:

```
#include <stdio.h>

int main() {
    int a = 5, b = 10, c;

    // USING THE VALUES FOR a AND b, COMPUTE c IN YOUR HEAD
    // THEN ENTER THE VALUE INSTEAD OF THE QUESTION MARK ?
    // THEN COMPILE AND RUN TO SEE IF YOU GUESSED RIGHT.
    // EXAMPLE: c = b * a = 10 * 5;
```

```

// printf("1. c = %d == %d\n", c, 50);

c = a + b * 2;
printf("1. c = %d == %d\n", c, ?); // what is c?

c = (a + b) * 2;
printf("2. c = %d == %d\n", c, ?);

c = b / a + 3;
printf("3. c = %d == %d\n", c, ?);

c = ++a + b--;
printf("4. a = %d == %d, b = %d == %d, c = %d == %d\n",
      a, ?, b, ?, c, ?);

return 0;
}

```

11.1 Solution:

```

#include <stdio.h>

int main() {
    int a = 5, b = 10, c;

    // USING THE VALUES FOR a AND b, COMPUTE c IN YOUR HEAD
    // THEN ENTER THE VALUE INSTEAD OF THE QUESTION MARK ?
    // THEN COMPILE AND RUN TO SEE IF YOU GUESSED RIGHT.
    // EXAMPLE: c = b * a = 10 * 5:
    // printf("1. c = %d == %d\n", c, 50);

    c = a + b * 2;
    printf("1. c = %d == %d\n", c, 25); // replace XX by your guess

    c = (a + b) * 2;
    printf("2. c = %d == %d\n", c, 30);

    c = b / a + 3;
    printf("3. c = %d == %d\n", c, 5);
}

```

```

    c = ++a + b--;
    printf("4. a = %d == %d, b = %d == %d, c = %d == %d\n",
a, 6, b, 9, c, 16);

    return 0;
}

```

1. c = 25 == 25
2. c = 30 == 30
3. c = 5 == 5
4. a = 6 == 6, b = 9 == 9, c = 16 == 16

12 Booleans in C

- C evaluates all non-zero values as **TRUE** (1), and all zero values as **FALSE** (0):

```

if (3) {
    puts("3 is TRUE"); // non-zero expression
}
if (!0) puts("0 is FALSE"); // !0 is literally non-zero

3 is TRUE
0 is FALSE

```

- The Boolean operators AND, OR and NOT are represented in C by the logical operators **&&**, **||** and **!**, respectively

13 ! operator (logical NOT)

- The **!** operator is a "unary" operator that is evaluated from the left. It is **TRUE** when its argument is **FALSE** (0), and it is **FALSE** when its argument is **TRUE** (non-zero).
- If **i = 100**, what is **!i**?

The Boolean value of 100 is **TRUE**. Therefore, **!100 = !TRUE = FALSE**.

- If **j = 1.0e-15**, what is **!j**?

The Boolean value of `1.0e-15` is TRUE. Therefore, `!1.0e-15`
`= !TRUE = FALSE`.

- Let's check! You can validate these arguments computationally:

```
// declare and assign variables
int i = 100;
double j = 1.e-15;
// print output
printf("!%d is %d because %d is non-zero!\n", i, !i, i);
printf("!(%.1e) is %d because %.1e is non-zero!\n", j, !j, j);

!100 is 0 because 100 is non-zero!
!(1.0e-15) is 0 because 1.0e-15 is non-zero!
```

14 && operator (logical AND)

- Evaluates a Boolean expression from left to right
- Its value is TRUE if and only if **both** sides of the operator are TRUE
- Example: guess the outcome first

```
if ( 3 > 1 && 5 == 10 )
    printf("The expression is TRUE.\n");
else
    printf("The expression is FALSE.\n");
```

The expression is FALSE.

- Example: guess the outcome first

```
if (3 < 5 && 5 == 5 )
    printf("The expression is TRUE.\n");
else
    printf
        ("The expression is FALSE.\n");
```

The expression is TRUE.

15 || operator (logical OR)

- Evaluates a Boolean expression from left to right
- It is **FALSE** if and only **both** sides of the operator are **FALSE**
- It is **TRUE** if either side of the operator is **TRUE**
- Example: guess the outcome first

```
if ( 3 > 5 || 5 == 5 )
    printf("The expression is TRUE.\n");
else
    printf("The expression is FALSE.\n");
```

The expression is TRUE.

- Example: guess the outcome first

```
if ( 3 > 5 || 6 < 5 )
    printf("The expression is TRUE.\n");
else
    printf("The expression is FALSE.\n");
```

The expression is FALSE.

16 PRACTICE Logical operators

- Go to Google Cloud shell (ide.cloud.google.com) and run the following command on the shell (-O is a big-Oh, not a zero):

```
wget -O logical.c tinyurl.com/logical-output
```

- Open the file `logical.c` in the `nano` editor.
- Complete the `printf` statements for ... in each of the code blocks according to the comments, and guess the output (0 or 1) by replacing the XX with your answer.
- Compile and run the program to see if you were right.
- Code template:

```

/*****
 * logical.c: Write and predict logical results *
 * Input: None. Output: integer values          *
 * Author: Marcus Birkenkrahe GPLv3            *
 * Date: 02/24/2025                             *
 *****/
#include <stdio.h>

int main(void)
{
    // variable declarations
    int i, j, k;

    // TRANSLATE THE SENTENCE IN THE COMMENT INTO A LOGICAL EXPRESSION
    // AND PUT THE CODE WHERE THE ... ARE. GUESS THE VALUE OF THE
    // LOGICAL EXPRESSION AND REPLACE THE ? WITH IT.
    // EXAMPLE: Check if i is smaller than j => 'i < j'
    // FOR i = 10 and j = 5: 10 < 5 is TRUE: ? => 1

    // Check if '(NOT i)' is smaller than j
    i = 10, j = 5;
    printf("%d = %d\n", ..., ?);

    // Check the value of 'NOT(NOT (i)) + NOT(j)'
    i = 2, j = 1;
    printf("%d = %d\n", ..., ?);

    // Check if this is true: 'NOT(x + y) = NOT(x) + NOT(y)'
    i = 2, j = 1;
    printf("%d = %d\n", ..., ?);

    // Compute 'i AND j OR k'
    i = 5, j = 0, k = -5;
    printf("%d = %d\n", ..., ?);

    // Compute 'i smaller than j OR k'
    i = 1, j = 2, k = 3;
    printf("%d = %d\n", ..., ?);

    return 0;
}

```

```
}
```

16.1 Solution

```
/* *****
 * logical.c: Write and predict logical results *
 * Input: None. Output: integer values          *
 * Author: Marcus Birkenkrahe GPLv3             *
 * Date: 02/24/2025                             *
 * *****/
#include <stdio.h>

int main(void)
{
    // variable declarations
    int i, j, k;

    // TRANSLATE THE SENTENCE IN THE COMMENT INTO A LOGICAL EXPRESSION
    // AND PUT THE CODE WHERE THE ... ARE. GUESS THE VALUE OF THE
    // LOGICAL EXPRESSION AND REPLACE THE ? WITH IT.
    // EXAMPLE: Check if i is smaller than j => 'i < j'
    // FOR i = 10 and j = 5: 10 < 5 is TRUE: ? => 1

    // Check if '(NOT i)' is smaller than j, for i=10 and j=5
    i = 10, j = 5;
    printf("%d = %d\n", !i < j, 1); // !10 is 0, and 5 > 0 is TRUE (1)

    // Check the value of 'NOT(NOT (i)) + NOT(j)', for i=2 and j=1
    i = 2, j = 1;
    printf("%d = %d\n", !!i + !j, 1); // !!2 = !0 = 1, !1 = 0, 1 + 0 = 1

    // Check if this is true: 'NOT(x + y) = NOT(x) + NOT(y)'
    i = 2, j = 1;
    printf("%d = %d\n", !(i+j)==!i+!j, 1); // !(2+1)=0 == !2+!1 = 0

    // Compute 'i AND j OR k', for i=5, j=0, k=-5
    i = 5, j = 0, k = -5;
    printf("%d = %d\n", i && j || k, 1); // 5 && 0 = 0, 0 || -5 = 0 || 1 = 1

    // Compute 'i < j OR k', for i=1, j=2, k=3
```

```

    i = 1, j = 2, k = 3;
    printf("%d = %d\n", i < j || k, 1); // (i < j) = 1, 3 is TRUE, 1 || 1 is 1

    return 0;
}

1 = 1
1 = 1
1 = 1
1 = 1
1 = 1

```

17 Proving Boolean equivalence with code

- Problem: show that $p \text{ XOR } q$ and $(p \text{ AND NOT } q) \text{ OR } (\text{NOT } p \text{ AND } q)$ are equivalent.
- Pseudocode:

ALGORITHM: compute the expressions:

A. $(p \text{ XOR } q)$

B. $((p \text{ AND NOT } q) \text{ OR } (\text{NOT } p \text{ AND } q))$

Input: all truth values of p and q (stored in a file)

|p0=0|q0=0|

|p0=0|q0=1|

|p0=1|q0=0|

|p0=1|q0=1|

Output: evaluation of A and B

Begin:

 // Declare values to Boolean variables

 // Read in values from input file

 // Print $A = p \text{ XOR } q$ for all values of p and q

 // Print $B = (p \text{ AND NOT } q) \text{ OR } (\text{NOT } p \text{ AND } q)$ for all values of p and q

End

- Create the input file **demorgan** (or generate it manually on Windoze):

```

echo "0 0" > demorgan
echo "0 1" >> demorgan
echo "1 0" >> demorgan
echo "1 1" >> demorgan
cat demorgan

```

- C code (without loops or arrays)

```

// Declare Boolean variables
int p0,p1,p2,p3,q0,q1,q2,q3;

// Read in values from input file
scanf("%d%d%d%d%d%d%d", &p0,&q0,&p1,&q1,&p2,&q2,&p3,&q3);

// Check that input was correctly read
printf("%d%d\n%d%d\n%d%d\n%d%d\n", p0,q0,p1,q1,p2,q2,p3,q3);

// Print A = p XOR q for all values of p and q
printf("p XOR q: %d %d %d %d\n",0,1,1,0);

// Print B = (p AND NOT q) OR (NOT p AND q) for all values of p and q
printf("p = %d, q = %d, (p AND !q) OR (!p AND q) = %-2d\n",p0,q0,(p0 && !q0) || (!p0 && q0));
printf("p = %d, q = %d, (p AND !q) OR (!p AND q) = %-2d\n",p1,q1,(p1 && !q1) || (!p1 && q1));
printf("p = %d, q = %d, (p AND !q) OR (!p AND q) = %-2d\n",p2,q2,(p2 && !q2) || (!p2 && q2));
printf("p = %d, q = %d, (p AND !q) OR (!p AND q) = %-2d\n",p3,q3,(p3 && !q3) || (!p3 && q3));

printf("\n.....Q.E.D.\n");

00
01
10
11
p XOR q: 0 1 1 0
p = 0, q = 0, (p AND !q) OR (!p AND q) = 0
p = 0, q = 1, (p AND !q) OR (!p AND q) = 1
p = 1, q = 0, (p AND !q) OR (!p AND q) = 1
p = 1, q = 1, (p AND !q) OR (!p AND q) = 0

.....Q.E.D.

```

- You could also dispense with reading the values (since they're constant) and set the values in the code - this makes it shorter:

```
// Declare and assign values to Boolean variables
int p0=0,q0=0,p1=0,q1=1,p2=1,q2=0,p3=1,q3=1;

// Print A = p XOR q for all values of p and q
printf("%d %d %d %d\n",0,1,1,0);

// Print B = (p AND NOT q) OR (NOT p AND q) for all values of p and q
printf("%-2d", (p0 && !q0) || (!p0 && q0));
printf("%-2d", (p1 && !q1) || (!p1 && q1));
printf("%-2d", (p2 && !q2) || (!p2 && q2));
printf("%-2d", (p3 && !q3) || (!p3 && q3));

printf("\n.....Q.E.D.\n");

0 1 1 0
0 1 1 0
.....Q.E.D.
```

18 Checking for upper and lower case

- Characters are represented by ASCII⁶ character sets
- E.g. a and A are represented by the ASCII codes 97 and 65, resp.
- Let's check that.

```
echo "a A" > ascii
cat ascii
```

In ??, two characters are scanned and then printed as characters and as integers:

```
char c1, c2;
scanf("%c %c", &c1, &c2);
printf("The ASCII value of %c is %d\n", c1, c1);
printf("The ASCII value of %c is %d\n", c2, c2);
```

⁶ASCII stands for the American Standard Code for Information Interchange.

The ASCII value of is 127
The ASCII value of `E` is 69

- What happens if you use the format specifier `%c%c` for `scanf`? Try it.

Answer: Instead of the ASCII value for `'A'` you get the ASCII value for the space, because after picking up the `a`, `scanf` finds the space (it only expects a string literal, and the space is one of those).

- User-friendly programs should use compound conditions to check for both lower and upper case letters:

```
if (response == 'A' || response == 'a') // accept if either a or A is response
```

19 PRACTICE Checking for upper and lower case

1. Get the file `letter.c` from the command-line and open it in `nano`:

```
wget -O letter.c tinyurl.com/letter-template
```

2. `letter.c` accepts a character `letter` as input, checks whether the letter is `b` or not, and prints a corresponding message:

```
/******  
* letter.c: check character input          *  
* Input: two character values              *  
* Output: Input is 'b' or not 'b'         *  
* Author: Marcus Birkenkrahe GPLv3        *  
* Date: 02/27/2025                        *  
*****/  
#include <stdio.h>  
  
int main(void)  
{  
    // TODO: declare character variables c1 and c2  
    char letter;  
    // TODO: get two characters c1 and c2 from the keyboard  
    scanf("%c", &letter);  
    // TODO: check whether 'letter' is the same as 'b'
```

```

if (letter == 'b')
printf("Input is 'b'.\n");
else
printf("Input is NOT 'b'.\n");

return 0;
}

```

Input is NOT 'b'.

3. Compile the file, rename the object file to `letter`, and run it with different letters to check if it works.

```

gcc letter.c -o letter
./letter

```

4. Copy the file `letter.c` to a file `letter2.c` and open it:

```

cp -v letter.c letter2.c

```

5. Change the **condition** from checking only for equality with lower-case `b` to checking for equality with lower- or upper-case:

```

/*****
* letter2c: check character input      *
* Input: two character values          *
* Output: Input is 'b' or 'B'         *
* Author: Marcus Birkenkrahe GPLv3    *
* Date: 02/27/2025                    *
*****/

```

```

#include <stdio.h>

```

```

int main(void)
{
    char letter;
    scanf("%c", &letter);

    if (letter == 'b' || letter == 'B')
        printf("Input is 'b' or 'B'.\n");
}

```



```

        else
            printf("Input is NOT 'b' or 'B'.\n");

        return 0;
    }

```

Input is NOT 'b' or 'B'.

6. Once more, compile `letter2.c`, rename the object file to `letter2`, and run it for different character input values to check it.

20 PRACTICE ASCII code of letters

1. Create a file `ascii.c`
2. Get two letters `c1` and `c2` from the keyboard.
3. Print the letters both as characters, and as ASCII values.
4. Sample input and output:

Input: b B

Output:

The ASCII value of b is 98.

The ASCII value of B is 66.

20.1 Solution:

```

/*****
* ascii.c: print ASCII value of characters      *
* Input: two character values                  *
* Output: ASCII value (int) of character (char) *
* Author: Marcus Birkenkrahe GPLv3           *
* Date: 02/27/2025                           *
*****/
#include <stdio.h>

int main(void)
{
    char c1, c2;

```

```

scanf("%c %c", &c1, &c2);

printf("The ASCII value of %c is %d.\n", c1, c1);
printf("The ASCII value of %c is %d.\n", c2, c2);
return 0;
}

```

The ASCII value of 1 is 49.
The ASCII value of 2 is 50.

- Testing:

```

gcc ascii.c -o ascii
./ascii < input

```

The ASCII value of 1 is 49.
The ASCII value of 2 is 50.

- Input file:

```

echo "b B" > input
cat input

```

b B

21 Checking for a range of values

- To validate input, you often need to check a range of values
- This is a common use of compound conditions, logical and relational operators
- We first create an input file `num` with a number in it.

```

echo 11 > num
cat num

```

- What does the code below do? Will it run? What will the output be for our choice of input?

```

int response = 0; // declare and initialize integer

scanf("%d", &response); // scan integer input

// check if input was in range or not
if ( response < 1 || response > 10 ) {
    puts("Number not in range.");
} else {
    puts("Number in range.");
}

```

Number not in range.

- How can you translate a range like $! [1, 10]$ into a conditional expression? It means that we want to test if a number is outside of the closed interval $[1, 10]$.
- The numbers that fulfil this condition are smaller than 1 or greater than 10, hence the condition is $x < 1 \ || \ x > 10$.
- This is more conveniently written as $x < 1 \ || \ 10 < x$.

22 PRACTICE Checking for a range of values

1. Get the template for `range.c` from the command-line:

```
wget -O range.c tinyurl.com/range-template
```

2. Define three integer variables `i`, `m`, and `n`, get their values from the keyboard, and check if the input value for `i` is in the interval $[m, n]$.
3. Complete, compile and run the file:

```

// range.c: compute condition with range
// input: none. output: Boolean
// author: Marcus Birkenkrahe GPLv3
// date: 2/27/25
#include <stdio.h>

```

```

int main(void)
{
    int i, m, n;
    scanf("%d %d %d", &i, &m, &n);

    if (m <= i && i < n)
        printf("%d is in the interval [%d,%d).\n", i, m, n);
    else
        printf("%d is NOT in the interval [%d,%d).\n", i, m, n);

    return 0;
}

```

0 is NOT in the interval [4096,0).

4. Compile **range.c**, rename the object file **range**, and run it with the sample values: 5, 0, 10 for i, m, n - testing if 5 is in [0,10).
5. Run **range** for different input values:

```

i = -5   m = 0   n = 10
i = 11   m = 0   n = 10
i = 0    m = 0   n = 10
i = 10   m = 0   n = 10

```

6. How would you change the condition to check if the input variable i is outside of [m,n) ?

22.1 Solution:

```

// range.c: compute condition with range
// input: none. output: Boolean
// author: Marcus Birkenkrahe GPLv3
// date: 2/27/25
#include <stdio.h>

int main(void)
{
    int i, m, n;
    scanf("%d %d %d", &i, &m, &n);

```

```

    if (i < m || n <= i)
        printf("%d is NOT in the interval [%d,%d).\n", i, m, n);
    else
        printf("%d is in the interval [%d,%d).\n", i, m, n);

    return 0;
}

0 is NOT in the interval [4096,0).

```

Testing:

```

echo "5 0 10" > input
cat input

5 0 10

```

23 PRACTICE Chained expression

In C, the expression `i < j < k` is perfectly legal but it does NOT check if `j` is between `i` and `k`, $i \in (i, k)$.

The relational operator `<` is evaluated from the left: `i < j` is computed. It is either 1 (TRUE) or 0 (FALSE).

Next, `0 < k` or `1 < k` is checked.

1. Get the template for `chain.c` from the command-line:

```
wget -O chain.c tinyurl.com/chain-template
```

2. Complete, compile and run the file:

```

// chain.c: compute condition
// input: none. output: Boolean
// author: Marcus Birkenkrahe GPLv3
// date: 2/27/25
#include <stdio.h>

int main(void)
{

```

```

    int i = 5, j = 1, k = 100;

    if (i < j < k)
        printf("TRUE: %d < %d < %d\n", i, j, k);
    else
        printf("NOT TRUE: %d < %d < %d\n", i, j, k);

    return 0;
}

```

TRUE: 5 < 1 < 100

3. Fix the code so that the output is correct. Then test it for different values of i, j, k.

23.1 Solution:

```

// chain.c: compute condition
// input: none. output: Boolean
// author: Marcus Birkenkrahe GPLv3
// date: 2/27/25
#include <stdio.h>

int main(void)
{
    int i = 5, j = 1, k = 100;

    if (i < j && j < k)
        printf("TRUE: %d < %d < %d\n", i, j, k);
    else
        printf("NOT TRUE: %d < %d < %d\n", i, j, k);

    return 0;
}

```

NOT TRUE: 5 < 1 < 100

Testing:

```

gcc chain.c -o chain
./chain

```

With input:

```
#include <stdio.h>

int main(void)
{
    int i,j,k;
    scanf("%d %d %d",&i,&j,&k);

    if (i < j && j < k)
        printf("TRUE: %d < %d < %d\n", i, j, k);
    else
        printf("NOT TRUE: %d < %d < %d\n", i, j, k);

    return 0;
}
```

NOT TRUE: 5 < 0 < 10

Input file:

```
echo "1 5 -100" > input
cat input

1 5 -100
```

24 PRACTICE Upload your practice files as a ZIP archive

- ZIP your seven files on the command line as an archive file `operators.zip` and upload it to Canvas.
- On the shell:

```
zip operators.zip calc.c predict.c boolean.c logical.c letter.c range.c chain.c
```

- If you enter `less operators.zip` you will see your files in the archive (leave the `less` screen by typing `q`:

```

aletheia@pop-os:~/GitHub/cc-25/src$ less operators.zip
Press RETURN to continue

Archive:  operators.zip
Length  Method      Size  Cmpr   Date       Time    CRC-32     Name
-----  -
      0  Stored        0    0%  2025-02-22  23:38  00000000   calc.c
    624  Defl:N       296   53%  2025-02-22  23:07  a106cb65   predict.c
    561  Defl:N       267   52%  2025-02-22  23:21  13eb4f30   boolean.c
      0  Stored        0    0%  2025-02-22  23:38  00000000   logical.c
      0  Stored        0    0%  2025-02-22  23:38  00000000   letter.c
      0  Stored        0    0%  2025-02-22  23:38  00000000   range.c
      0  Stored        0    0%  2025-02-22  23:38  00000000   chain.c
-----  -
    1185                563   53%
operators.zip (END)q

```

- If you enter file `operators.zip`, you should see a message confirming that this is Zip archive data.

```

$ file operators.zip
operators.zip: Zip archive data, at least v1.0 to extract, compression method=store

```

25 References

- Davenport/Vine (2015) C Programming for the Absolute Beginner (3ed). Cengage Learning.
- GVSUmath (Aug 10, 2012). Proving Logical Equivalences without Truth Tables [video]. URL: youtu.be/iPbLzl2kMHA.
- Kernighan/Ritchie (1978). The C Programming Language (1st). Prentice Hall.
- King (2008). C Programming - A modern approach (2e). W A Norton.
- Orgmode.org (n.d.). 16 Working with Source Code [website]. URL: orgmode.org